Technical sheet :

## PRUNING CLIPPER (COMPACT MACHINES)



## **Customer benefits**

- Great attachment for easy removal of trees, branches and brushfrom hard to reach areas, overrun pastures, fields and fence rows.

## **Technical characteristics**

- 90° turning radius on each side.
- Branches max 15 cm / 6 in.
- Windshield grid is recommended to work with this attachment.
- Electric predisposition on the boom head is also recommended.
- Works with a remote control to modify the hydraulic action.

[The 3D picture at the top of this page is the reference PRC 1500 / 180R SK - 52728899].



## PRUNING CLIPPER (COMPACT MACHINES) Created on August 2, 2025 at 4:44 AM UTC

Technical characteristics		PRC 1500 / 180 R		
Distance to center of gravity (mm)		494		
Weight				
Overall weight (kg)		300		
Weight and dimensions				
Overall height (mm)	h17	650		
Overall length (mm)	11	1545		
Width (mm)		1200		
Maximum diameter (mm)		150		
Working Parameters				
Required machine equipment				

Machines compatibility	PRC 1500 / 180 R		
All-Tach® 4 point Carriage Euro Carriage	52728899		
4 point Carriage	52741065		
Euro Carriage	52741064		
GCT 3-14	x		
GCT 3-14 +	x		
ULM 412 H	x		
ULM 412 H	x		
ULM 415 H	x		
ULM 415 H	X		

TABLE SYMBOL								
$\times$	No predisposition required		Hydraulic line		Return piping to hydraulic oil tank			
	Electric predisposition		Platform predisposition		Tyre handler, cylinder handler predisposition			





Head Office B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes