Technical sheet:

# PRUNING CLIPPER (COMPACT MACHINES)



### **Technical characteristics**

- 90° turning radius on each side.
- Branches max 15 cm / 6 in.
- · Windshield grid is recommended to work with this attachment.
- Electric predisposition on the boom head is also recommended.
- Works with a remote control to modify the hydraulic action.

[The 3D picture at the top of this page is the reference PRC  $1500 / 180R \, SK - 52728899$ ].

### **Customer benefits**

 Great attachment for easy removal of trees, branches and brushfrom hard to reach areas, overrun pastures, fields and fence rows.



## PRUNING CLIPPER (COMPACT MACHINES) Created on September 9, 2025 at 7:10 PM UTC

Technical characteristics		PRC 1500 / 180 R
Distance to center of gravity (mm)		494
Weight		
Overall weight (kg)		300
Weight and dimensions		
Overall height (mm)	h17	650
Overall length (mm)	11	1545
Width (mm)		1200
Maximum diameter (mm)		150
Working Parameters		
Required machine equipment		Q. ■ ₩

Machines compatibility	PRC 1500 / 180 R			
All-Tach®	52728899			
4 point Carriage Euro Carriage	52741065			
Euro Carriage	52741064			
GCT 3-14	х			
GCT 3-14 +	х			
ULM 412 H	х			
ULM 412 H	Х			
ULM 415 H	X			
ULM 415 H	x			

TABLE SYMBOL								
×	No predisposition required	88	Hydraulic line		Return piping to hydraulic oil tank			
	Electric predisposition		Platform predisposition		Tyre handler, cylinder handler predisposition			





#### **Head Office**

B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes