

Technical sheet :

# **PRUNING CLIPPER (COMPACT MACHINES)**

---



---


## **Technical characteristics**

- 90° turning radius on each side.
- Branches max 15 cm / 6 in.
- Windshield grid is recommended to work with this attachment.
- Electric predisposition on the boom head is also recommended.
- Works with a remote control to modify the hydraulic action.

[The 3D picture at the top of this page is the reference PRC 1500 / 180R SK - 52728899].

## **Customer benefits**

- Great attachment for easy removal of trees, branches and brush from hard to reach areas, overrun pastures, fields and fence rows.

Technical characteristics		PRC 1500 / 180 R	
Distance to center of gravity (mm)		494	
Weight			
Overall weight (kg)		300	
Weight and dimensions			
Overall height (mm)	h17	650	
Overall length (mm)	l1	1545	
Width (mm)		1200	
Maximum diameter (mm)		150	
Working Parameters			
Required machine equipment			

Machines compatibility		PRC 1500 / 180 R	
All-Tach®		52728899	
4 point Cariage		52741065	
Euro Cariage		52741064	
GCT 3-14		X	
GCT 3-14 +		X	
ULM 412 H		X	
ULM 412 H		X	
ULM 415 H		X	
ULM 415 H		X	

TABLE SYMBOL					
	No predisposition required		Hydraulic line		Return piping to hydraulic oil tank
	Electric predisposition		Platform predisposition		Tyre handler, cylinder handler predisposition



 **MANITOU**  
**HANDLING YOUR WORLD**

**Head Office**

B.P. 249 - 430 rue de l'Aubinière  
44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

[www.manitou.com](http://www.manitou.com)



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes