Technical sheet :

PRUNING CLIPPER (COMPACT MACHINES)



Customer benefits

- 90° turning radius on each side.
- Branches ø max 15 cm.
- Use of the windshield grid is recommended.
- An electrical predisposition on the boom head is also recommended.
- Use of remote control.

Technical characteristics

- Excellent accessory for easily removing trees, branches and brush from hard-to-reach areas, overgrown pastures, fields and fence rows.

[La photo 3D en haut de cette page est la référence PRC 1500 / 180R SK - 52728899].



PRUNING CLIPPER (COMPACT MACHINES) Created on 1 May 2024 at 3:23:55 AM UTC

Technical characteristics		PRC 1500 / 180 R
Distance to center of gravity (mm)		494
Weight		
Overall weight (kg)		300
Weight and dimensions		
Overall height (mm)	h17	650
Overall length (mm)	11	1545
Width (mm)		1200
Diameter maximum (mm)		150
Working Parameters		
Machine Equipment		日本

Machines compatibility	PRC 1500 / 180 R		
All-Tach® 4 point Carriage Euro Carriage	52728899		
4 point Carriage	52741065		
Euro Carriage	52741064		
GCT 3-14	x		
GCT 3-14 +	x		
ULM 412 H	x		
ULM 412 H	x		
ULM 415 H	x		
ULM 415 H	X		

TABLE SYMBOL									
\times	No predisposition required		Hydraulic line		Return piping to hydraulic oil tank				
	Electric predisposition		Platform predisposition		Tyre handler, cylinder handler predisposition				





Head Office B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes