

Technical sheet :

TILTING FORKS CARRIAGE



Technical characteristics

- Tilting forks.
- Forks compliant with FEM/ISO standard, forks' length according to model.
- Forks are not included in the PFB, order 2 forks (except for CAT 1020 / 1500 + 2 F 100x40x1200 & CAT 1260 / 5T + F 150x50x1200 reference).

[The 3D picture at the top of this page is the reference CAT 1020 / 1500 + 2 F 100x40x1200 - 52706271].

Customer benefits







- Efficient handling solution.
- Adapted to rough terrain.

| Capacities | | CAT 1020 / 1500 + 2 F 100x40x1200 | CAT 1260 / 5 T + F 150x50x1200 | PFB 20N 1020 | PFB 25N 1020 | PFB 25N 1260 | PFB 35N 1260 | PFB 35N 1470 | PFB 35N 1580 | PFB 45N 1260 | PFB 45N 1670 |
|----------------------------------|-----|-----------------------------------|--------------------------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|
| Capacity (kg) | | 1500 | 5000 | 2000 | 2500 | 2500 | 3500 | 3500 | 3500 | 4500 | 4500 |
| Weight | | | | | | | | | | | |
| Overall weight (kg) | | 137 | 406 | 166 | 71 | 80 | 93 | 117 | 122 | 198 | 252 |
| Weight and dimensions | | | | | | | | | | | |
| Overall height (mm) | h17 | 695 | 677 | 582 | - | - | - | - | - | - | - |
| Overall length (mm) | l1 | 1372 | 1497 | - | - | - | - | - | - | - | - |
| Width (mm) | | 1052 | 1302 | 1052 | 1026 | 1302 | 1302 | 1512 | 1622 | 1286 | 1696 |
| Working Parameters | | | | | | | | | | | |
| Required machine equipment | | ✗ | ✗ | ✗ | ✗ | ✗ | ✗ | ✗ | ✗ | ✗ | ✗ |
| Minimum forks spread (mm) | b5 | 201 | 306 | 216 | - | - | - | - | - | - | - |
| Maximum forks spread (mm) | b5 | 965 | 1150 | 980 | - | - | - | - | - | - | - |
| Available fork dimensions | | | | | | | | | | | |
| 100 x 40 x 1200 | | 53016603 | | 415691 | | | | | | | |
| 125 x 45 x 1200 | | | | | 415835 | | 415618 | | | | |
| 125 x 50 x 1200 | | | | | | | | | | 415652 | |
| 150 x 50 x 1200 | | | 578097 | | | | | | | | |

| Machines compatibility | | CAT 1020 / 1500 + 2 F 100x40x1200 | CAT 1260 / 5 T + F 150x50x1200 | PFB 20N 1020 | PFB 25N 1020 | PFB 25N 1260 | PFB 35N 1260 | PFB 35N 1470 | PFB 35N 1580 | PFB 45N 1260 | PFB 45N 1670 |
|-------------------------------|----------|-----------------------------------|--------------------------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|--------------|
| Reference number | - | 52735505 | 52000814 | 571958 | 571959 | 653744 | 653745 | 653746 | 654407 | 653747 | |
| Skid Steer Carriage reference | - | - | - | 52000825 | - | - | - | - | - | - | - |
| All-Tach® | 52706271 | - | - | - | - | - | - | - | - | - | - |
| 4 point Carriage | 52723636 | - | - | - | - | - | - | - | - | - | - |
| Euro Carriage | 52723637 | - | - | - | - | - | - | - | - | - | - |
| ALT950 | - | - | - | - | - | - | X | - | - | - | - |
| GCT 3-14 | X | - | - | - | - | - | - | - | - | - | - |
| GCT 3-14 + | X | - | - | - | - | - | - | - | - | - | - |
| MLA-T 533-145 V+ - ST5 | - | - | - | - | - | - | X | - | - | - | - |
| MLT 420-60 H | - | - | X | - | - | - | - | - | - | - | - |
| MLT 625-75 H | - | - | - | X | X | - | - | - | - | - | - |
| MLT 630-115 (S1) | - | - | - | - | - | - | X | X | X | - | - |
| MLT 630-115 (S2) | - | - | - | - | - | - | X | X | X | - | - |
| MLT 630-115 V (S1) | - | - | - | - | - | - | X | X | X | - | - |
| MLT 630-115 V (S2) | - | - | - | - | - | - | X | X | X | - | - |
| MLT 630-115 V CP (S1) | - | - | - | - | - | - | X | X | X | - | - |
| MLT 630-115 V CP (S2) | - | - | - | - | - | - | X | X | X | - | - |
| MLT 635-130 PS+ (S1) | - | - | - | - | - | - | X | X | X | - | - |
| MLT 635-130 PS+ (S2) | - | - | - | - | - | - | X | X | X | - | - |
| MLT 635-140 V+ (S1) | - | - | - | - | - | - | X | X | X | - | - |
| MLT 635-140 V+ (S2) | - | - | - | - | - | - | X | X | X | - | - |
| MLT 730-115 V (S1) | - | - | - | - | - | - | X | X | X | - | - |
| MLT 730-115 V (S2) | - | - | - | - | - | - | X | X | X | - | - |
| MLT 730-115 V CP (S1) | - | - | - | - | - | - | X | X | X | - | - |
| MLT 730-115 V CP (S2) | - | - | - | - | - | - | X | X | X | - | - |
| MLT 733-115 | - | - | - | - | - | - | X | X | X | - | - |
| MLT 733-115 (S2) | - | - | - | - | - | - | X | X | X | - | - |
| MLT 733-115 LSU (S1) | - | - | - | - | - | - | X | X | X | - | - |
| MLT 737-130 PS+ (S1) | - | - | - | - | - | - | - | - | - | - | X |
| MLT 738-130 PS+ (S1) | - | - | - | - | - | - | - | - | - | X | X |
| MLT 741-130 PS+ (S1) | - | - | - | - | - | - | - | - | - | X | X |
| MLT 741-140 V+ (S1) | - | - | - | - | - | - | - | - | - | X | X |
| MLT 742-130 PS+ (S1) | - | - | - | - | - | - | - | - | - | X | X |
| MLT 742-140 V+ (S1) | - | - | - | - | - | - | - | - | - | X | X |
| MLT 841-145 PS+ | - | - | - | - | - | - | - | - | - | X | X |
| MLT 850-145 V+ | - | X | - | - | - | - | - | - | - | - | - |
| MLT 937-115 (S1) | - | - | - | - | - | - | - | - | - | X | X |
| MLT 940-140 V+ (S1) | - | - | - | - | - | - | - | - | - | - | X |
| MLT 940-140 V+ (S2) | - | - | - | - | - | - | - | - | - | X | X |
| MLT 1041-145 PS+L | - | - | - | - | - | - | - | - | - | X | X |
| MLFX 625-75 H | - | - | - | X | X | - | - | - | - | - | - |
| MLFX 732 | - | - | - | - | - | - | X | - | - | - | - |
| MLFX 735 T LSU | - | - | - | - | - | - | X | X | X | - | - |
| MLFX 738-130 PS+ (S1) | - | - | - | - | - | - | - | - | - | X | X |
| MLFX 741 T LSU | - | - | - | - | - | - | - | - | - | X | X |
| MLFX 841 - 145 PS+ | - | - | - | - | - | - | - | - | - | X | X |
| MLFX 850-145 V+ | - | X | - | - | - | - | - | - | - | - | - |
| MLFX 1041-145 PS+L | - | - | - | - | - | - | - | - | - | X | X |
| MT 420 H | - | - | X | - | - | - | - | - | - | - | - |
| MT 625 H | - | - | - | X | X | - | - | - | - | - | - |
| MT 625 H Comfort | - | - | - | X | X | - | - | - | - | - | - |
| MT 625 HA | - | - | - | X | X | - | - | - | - | - | - |
| MT 735 75D ST5 | - | - | - | - | - | - | X | X | X | - | - |
| MT 935 75D ST5 | - | - | - | - | - | - | X | X | X | - | - |
| MT 1135 75 D | - | - | - | - | - | - | X | X | X | - | - |
| MT 1135 | - | - | - | - | - | - | X | X | - | - | - |
| MT 1135 H 100D | - | - | - | - | - | - | X | X | X | - | - |
| MT 1335 75D ST5 | - | - | - | - | - | - | X | X | X | - | - |
| MT 1335 100D ST5 | - | - | - | - | - | - | X | X | X | - | - |

| Capacities | | PFB 4SN 2000 | PFB 75MT 1750 | PFB 75MT 2000 | PFB FEM4 1200 |
|----------------------------------|-----|--------------|---------------|---------------|---------------|
| Capacity (kg) | | 4500 | 7500 | 7500 | 6000 |
| Weight | | | | | |
| Overall weight (kg) | | 295 | - | - | - |
| Weight and dimensions | | | | | |
| Overall height (mm) | h17 | - | - | - | - |
| Overall length (mm) | l1 | - | - | - | - |
| Width (mm) | | 2026 | 1834 | 2084 | 1200 |
| Working Parameters | | | | | |
| Required machine equipment | | ✗ | ✗ | ✗ | ✗ |
| Minimum forks spread (mm) | b5 | - | - | - | - |
| Maximum forks spread (mm) | b5 | - | - | - | - |
| Available fork dimensions | | | | | |
| 125 x 50 x 1200 | | 615652 | | | |
| 200 x 60 x 1200 | | | | | 513110 |

| Machines compatibility | PFB 4SN 2000 | PFB 75MT 1750 | PFB 75MT 2000 | PFB FEM4 1200 |
|----------------------------------|--------------|---------------|---------------|---------------|
| Reference number | 653748 | 504107 | 527216 | 732330 |
| Skid Steer Carriage reference | - | - | - | - |
| All-Tach® | - | - | - | - |
| 4 point Carriage | - | - | - | - |
| Euro Carriage | - | - | - | - |
| MLT 737-130 PS+ (S1) | X | - | - | - |
| MLT 738-130 PS+ (S1) | X | - | - | - |
| MLT 741-130 PS+ (S1) | X | - | - | - |
| MLT 741-140 V+ (S1) | X | - | - | - |
| MLT 742-130 PS+ (S1) | X | - | - | - |
| MLT 742-140 V+ (S1) | X | - | - | - |
| MLT 937-115 (S1) | X | - | - | - |
| MLT 940-140 V+ (S1) | X | - | - | - |
| MLT 940-140 V+ (S2) | X | - | - | - |
| MLT 961-160 V+ L | - | X | X | X |
| MLTX 738-130 PS+ (S1) | X | - | - | - |
| MLTX 961-160 V+ L | - | X | X | X |
| MT 1440 | X | - | - | - |
| MT 1440 e | X | - | - | - |
| MT 1440 easy ST5 | X | - | - | - |
| MT 1440 ST5 | X | - | - | - |
| MT 1840 | X | - | - | - |
| MT 1840 e | X | - | - | - |
| MT 1840 easy ST5 | X | - | - | - |
| MT 1840 ST5 | X | - | - | - |
| MTX 1440 | X | - | - | - |
| MTX 1840 | X | - | - | - |
| MLT 737-130 PS+ ST4 OLD | X | - | - | - |
| MLT 741-140 V+ ST4 OLD | X | - | - | - |
| MLT 845-100 H OLD | X | - | - | - |
| MLT 845-120 OLD | X | - | - | - |
| MLT 940-140 V+ ST4 OLD | X | - | - | - |
| MLT 961-145 V+ L OLD | - | X | X | X |
| MLTX 737-130 PS+ OLD | X | - | - | - |
| MLTX 737-130 PS+ (S2) OLD | X | - | - | - |
| MLTX 741-140 V+ S1 OLD | X | - | - | - |
| MLTX 845-120 OLD | X | - | - | - |
| MLTX 845-120 H OLD | X | - | - | - |
| MLTX 961-145 V+ L OLD | - | X | X | X |
| MT 1440 A ST5 OLD | X | - | - | - |
| MT 1440 HA ST5 OLD | X | - | - | - |
| MT 1840 A ST5 S1 OLD | X | - | - | - |
| MT 1840 HA ST4 OLD | X | - | - | - |
| MT 1840 HA ST5 S1 OLD | X | - | - | - |
| MTX 1440 A OLD | X | - | - | - |
| MTX 1840 A OLD | X | - | - | - |

| TABLE SYMBOL | | | | | |
|---|----------------------------|---|-------------------------|---|---|
|  | No predisposition required |  | Hydraulic line |  | Return piping to hydraulic oil tank |
|  | Electric predisposition |  | Platform predisposition |  | Tyre handler, cylinder handler predisposition |



Head Office

B.P. 249 - 430 rue de l'Aubinière
44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes