Technical sheet :

FLOATING FORKS CARRIAGE



Customer benefits

- Carriage adapted to uneven ground.
- Pin-type forks + side leveling = very easy pallet collection in all conditions
- Must-have on construction yards.

Technical characteristics

- Pin-type forks with side-movement lock.
- Forks mounted on a mobile bar with leveling function.
- Welded load backrest (MT, MLT) / bolted backrest (MRT, MHT).
- Note: road circulation kit mandatory in Italy. Contact your dealer.
- Note: road circulation kit mandatory in Germany on MRT Vision/ Vision+. Contact your dealer.



FLOATING FORKS CARRIAGE Created on November 24, 2024 at 7:14 AM UTC

Capacity (kg) 7000 5500 Weight and dimensions Comparison Comparison Width (mm) 1030 1300 1300 Working Parameters Comparison Comparison Comparison Machine Equipment Comparison Comparison Comparison 120 x 60 x 1200 Comparison Comparison Comparison	Capacities	TFF 7t	TFF 5.5t
Width (mm) 1030 1300 Working Parameters Image: Constraint of the second	Capacity (kg)	7000	5500
Working Parameters Machine Equipment Available fork dimensions	Weight and dimensions		
Machine Equipment X X X X X X X X X X X X X X X X X X X	Width (mm)	1030	1300
Available fork dimensions	Working Parameters		
	Machine Equipment	×	\times
120 x 60 x 1200	Available fork dimensions		
130 x 00 x 1200 932132	130 x 60 x 1200		932152

Machines compatibility	TFF 7t	TFF 5.5t
MRT 2470 Privilege Plus OLD	Х	
MRT 3255 Privilege Plus OLD		Х
MRT-X 2470 Privilege Plus OLD	Х	
MRT-X 3255 Privilege Plus OLD		Х

TABLE SYMBOL			
\times	No predisposition required	Hydraulic line	Return piping to hydraulic oil tank
	Electric predisposition	Platform predisposition	Tyre handler, cylinder handler predisposition



Head Office B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes