Technical sheet:

FLOATING FORKS CARRIAGE



Customer benefits

- Carriage adapted to uneven ground.
- Pin-type forks + side leveling = very easy pallet collection in all conditions
- Must-have on construction yards.

Technical characteristics

- Pin-type forks with side-movement lock.
- Forks mounted on a mobile bar with leveling function.
- Welded load backrest (MT, MLT) / bolted backrest (MRT, MHT).
- Note: road circulation kit mandatory in Italy. Contact your dealer.
- Note: road circulation kit mandatory in Germany on MRT Vision/ Vision+. Contact your dealer.



FLOATING FORKS CARRIAGE Created on 5 May 2024 at 4:45:53 AM UTC

| Capacities | TFF 7t | TFF 5.5t | | | | | |
|---------------------------|--------|----------|--|--|--|--|--|
| Capacity (kg) | 7000 | 5500 | | | | | |
| Weight and dimensions | | | | | | | |
| Width (mm) | 1030 | 1300 | | | | | |
| Working Parameters | | | | | | | |
| Machine Equipment | × | X | | | | | |
| Available fork dimensions | | | | | | | |
| 130 x 60 x 1200 | | 932152 | | | | | |

| Machines compatibility | TFF 7t | TFF 5.5t |
|-------------------------------|--------|----------|
| MRT 2470 Privilege Plus OLD | Х | |
| MRT 3255 Privilege Plus OLD | | X |
| MRT-X 2470 Privilege Plus OLD | X | |
| MRT-X 3255 Privilege Plus OLD | | Х |

| TABLE SYMBOL | | | | | | |
|--------------|----------------------------|----|-------------------------|--|---|--|
| × | No predisposition required | 88 | Hydraulic line | | Return piping to hydraulic oil tank | |
| | Electric predisposition | | Platform predisposition | | Tyre handler, cylinder handler predisposition | |





Head Office

B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes