Technical sheet:

# TILTING & SLEWING FORKS CARRIAGE



### **Technical characteristics**

- FEM cat forks. 2.
- 90°/90° hydraulic rotation.
- Use of reliable Manitou components.
- Rotation with 2 cylinders for more precision.
- Straight and turned capacity 1500 kg / 3308 lb.
- Note: Road circulation kit mandatory in Italy. Contact your dealer

## **Customer benefits**

- Easier handling of long loads in constrained spaces.
- Reduced machine movements and manoeuvres less fuel consumption.
- Recommended for the placement of sandwich panels on roofs (in combination with the cavage of the machine's carriage).



#### TILTING & SLEWING FORKS CARRIAGE Created on November 9, 2025 at 12:08 AM UTC

Technical characteristics		PFB 90° (a)	PFB 90° (b)
Distance to center of gravity (mm)			755
Capacities			
Capacity (kg)		1000	1500
Weight			
Overall weight (kg)		631	662
Weight and dimensions			
Overall height (mm)	h17		1008
Overall length (mm)	I1		2432
Width (mm)		1360	1360
Working Parameters			
Required machine equipment		<b> </b>	<del>8</del> 8
Available fork dimensions			
100 x 45 x 1200			923348

Machines compatibility	PFB 90° (a)	PFB 90° (b)
Reference number E-RECO		923348
MRT 2260		X
MRT 2260 e		X
MRT 2570		X
MRT 2660		X
MRT 2660 e		X
MRT 3060		X
MRT 3570		X
MRT 3570 ES		X
MRT-X 2150 Privilege Plus	Х	X
MRT-X 2260		X
MRT-X 2470 Privilege Plus		X
MRT-X 2550 Privilege Plus	Х	X
MRT-X 2570		X
MRT-X 2660		X
MRT-X 3050 Privilege Plus		X
MRT-X 3060		X
MRT-X 3255 Privilege Plus		X
MRT-X 3570		X
MRT-X 3570 ES		X
MRT 2150 Privilege Plus OLD	X	X
MRT 2470 Privilege Plus OLD		X
MRT 2550 Privilege Plus OLD	Х	X
MRT 3050 Privilege Plus OLD		X
MRT 3255 Privilege Plus OLD		Х

TABLE SYMBOL							
X	No predisposition required	88	Hydraulic line		Return piping to hydraulic oil tank		
	Electric predisposition		Platform predisposition		Tyre handler, cylinder handler predisposition		





#### **Head Office**

B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes