

Technical sheet :

SILAGE FACING BUCKET



Customer benefits

- Loads and aerates silages in one operation.
- Ready-to-use silage: direct distribution or use in the mixing wagon.
- Clean silage pit face, limits secondary fermentation.
- Time-saving, a single attachment for the handling of silage and bulk feed.
- For corn silage and grass silage (short wisps).
Not suitable for long wisp silage (10 cm / 4 in max.).

Technical characteristics

- Synchronized hydraulic movements.
- Hydraulic motor integrated in the rotor, perfect protection & longevity.
- Backward rotor rotation, better bucket filling 500 HB wear plate.
- Handling material with a density $\leq 1000 \text{ kg/m}^3 / 62 \text{ lb/ft}^3$.

[The 3D picture at the top of this page is the reference CRS 2550 / 2000 - 52612540].

| Capacities | BSCR 2100 / 1130 | CRS 2350 / 1800 | CRS 2550 / 2000 |
|-----------------------|---|---|---|
| Capacity (kg) | 1130 | 1800 | 2000 |
| Heaped capacity (l) | 1130 | 1800 | 2000 |
| Weight | | | |
| Overall weight (kg) | 540 | 900 | 955 |
| Weight and dimensions | | | |
| Width (mm) | 2100 | 2350 | 2550 |
| Working Parameters | | | |
| Machine Equipment |  |  |  |

| Machines compatibility | BSCR 2100 / 1130 | CRS 2350 / 1800 | CRS 2550 / 2000 |
|---------------------------------|------------------|-----------------|-----------------|
| Reference number | 52728902 | 52612542 | 52612540 |
| MLT 625-75 H | X | - | - |
| MLT 630-115 | - | X | - |
| MLT 630-115 V | - | X | - |
| MLT 630-115 V CP | - | X | - |
| MLT 635-130 PS+ | - | - | X |
| MLT 635-140 V+ | - | - | X |
| MLT 730-115 V | - | X | - |
| MLT 730-115 V CP | - | X | - |
| MLT 733-115 LSU | - | - | X |
| MLT 737-130 PS+ | - | - | X |
| MLT 841-145 PS+ | - | - | X |
| MLT 940-140 V+ | - | - | X |
| MLT 1041-145 PS+L | - | - | X |
| MLFX 625-75 H | X | - | - |
| MLFX 732 | - | - | X |
| MLFX 735 T LSU | - | - | X |
| MLFX 737-130 PS+ | - | - | X |
| MLFX 741 T LSU | - | - | X |
| MLFX 841 - 145 PS+ | - | - | X |
| MLFX 1041-145 PS+L | - | - | X |
| MLT 630-105 ST4 OLD | - | X | - |
| MLT 630-105 V CP ST4 OLD | - | X | - |
| MLT 630-105 V ST4 OLD | - | X | - |
| MLT 635-130 PS+ ST4 OLD | - | - | X |
| MLT 635-140 V+ ST4 OLD | - | - | X |
| MLT 730-115 V CP ST4 OLD | - | X | - |
| MLT 730-115 V ST4 OLD | - | X | - |
| MLT 733-115 OLD | - | - | X |
| MLT 733-115 LSU ST4 OLD | - | - | X |
| MLT 733-115 ST4 OLD | - | - | X |
| MLT 737-130 PS+ ST4 OLD | - | - | X |
| MLT 741-140 V+ ST4 OLD | - | - | X |
| MLT 840-145 PS+ OLD | - | - | X |
| MLT 940-140 V+ ST4 OLD | - | - | X |
| MLT 1040-145 PS+ L OLD | - | - | X |
| MLFX 737-130 PS+ OLD | - | - | X |
| MLFX 741-140 V+ S1 OLD | - | - | X |
| MLFX 840-140 PS+ OLD | - | - | X |
| MLFX 1040-140 PS+ L OLD | - | - | X |

| TABLE SYMBOL | | | | | |
|---|----------------------------|---|-------------------------|---|---|
|  | No predisposition required |  | Hydraulic line |  | Return piping to hydraulic oil tank |
|  | Electric predisposition |  | Platform predisposition |  | Tyre handler, cylinder handler predisposition |



Head Office

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes