

Technical sheet :

PLATFORM










Customer benefits

- Uncompromized safety in people lifting applications.
- Simple and efficient platform.
- Cost efficient solution for people lifting.
- Safety: hand rail all around the platform.
- Access from both sides for higher flexibility.
- Fork sleeves for yard handling.

Technical characteristics







- Capacity 200 kg / 441 lb or 365 kg / 805 lb.
- Slewing platform +/- 90° on both sides or fixed.
- Legally approved for 3 people (platform capacity includes 3 people).
- Overload (365 kg / 805 lb only) and presence sensor.
- Painted platform.
- Non-slip metal floor.
- Fork sleeves: 238 mm x 100 mm.
- E-Reco 2 - 52719658 : Version dedicated to North American & Australian/NZ markets

[The 3D picture at the top of this page is the reference NAC 2M - 788782].

Technical characteristics		NAC 2M	NAC 1.2 x 0.8 M	ORH	PF 1200 / 200 2P	PF 2000 / 365 3P	PF 2000 / 365	PS 2000 / 365 3P
Capacity including people (kg)		365	200	365	200	365	365	365
Number of people		3	2	3	2	3	3	3
Distance to center of gravity (mm)		700	407	1203	407	700	646	1203
Weight								
Overall weight (kg)		404	165	570	165	393	409	570
Weight and dimensions								
Overall height (mm)	h17	1292	1240	1292	1240	1631	1631	1319
Overall length (mm)	l1	1812	1095	2490	1173	1812	1755	2490
Width (mm)		2190	1391	2130	1391	2190	2190	2190
Depth (mm)	p5	1150	740	1150	740	1150	1150	1150
Working Parameters								
Machine Equipment								
Rotation 1 (°)		-	-	90	-	-	-	90
Rotation 2 (°)		-	-	90	-	-	-	90

Machines compatibility	NAC 2M	NAC 1.2 x 0.8 M	ORH	PF 1200 / 200 2P	PF 2000 / 365 3P	PF 2000 / 365	PS 2000 / 365 3P
Reference number	788782	939382	-	-	-	-	-
MT 625 HA	X	X	-	-	-	-	-
MT 930 HA	X	X	-	-	-	-	-
MTX 1440 A	X	-	-	-	-	-	-
MTX 1840 A	X	-	-	-	-	-	-
MT 1135 HA Easy ST5 OLD	X	-	-	-	-	-	-
MT 1335 HA easy ST5 OLD	X	-	-	-	-	-	-
MT 1440 A OLD	X	-	-	-	-	-	-
MT 1440 HA OLD	X	-	-	-	-	-	-
MT 1840 A OLD	X	-	-	-	-	-	-
MT 1840 HA OLD	X	-	-	-	-	-	-
Reference number E-RECO	921296	923345	921304	52719244	52719245	52727780	52719246
MHT 790 Mining ST5	-	-	-	-	X	-	X
MHT 790 ST5	-	-	-	-	X	-	X
MHT 10135 ST5	-	-	-	-	-	X	-
MHT 10160 ST5	-	-	-	-	-	X	-
MHT 10200 ST5	-	-	-	-	-	X	-
MHT 11250 Mining ST5	-	-	-	-	-	X	-
MHT 11250 ST5	-	-	-	-	-	X	-
MHTX 790 ST3A	-	-	-	-	X	-	X
MHTX 10135 ST3A	-	-	-	-	-	X	-
MHTX 10160 ST3A	-	-	-	-	-	X	-
MHTX 10200 ST3A	-	-	-	-	-	X	-
MHTX 11250 Mining	-	-	-	-	-	X	-
MHTX 11250 ST3A	-	-	-	-	-	X	-
MRT 1645 75	-	-	-	X	X	-	X
MRT 1645 115	-	-	-	X	X	-	X
MRT 1845 75	-	-	-	X	X	-	X
MRT 1845 115	-	-	-	X	X	-	X
MRT 2145 115	-	-	-	X	X	-	X
MRT 2260	-	-	-	X	X	-	X
MRT 2260 e	-	-	-	X	X	-	X
MRT 2545 115	-	-	-	X	X	-	X
MRT 2570	-	-	-	X	X	-	X
MRT 2660	-	-	-	X	X	-	X
MRT 2660 e	-	-	-	X	X	-	X
MRT 3060	-	-	-	X	X	-	X
MRT 3570	-	-	-	X	X	-	X
MRT 3570 ES	-	-	-	X	X	-	X
MRTX 1645	-	-	-	X	X	-	X
MRTX 1845	-	-	-	X	X	-	X
MRTX 2145	-	-	-	X	X	-	X
MRTX 2260	-	-	-	X	X	-	X
MRTX 2545	-	-	-	X	X	-	X
MRTX 2570	-	-	-	X	X	-	X
MRTX 2660	-	-	-	X	X	-	X
MRTX 3060	-	-	-	X	X	-	X
MRTX 3570	-	-	-	X	X	-	X
MRTX 3570 ES	-	-	-	X	X	-	X
MHT 790 OLD	-	-	X	-	X	-	-
MHTX 790 OLD	-	-	-	-	X	-	X
MHTX 790 Mining OLD	-	-	-	-	X	-	X
MRT 1640 Easy T4 S2 360° OLD	X	-	X	-	-	-	-
MRT 1840 Easy T4 S2 360° OLD	X	-	X	-	-	-	-
MRT 1840 Easy T4 S2 400° OLD	X	-	X	-	-	-	-
MRT 2145 Easy T4 S2 360° OLD	X	-	X	-	-	-	-
MRT 2145 Easy T4 S2 400° OLD	X	-	X	-	-	-	-
MRT 2150 Privilege Plus OLD	X	X	X	-	-	-	-
MRT 2470 Privilege Plus OLD	X	X	X	-	-	-	-
MRT 2545 Easy T4 S2 360° OLD	-	-	X	-	-	-	-
MRT 2545 Easy T4 S2 400° OLD	X	-	X	-	-	-	-
MRT 2550 Privilege Plus OLD	X	X	X	-	-	-	-
MRT 3050 Privilege Plus OLD	X	X	X	-	-	-	-

Machines compatibility	NAC 2M	NAC 1.2 x 0.8 M	ORH	PF 1200 / 200 2P	PF 2000 / 365 3P	PF 2000 / 365	PS 2000 / 365 3P
MRT 3255 Privilege Plus OLD	X	-	X	-	-	-	-
MRT-X 1840 Easy 360° OLD	X	-	X	-	-	-	-
MRT-X 1840 Easy 400° OLD	X	-	X	-	-	-	-
MRT-X 2150 Privilege Plus OLD	X	X	X	-	-	-	-
MRT-X 2470 Privilege Plus OLD	X	X	X	-	-	-	-
MRT-X 2545 Easy 360° OLD	X	-	X	-	-	-	-
MRT-X 2545 Easy 400° OLD	X	-	X	-	-	-	-
MRT-X 2550 Privilege Plus OLD	X	X	X	-	-	-	-
MRT-X 3050 Privilege Plus OLD	X	X	X	-	-	-	-
MRT-X 3255 Privilege Plus OLD	X	-	X	-	-	-	-
Reference number E-RECO 2	939240	-	-	-	52719658	52747069	-
MHT 790 Mining ST5	-	-	-	-	X	-	X
MHT 790 ST5	-	-	-	-	X	-	-
MHT 10135 ST5	-	-	-	-	-	X	-
MHT 10160 ST5	-	-	-	-	-	X	-
MHT 10200 ST5	-	-	-	-	-	X	-
MHT 11250 Mining ST5	-	-	-	-	-	X	-
MHT 11250 ST5	-	-	-	-	-	X	-
MHT-X 790 ST3A	-	-	-	-	X	-	-
MHT-X 10135 ST3A	-	-	-	-	-	X	-
MHT-X 10160 ST3A	-	-	-	-	-	X	-
MHT-X 10200 ST3A	-	-	-	-	-	X	-
MHT-X 11250 Mining	-	-	-	-	-	X	-
MHT-X 11250 ST3A	-	-	-	-	-	X	-
MRT 1645 75	-	-	-	-	X	-	-
MRT 1645 115	-	-	-	-	X	-	-
MRT 1845 75	-	-	-	-	X	-	-
MRT 1845 115	-	-	-	-	X	-	-
MRT 2145 115	-	-	-	-	X	-	-
MRT 2260	-	-	-	-	X	-	-
MRT 2260 e	-	-	-	-	X	-	-
MRT 2545 115	-	-	-	-	X	-	-
MRT 2570	-	-	-	-	X	-	-
MRT 2660	-	-	-	-	X	-	-
MRT 2660 e	-	-	-	-	X	-	-
MRT 3060	-	-	-	-	X	-	-
MRT 3570	-	-	-	-	X	-	-
MRT 3570 ES	-	-	-	-	X	-	-
MRT-X 1645	-	-	-	-	X	-	-
MRT-X 1845	-	-	-	-	X	-	-
MRT-X 2145	-	-	-	-	X	-	-
MRT-X 2260	-	-	-	-	X	-	-
MRT-X 2545	-	-	-	-	X	-	-
MRT-X 2570	-	-	-	-	X	-	-
MRT-X 2660	-	-	-	-	X	-	-
MRT-X 3060	-	-	-	-	X	-	-
MRT-X 3570	-	-	-	-	X	-	-
MRT-X 3570 ES	-	-	-	-	X	-	-
MHT 790 OLD	-	-	-	-	X	-	-
MHT 10130 OLD	X	-	-	-	-	-	-
MHT 10180 OLD	X	-	-	-	-	-	-
MHT 10230 OLD	X	-	-	-	-	-	-
MHT-X 790 OLD	-	-	-	-	X	-	-
MHT-X 790 Mining OLD	-	-	-	-	X	-	X

TABLE SYMBOL					
	No predisposition required		Hydraulic line		Return piping to hydraulic oil tank
	Electric predisposition		Platform predisposition		Tyre handler, cylinder handler predisposition



Head Office

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes