Technical sheet:

# HIGH CAPACITY AGRICULTURAL GRAB BUCKET



## **Technical characteristics**

- Welded teeth WE.
- Handling materials with a density ≤ 1000 kg/m³ / 62 lb/ft³.
- 500 HB bolt-on cutting edge in standard.
- Reinforced bucket: improved material grip on sides & top Increased struck capacity (1500 L / 53 ft³).

[The 3D picture at the top of this page is the reference CBG  $2480 / 2600 \, MS - 790658$ ].

## **Customer benefits**

- Robust and versatile bucket suitable for massive agricultural applications.
- Reinforced bucket for a massive work output in agricultural applications.
- Ideal to handle cereals and other bulk materials.



#### HIGH CAPACITY AGRICULTURAL GRAB BUCKET Created on December 15, 2025 at 6:03 PM UTC

Technical characteristics		CBG 2480 / 2000 MS CBG 2480 / 2600 MS				
Distance to center of gravity (mm)		388	380			
Capacities						
Capacity (kg)		2000	2600			
Heaped capacity (I)		2000	2600			
Struck capacity (I)		1500	1500			
Weight						
Overall weight (kg)		1225	1357			
Weight and dimensions						
Overall length (mm)	I1	1491	1670			
Width (mm)		2480	2480			
Closed grapple height (mm)	h33	1502	1502			
Opened grapple height (mm)	h34	2292	2452			
Working Parameters						
Required machine equipment		<b>\\ \\ \\ \</b>	<b></b>			
Teeth		6	7			
Minimum forks spread (mm)	b5	453	362			
Maximum forks spread (mm)	b5	453	453 362			
Other Data for Attachments						
Wear plate hardness		500	500			

Machines compatibility	CBG 2480 / 2000 MS	CBG 2480 / 2600 MS		
Reference number with bolted wearplate (WP)	790656	790658		
MLT 841-145 PS+	Х			
MLT 850-145 V+	Х	X		
MLT 961-160 V+ L		X		
MLT 1041-145 PS+L	Х			
MLT-X 841 - 145 PS+	X			
MLT-X 850-145 V+	Х	X		
MLT-X 961-160 V+ L		X		
MLT-X 1041-145 PS+L	Х	•		
MLT 840-145 PS+ <b>OLD</b>	X			
MLT 845-100 H OLD	Х			
MLT 845-120 <b>OLD</b>	X			
MLT 961-145 V+ L OLD		X		
MLT 1040-145 PS+ L <b>OLD</b>	X			
MLT-X 840-140 PS+ OLD	X			
MLT-X 845-120 <b>OLD</b>	X			
MLT-X 845-120 H OLD	Х			
MLT-X 961-145 V+ L <b>OLD</b>		Х		
MLT-X 1040-140 PS+ L OLD	Х			

TABLE SYMBOL							
×	No predisposition required	88	Hydraulic line		Return piping to hydraulic oil tank		
	Electric predisposition		Platform predisposition		Tyre handler, cylinder handler predisposition		





#### **Head Office**

B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes