

Technical sheet :

HIGH CAPACITY AGRICULTURAL GRAB BUCKET





Customer benefits

- Robust and versatile bucket suitable for massive agricultural applications.
- Reinforced bucket for a massive work output in agricultural applications.
- Ideal to handle cereals and other bulk materials.

Technical characteristics

- Welded teeth - WE.
- Handling materials with a density $\leq 1000 \text{ kg/m}^3$ / 62 lb/ft³.
- 500 HB bolt-on cutting edge in standard.
- Reinforced bucket: improved material grip on sides & top
Increased struck capacity (1500 L / 53 ft³).

[The 3D picture at the top of this page is the reference CBG 2480 / 2600 MS - 790658].

| Technical characteristics | | CBG 2480 / 2000 MS | CBG 2480 / 2600 MS |
|------------------------------------|-----|-----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| Distance to center of gravity (mm) | | 388 | 380 |
| Capacities | | | |
| Capacity (kg) | | 2000 | 2600 |
| Heaped capacity (l) | | 2000 | 2600 |
| Struck capacity (l) | | 1500 | 1500 |
| Weight | | | |
| Overall weight (kg) | | 1225 | 1357 |
| Weight and dimensions | | | |
| Overall length (mm) | l1 | 1491 | 1670 |
| Width (mm) | | 2480 | 2480 |
| Closed grapple height (mm) | h33 | 1502 | 1502 |
| Opened grapple height (mm) | h34 | 2292 | 2452 |
| Working Parameters | | | |
| Machine Equipment | |  |  |
| Teeth | | 6 | 7 |
| Fork spread minimum (mm) | b5 | 453 | 362 |
| Maximum forks spread (mm) | b5 | 453 | 362 |
| Other Data for Attachments | | | |
| Wear plate hardness | | 500 | 500 |

| Machines compatibility | CBG 2480 / 2000 MS | CBG 2480 / 2600 MS |
|---------------------------------------------|--------------------|--------------------|
| Reference number with bolted wearplate (WP) | 790656 | 790658 |
| MLT 841-145 PS+ | X | - |
| MLT 850-145 V+ | X | X |
| MLT 961-160 V+ L | - | X |
| MLT 1041-145 PS+L | X | - |
| MLFX 841 - 145 PS+ | X | - |
| MLFX 850-145 V+ | X | X |
| MLFX 961-160 V+ L | - | X |
| MLFX 1041-145 PS+L | X | - |
| MLT 840-145 PS+ OLD | X | - |
| MLT 845-100 H OLD | X | - |
| MLT 845-120 OLD | X | - |
| MLT 961-145 V+ L OLD | - | X |
| MLT 1040-145 PS+ L OLD | X | - |
| MLFX 840-140 PS+ OLD | X | - |
| MLFX 845-120 OLD | X | - |
| MLFX 845-120 H OLD | X | - |
| MLFX 961-145 V+ L OLD | - | X |
| MLFX 1040-140 PS+ L OLD | X | - |

| TABLE SYMBOL | | | | | |
|-------------------------------------------------------------------------------------|----------------------------|-------------------------------------------------------------------------------------|-------------------------|---------------------------------------------------------------------------------------|-----------------------------------------------|
|  | No predisposition required |  | Hydraulic line |  | Return piping to hydraulic oil tank |
|  | Electric predisposition |  | Platform predisposition |  | Tyre handler, cylinder handler predisposition |



Head Office

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes