

Technical sheet :

# 3-HOOK JIB



## Customer benefits

- Perfect attachments for all heavy suspended loads.
- Jib fitted with 3 hooks to meet various needs of building sites.
- Adaptability for all yard handling applications.

## Technical characteristics

- 3 capacity / outreach couples.
- Safety: homologated swivel self locking hook.

[The 3D picture at the top of this page is the reference P 25 T - 53010431].

 **ATTACHMENTS**

Technical characteristics		JH 16 T - 10 T - 7.5 T	JH 20 T - 14 T - 10 T	JH 13.5 T - 10 T - 7.5 T	P 9 T	P 13 T	P 18 T	P 25 T	P 36 T	P 40 T (Available upon request)
Distance to center of gravity (mm)		821	821	821	718	833	821	901	930	-
<b>Capacities</b>										
Capacity (kg)		16000	20000	13500	9000	13000	18000	25000	36000	40000
Capacity 2 (kg)		10000	14000	10000	5000	10000	14000	18000	16000	22000
Capacity 3 (kg)		7500	10000	7500	2000	7500	10000	13000	10000	-
<b>Weight</b>										
Overall weight (kg)		555	590	555	295	560	570	890	1490	3500
<b>Dimensions</b>										
Max. outreach (mm)		700	700	700	470	700	700	700	905	905
Max @ outreach 2 (mm)		1350	1350	1350	1385	1350	1350	1250	2005	905
Max @ outreach 3 (mm)		2000	2000	2000	2300	2000	2000	1800	3000	3000
<b>Weight and dimensions</b>										
Overall length (mm)	I1	2215	2215	2215	2518	2215	2215	2085	3351	-
Width (mm)		830	830	830	815	800	830	850	1170	-
<b>Working Parameters</b>										
Machine Equipment		✗	✗	✗	✗	✗	✗	✗	✗	-

Machines compatibility		JH 16 T - 10 T - 7.5 T	JH 20 T - 14 T - 10 T	JH 13.5 T - 10 T - 7.5 T	P 9 T	P 13 T	P 18 T	P 25 T	P 36 T	P 40 T (Available upon request)
Reference number		-	-	-	-	-	-	-	-	999100
Reference number E-RECO		52701741	52701742	52701740	930830	53009841	53011885	53010431	52604320	-
MHT 790 Mining ST5		-	-	-	X	-	-	-	-	-
MHT 790 ST5		-	-	-	X	-	-	-	-	-
MHT 10135 ST5		-	-	X	-	-	-	-	-	-
MHT 10160 ST5		X	-	-	-	-	-	-	-	-
MHT 10200 ST5		-	X	-	-	-	-	-	-	-
MHT 11250 Mining ST5		-	-	-	-	-	-	X	-	-
MHT 11250 ST5		-	-	-	-	-	-	X	-	-
MHT 12330		-	-	-	-	-	-	X	X	-
MHT-X 790 ST3A		-	-	-	X	-	-	-	-	-
MHT-X 10135 ST3A		-	-	X	-	-	-	-	-	-
MHT-X 10160 ST3A		X	-	-	-	-	-	-	-	-
MHT-X 10200 ST3A		-	X	-	-	-	-	-	-	-
MHT-X 11250 Mining		-	-	-	-	-	-	X	-	-
MHT-X 11250 ST3A		-	-	-	-	-	-	X	-	-
MHT-X 12330		-	-	-	-	-	-	X	X	-
MRT 2260 e		-	-	-	X	-	-	-	-	-
MRT 2570		-	-	-	X	-	-	-	-	-
MRT 2660 e		-	-	-	X	-	-	-	-	-
MRT 3570		-	-	-	X	-	-	-	-	-
MRT 3570 ES		-	-	-	X	-	-	-	-	-
MRT-X 2570		-	-	-	X	-	-	-	-	-
MRT-X 3570		-	-	-	X	-	-	-	-	-
MRT-X 3570 ES		-	-	-	X	-	-	-	-	-
MHT 790 <b>OLD</b>		-	-	-	X	-	-	-	-	-
MHT 10130 <b>OLD</b>		-	-	-	-	X	-	-	-	-
MHT 10180 <b>OLD</b>		-	-	-	-	-	X	-	-	-
MHT 10230 <b>OLD</b>		-	-	-	-	-	-	X	-	-
MHT 14350 <b>OLD</b>		-	-	-	-	-	-	-	-	X
MHT-X 790 <b>OLD</b>		-	-	-	X	-	-	-	-	-
MHT-X 790 Mining <b>OLD</b>		-	-	-	X	-	-	-	-	-
MHT-X 14350 <b>OLD</b>		-	-	-	-	-	-	-	-	X
MRT 2470 Privilege Plus <b>OLD</b>		-	-	-	X	-	-	-	-	-
MRT-X 2470 Privilege Plus <b>OLD</b>		-	-	-	X	-	-	-	-	-

TABLE SYMBOL					
	No predisposition required		Hydraulic line		Return piping to hydraulic oil tank
	Electric predisposition		Platform predisposition		Tyre handler, cylinder handler predisposition



**Head Office**

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

[www.manitou.com](http://www.manitou.com)



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes