

Technical sheet :

# 3-HOOK JIB



## Technical characteristics

- 3 capacity / outreach couples.
- Safety: homologated swivel self locking hook.

[The 3D picture at the top of this page is the reference P 25 T - 53010431].

## Customer benefits

- Perfect attachments for all heavy suspended loads.
- Jib fitted with 3 hooks to meet various needs of building sites.
- Adaptability for all yard handling applications.

| Technical characteristics          |    | JH 16 T - 10 T - 7.5 T | JH 20 T - 14 T - 10 T | JH 13.5 T - 10 T - 7.5 T | P 9 T | P 13 T | P 18 T | P 25 T | P 36 T | P 40 T (Available upon request) |
|------------------------------------|----|------------------------|-----------------------|--------------------------|-------|--------|--------|--------|--------|---------------------------------|
| Distance to center of gravity (mm) |    | 821                    | 821                   | 821                      | 718   | 833    | 821    | 901    | 930    | -                               |
| <b>Capacities</b>                  |    |                        |                       |                          |       |        |        |        |        |                                 |
| Capacity (kg)                      |    | 16000                  | 20000                 | 13500                    | 9000  | 13000  | 18000  | 25000  | 36000  | 40000                           |
| Capacity 2 (kg)                    |    | 10000                  | 14000                 | 10000                    | 5000  | 10000  | 14000  | 18000  | 16000  | 22000                           |
| Capacity 3 (kg)                    |    | 7500                   | 10000                 | 7500                     | 2000  | 7500   | 10000  | 13000  | 10000  | -                               |
| <b>Weight</b>                      |    |                        |                       |                          |       |        |        |        |        |                                 |
| Overall weight (kg)                |    | 555                    | 590                   | 555                      | 295   | 560    | 570    | 890    | 1490   | 3500                            |
| <b>Dimensions</b>                  |    |                        |                       |                          |       |        |        |        |        |                                 |
| Maximum outreach (mm)              |    | 700                    | 700                   | 700                      | 470   | 700    | 700    | 700    | 905    | 905                             |
| Maximum outreach 2 (mm)            |    | 1350                   | 1350                  | 1350                     | 1385  | 1350   | 1350   | 1250   | 2005   | 905                             |
| Maximum outreach 3 (mm)            |    | 2000                   | 2000                  | 2000                     | 2300  | 2000   | 2000   | 1800   | 3000   | 3000                            |
| <b>Weight and dimensions</b>       |    |                        |                       |                          |       |        |        |        |        |                                 |
| Overall length (mm)                | I1 | 2215                   | 2215                  | 2215                     | 2518  | 2215   | 2215   | 2085   | 3351   | -                               |
| Width (mm)                         |    | 830                    | 830                   | 830                      | 815   | 800    | 830    | 850    | 1170   | -                               |
| <b>Working Parameters</b>          |    |                        |                       |                          |       |        |        |        |        |                                 |
| Required machine equipment         |    | ✗                      | ✗                     | ✗                        | ✗     | ✗      | ✗      | ✗      | ✗      | -                               |

| Machines compatibility               |  | JH 16 T - 10 T - 7.5 T | JH 20 T - 14 T - 10 T | JH 13.5 T - 10 T - 7.5 T | P 9 T  | P 13 T   | P 18 T   | P 25 T   | P 36 T   | P 40 T (Available upon request) |
|--------------------------------------|--|------------------------|-----------------------|--------------------------|--------|----------|----------|----------|----------|---------------------------------|
| Reference number                     |  | -                      | -                     | -                        | -      | -        | -        | -        | -        | 939100                          |
| Reference number E-RECO              |  | 52701741               | 52701742              | 52701740                 | 930830 | 53009841 | 53011885 | 53010431 | 52604320 | -                               |
| MHT 790 Mining ST5                   |  | -                      | -                     | -                        | X      | -        | -        | -        | -        | -                               |
| MHT 790 ST5                          |  | -                      | -                     | -                        | X      | -        | -        | -        | -        | -                               |
| MHT 10135 ST5                        |  | -                      | -                     | X                        | -      | -        | -        | -        | -        | -                               |
| MHT 10160 ST5                        |  | X                      | -                     | -                        | -      | -        | -        | -        | -        | -                               |
| MHT 10200 ST5                        |  | -                      | X                     | -                        | -      | -        | -        | -        | -        | -                               |
| MHT 11250 Mining ST5                 |  | -                      | -                     | -                        | -      | -        | -        | X        | -        | -                               |
| MHT 11250 ST5                        |  | -                      | -                     | -                        | -      | -        | -        | X        | -        | -                               |
| MHT 12330                            |  | -                      | -                     | -                        | -      | -        | -        | X        | X        | -                               |
| MHT-X 790 ST3A                       |  | -                      | -                     | -                        | X      | -        | -        | -        | -        | -                               |
| MHT-X 10135 ST3A                     |  | -                      | -                     | X                        | -      | -        | -        | -        | -        | -                               |
| MHT-X 10160 ST3A                     |  | X                      | -                     | -                        | -      | -        | -        | -        | -        | -                               |
| MHT-X 10200 ST3A                     |  | -                      | X                     | -                        | -      | -        | -        | -        | -        | -                               |
| MHT-X 11250 Mining                   |  | -                      | -                     | -                        | -      | -        | -        | X        | -        | -                               |
| MHT-X 11250 ST3A                     |  | -                      | -                     | -                        | -      | -        | -        | X        | -        | -                               |
| MHT-X 12330                          |  | -                      | -                     | -                        | -      | -        | -        | X        | X        | -                               |
| MRT 2260                             |  | -                      | -                     | -                        | X      | -        | -        | -        | -        | -                               |
| MRT 2260 e                           |  | -                      | -                     | -                        | X      | -        | -        | -        | -        | -                               |
| MRT 2570                             |  | -                      | -                     | -                        | X      | -        | -        | -        | -        | -                               |
| MRT 2660                             |  | -                      | -                     | -                        | X      | -        | -        | -        | -        | -                               |
| MRT 2660 e                           |  | -                      | -                     | -                        | X      | -        | -        | -        | -        | -                               |
| MRT 3570                             |  | -                      | -                     | -                        | X      | -        | -        | -        | -        | -                               |
| MRT 3570 ES                          |  | -                      | -                     | -                        | X      | -        | -        | -        | -        | -                               |
| MRT-X 2260                           |  | -                      | -                     | -                        | X      | -        | -        | -        | -        | -                               |
| MRT-X 2570                           |  | -                      | -                     | -                        | X      | -        | -        | -        | -        | -                               |
| MRT-X 2660                           |  | -                      | -                     | -                        | X      | -        | -        | -        | -        | -                               |
| MRT-X 3570                           |  | -                      | -                     | -                        | X      | -        | -        | -        | -        | -                               |
| MRT-X 3570 ES                        |  | -                      | -                     | -                        | X      | -        | -        | -        | -        | -                               |
| MHT 790 <b>OLD</b>                   |  | -                      | -                     | -                        | X      | -        | -        | -        | -        | -                               |
| MHT 10130 <b>OLD</b>                 |  | -                      | -                     | -                        | -      | X        | -        | -        | -        | -                               |
| MHT 10180 <b>OLD</b>                 |  | -                      | -                     | -                        | -      | -        | X        | -        | -        | -                               |
| MHT 10230 <b>OLD</b>                 |  | -                      | -                     | -                        | -      | -        | -        | X        | -        | -                               |
| MHT 14350 <b>OLD</b>                 |  | -                      | -                     | -                        | -      | -        | -        | -        | -        | X                               |
| MHT-X 790 <b>OLD</b>                 |  | -                      | -                     | -                        | X      | -        | -        | -        | -        | -                               |
| MHT-X 790 Mining <b>OLD</b>          |  | -                      | -                     | -                        | X      | -        | -        | -        | -        | -                               |
| MHT-X 14350 <b>OLD</b>               |  | -                      | -                     | -                        | -      | -        | -        | -        | -        | X                               |
| MRT 2470 Privilège Plus <b>OLD</b>   |  | -                      | -                     | -                        | X      | -        | -        | -        | -        | -                               |
| MRT-X 2470 Privilège Plus <b>OLD</b> |  | -                      | -                     | -                        | X      | -        | -        | -        | -        | -                               |

| TABLE SYMBOL |                            |  |                         |  |   |
|--------------|----------------------------|--|-------------------------|--|---|
|              | No predisposition required |  | Hydraulic line          |  | Return piping to hydraulic oil tank           |
|              | Electric predisposition    |  | Platform predisposition |  | Tyre handler, cylinder handler predisposition |



**Head Office**

B.P. 249 - 430 rue de l'Aubinière  
44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

[www.manitou.com](http://www.manitou.com)



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes