

Technical sheet :

3-HOOK JIB



Customer benefits

- Easy load placement directly from the cab.
- Especially interesting to place loads in narrow spaces.
- Improves efficiency-less time wasted placing the machine.
- Placement through rotation, not side shift = load moves backward when the jib swings.

Technical characteristics

- 3 capacity / outreach couples.
- Safety: homologated swivel self locking hook.

[The 3D picture at the top of this page is the reference P 25 T - 53010431].

| Technical characteristics | | JH 16 T - 10 T - 7.5 T | JH 20 T - 14 T - 10 T | JH 13.5 T - 10 T - 7.5 T | P 9 T | P 13 T | P 18 T | P 25 T | P 36 T | P 40 T (Available upon request) |
|------------------------------------|----|------------------------|-----------------------|--------------------------|-------|--------|--------|--------|--------|---------------------------------|
| Distance to center of gravity (mm) | | 821 | 821 | 821 | 718 | 833 | 821 | 901 | 930 | - |
| Capacities | | | | | | | | | | |
| Capacity (kg) | | 16000 | 20000 | 13500 | 9000 | 13000 | 18000 | 25000 | 36000 | 40000 |
| Capacity 2 (kg) | | 10000 | 14000 | 10000 | 5000 | 10000 | 14000 | 18000 | 16000 | 22000 |
| Capacity 3 (kg) | | 7500 | 10000 | 7500 | 2000 | 7500 | 10000 | 13000 | 10000 | - |
| Weight | | | | | | | | | | |
| Overall weight (kg) | | 555 | 590 | 555 | 295 | 560 | 570 | 890 | 1490 | 3500 |
| Dimensions | | | | | | | | | | |
| Max. outreach (mm) | | 700 | 700 | 700 | 470 | 700 | 700 | 700 | 905 | 905 |
| Max @ outreach 2 (mm) | | 1350 | 1350 | 1350 | 1385 | 1350 | 1350 | 1250 | 2005 | 905 |
| Max @ outreach 3 (mm) | | 2000 | 2000 | 2000 | 2300 | 2000 | 2000 | 1800 | 3000 | 3000 |
| Weight and dimensions | | | | | | | | | | |
| Overall length (mm) | I1 | 2215 | 2215 | 2215 | 2518 | 2215 | 2215 | 2085 | 3351 | - |
| Width (mm) | | 830 | 830 | 830 | 815 | 800 | 830 | 850 | 1170 | - |
| Working Parameters | | | | | | | | | | |
| Machine Equipment | | ✗ | ✗ | ✗ | ✗ | ✗ | ✗ | ✗ | ✗ | - |

| Machines compatibility | JH 16 T - 10 T - 7.5 T | JH 20 T - 14 T - 10 T | JH 13.5 T - 10 T - 7.5 T | P 9 T | P 13 T | P 18 T | P 25 T | P 36 T | P 40 T (Available upon request) |
|--------------------------------------|------------------------|-----------------------|--------------------------|--------|----------|----------|----------|----------|---------------------------------|
| Reference number | - | - | - | - | - | - | - | - | 999100 |
| Reference number E-RECO | 52701741 | 52701742 | 52701740 | 930830 | 53009841 | 53011885 | 53010431 | 52604320 | - |
| MHT 790 Mining ST5 | - | - | - | X | - | - | - | - | - |
| MHT 790 ST5 | - | - | - | X | - | - | - | - | - |
| MHT 10135 ST5 | - | - | X | - | - | - | - | - | - |
| MHT 10160 ST5 | X | - | - | - | - | - | - | - | - |
| MHT 10200 ST5 | - | X | - | - | - | - | - | - | - |
| MHT 11250 Mining ST5 | - | - | - | - | - | - | X | - | - |
| MHT 11250 ST5 | - | - | - | - | - | - | X | - | - |
| MHT 12330 | - | - | - | - | - | - | X | X | - |
| MHT-X 790 ST3A | - | - | - | X | - | - | - | - | - |
| MHT-X 10135 ST3A | - | - | X | - | - | - | - | - | - |
| MHT-X 10160 ST3A | X | - | - | - | - | - | - | - | - |
| MHT-X 10200 ST3A | - | X | - | - | - | - | - | - | - |
| MHT-X 11250 Mining | - | - | - | - | - | - | X | - | - |
| MHT-X 11250 ST3A | - | - | - | - | - | - | X | - | - |
| MHT-X 12330 | - | - | - | - | - | - | X | X | - |
| MRT 2260 e | - | - | - | X | - | - | - | - | - |
| MRT 2570 | - | - | - | X | - | - | - | - | - |
| MRT 2660 e | - | - | - | X | - | - | - | - | - |
| MRT 3570 | - | - | - | X | - | - | - | - | - |
| MRT 3570 ES | - | - | - | X | - | - | - | - | - |
| MRT-X 2570 | - | - | - | X | - | - | - | - | - |
| MRT-X 3570 | - | - | - | X | - | - | - | - | - |
| MRT-X 3570 ES | - | - | - | X | - | - | - | - | - |
| MHT 790 OLD | - | - | - | X | - | - | - | - | - |
| MHT 10130 OLD | - | - | - | - | X | - | - | - | - |
| MHT 10180 OLD | - | - | - | - | - | X | - | - | - |
| MHT 10230 OLD | - | - | - | - | - | - | X | - | - |
| MHT 14350 OLD | - | - | - | - | - | - | - | - | X |
| MHT-X 790 OLD | - | - | - | X | - | - | - | - | - |
| MHT-X 790 Mining OLD | - | - | - | X | - | - | - | - | - |
| MHT-X 14350 OLD | - | - | - | - | - | - | - | - | X |
| MRT 2470 Privilege Plus OLD | - | - | - | X | - | - | - | - | - |
| MRT-X 2470 Privilege Plus OLD | - | - | - | X | - | - | - | - | - |

| TABLE SYMBOL | | | | | |
|--------------|----------------------------|--|-------------------------|--|---|
| | No predisposition required | | Hydraulic line | | Return piping to hydraulic oil tank |
| | Electric predisposition | | Platform predisposition | | Tyre handler, cylinder handler predisposition |



Head Office

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes