Technical sheet :

3-HOOK JIB



Customer benefits

- Perfect attachments for all heavy suspended loads.
- Jib fitted with 3 hooks to meet various needs of building sites.
- Adaptability for all yard handling applications.

Technical characteristics

- 3 capacity / outreach couples.
- Safety: homologated swivel self locking hook.

[The 3D picture at the top of this page is the reference P 25 T - 53010431].



э-ноок лв Created on July 19, 2025 at 5:45 AM UTC

| | | | | | | 3- | ноок јів | created on Ju | iy 19, 2025 ai | 5.45 AIVI UT |
|------------------------------------|----|---------------------------|--------------------------|-----------------------------|----------|----------|----------|---------------|----------------|---------------------------------------|
| Technical characteristics | | JH 16 T - 10 T - 7.5 T | JH 20 T - 14 T - 10 T | JH 13.5 T - 10 T - 7.5 T | P 9 T | P 13 T | Р 18 Т | P 25 T | P 36 T | P 40 T (Available upon request) |
| Distance to center of gravity (mm) | | 821 | 821 | 821 | 718 | 833 | 821 | 901 | 930 | |
| Capacities | | | | | | | | | | |
| Capacity (kg) | | 16000 | 20000 | 13500 | 9000 | 13000 | 18000 | 25000 | 36000 | 40000 |
| Capacity 2 (kg) | | 10000 | 14000 | 10000 | 5000 | 10000 | 14000 | 18000 | 16000 | 22000 |
| Capacity 3 (kg) | | 7500 | 10000 | 7500 | 2000 | 7500 | 10000 | 13000 | 10000 | |
| Weight | | | | | | | | | | |
| Overall weight (kg) | | 555 | 590 | 555 | 295 | 560 | 570 | 890 | 1490 | 3500 |
| Dimensions | | | | | | | | | | |
| Maximum outreach (mm) | | 700 | 700 | 700 | 470 | 700 | 700 | 700 | 905 | 905 |
| Maximum outreach 2 (mm) | | 1350 | 1350 | 1350 | 1385 | 1350 | 1350 | 1250 | 2005 | 905 |
| Maximum outreach 3 (mm) | | 2000 | 2000 | 2000 | 2300 | 2000 | 2000 | 1800 | 3000 | 3000 |
| Weight and dimensions | | | | | | | | | | |
| Overall length (mm) | 11 | 2215 | 2215 | 2215 | 2518 | 2215 | 2215 | 2085 | 3351 | |
| Width (mm) | | 830 | 830 | 830 | 815 | 800 | 830 | 850 | 1170 | |
| Working Parameters | | | | | | | | | | |
| Required machine equipment | | \times | \times | \times | \times | \times | \times | \times | \times | |

| Reference number - - - - - - - - - 99700 Reference number E-RECO 5271740 52701740 52701740 5001001 5001001 55501001 55501001 55501001 55501001 - </th <th>Machines compatibility</th> <th>JH 16 T - 10 T - 7.5 T</th> <th>JH 20 T - 14 T - 10 T</th> <th>JH 13.5 T - 10 T - 7.5 T</th> <th>P 9 T</th> <th>P 13 T</th> <th>P 18 T</th> <th>P 25 T</th> <th>P 36 T</th> <th>P 40 T (Available upon request)</th> | Machines compatibility | JH 16 T - 10 T - 7.5 T | JH 20 T - 14 T - 10 T | JH 13.5 T - 10 T - 7.5 T | P 9 T | P 13 T | P 18 T | P 25 T | P 36 T | P 40 T (Available upon request) |
|--|-------------------------------|---------------------------|--------------------------|-----------------------------|--------|----------|----------|----------|----------|---------------------------------------|
| MHT 790 Mining STS - - X - - - - MHT 703 STS - - X - < | Reference number | - | - | - | | - | - | - | - | 939100 |
| MHT 700 ST5 | Reference number E-RECO | 52701741 | 52701742 | 52701740 | 930830 | 53009841 | 53011885 | 53010431 | 52604320 | - |
| MHT 1013S ST5x <t< td=""><td>MHT 790 Mining ST5</td><td></td><td></td><td></td><td>х</td><td></td><td></td><td></td><td></td><td></td></t<> | MHT 790 Mining ST5 | | | | х | | | | | |
| MHT 10160 ST5 x - - - - - - - MHT 10200 ST5 - - - - x - - MHT 11250 Mining ST5 - - - - x x - MHT 11230 ST5 - - - - x x - - MHT 1230 ST5 - - - x - x x - MHT 1230 ST5 - - x - x x - - x x - - x x - - x - - x - - - x - - x - | MHT 790 ST5 | | - | | х | | - | - | | |
| MHT 10200 ST5 . x MHT 11250 Mining ST5 . | MHT 10135 ST5 | | | х | | | | - | | |
| MHT 11250 Mining ST5 · · · · · · · × · MHT 11250 ST5 · · · · · · × | MHT 10160 ST5 | х | - | | - | | - | - | | |
| MHT 11250 ST3A< | MHT 10200 ST5 | | х | | | | | - | | |
| MHT 12330XXXMHTX 790 ST3AX | MHT 11250 Mining ST5 | | - | | - | | - | х | | |
| MHTX 790 ST3AXMHTX 10105 ST3AX <td>MHT 11250 ST5</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>х</td> <td></td> <td></td> | MHT 11250 ST5 | | | | | | | х | | |
| MHTX 10135 ST3A··· | MHT 12330 | | - | | - | | - | х | х | |
| MHTX 10160 ST3Ax | MHT-X 790 ST3A | | | | х | | | - | | |
| MHTX 10200 ST3A··· | MHT-X 10135 ST3A | - | - | х | - | - | - | - | - | |
| MHTX 11250 Mining <td>MHT-X 10160 ST3A</td> <td>х</td> <td></td> <td></td> <td></td> <td>-</td> <td></td> <td>-</td> <td></td> <td></td> | MHT-X 10160 ST3A | х | | | | - | | - | | |
| MHTX 11250 ST3A · | MHT-X 10200 ST3A | - | х | | - | - | - | - | - | - |
| MHTX 12330xxxMRT 2260 eX <td< td=""><td>MHT-X 11250 Mining</td><td></td><td></td><td></td><td></td><td>-</td><td></td><td>х</td><td></td><td></td></td<> | MHT-X 11250 Mining | | | | | - | | х | | |
| MRT 2260 e···X·· | MHT-X 11250 ST3A | - | - | | - | - | - | х | - | - |
| MRT 2570XMRT 2660 eX< | MHT-X 12330 | | | | | - | | х | х | |
| MRT 2660 eXMRT 3570XMRT 3570 ESX | MRT 2260 e | - | - | | х | - | - | - | - | - |
| MRT 3570 . x . x .< | MRT 2570 | - | - | | х | | - | - | | |
| MRT 3570 ES · · × · <th< td=""><td>MRT 2660 e</td><td>-</td><td>-</td><td>-</td><td>х</td><td>-</td><td>-</td><td>-</td><td>-</td><td></td></th<> | MRT 2660 e | - | - | - | х | - | - | - | - | |
| MRFX 2570 · · X · | MRT 3570 | | | | х | - | | - | | |
| MRT-X 3570 - - X - M M - | MRT 3570 ES | - | - | - | х | - | - | - | - | |
| MRFX 3570 ES · · X · <t< td=""><td>MRT-X 2570</td><td></td><td></td><td></td><td>х</td><td></td><td></td><td>-</td><td></td><td></td></t<> | MRT-X 2570 | | | | х | | | - | | |
| MHT 790 (LD) - - X - <t< td=""><td>MRT-X 3570</td><td>-</td><td>-</td><td>-</td><td>х</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></t<> | MRT-X 3570 | - | - | - | х | - | - | - | - | - |
| MHT 10130 CLD - - X X - <th< td=""><td>MRT-X 3570 ES</td><td></td><td></td><td></td><td>х</td><td></td><td></td><td>-</td><td></td><td></td></th<> | MRT-X 3570 ES | | | | х | | | - | | |
| MHT 10180 CLD - - - X - <th< td=""><td>MHT 790 OLD</td><td>-</td><td>-</td><td>-</td><td>Х</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></th<> | MHT 790 OLD | - | - | - | Х | - | - | - | - | - |
| MHT 10230 OLD · <th< td=""><td>MHT 10130 OLD</td><td></td><td></td><td></td><td></td><td>Х</td><td></td><td></td><td></td><td></td></th<> | MHT 10130 OLD | | | | | Х | | | | |
| MHT 14350 OLD - - - - X MHT-X 790 OLD - - X X - - X MHT-X 790 OLD - - X X - - - X MHT-X 790 OLD - - X X - <td< td=""><td>MHT 10180 OLD</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td><td>Х</td><td>-</td><td>-</td><td>-</td></td<> | MHT 10180 OLD | - | - | - | - | - | Х | - | - | - |
| MHFX 790 OLD · · X · | MHT 10230 OLD | | | | | | | Х | | |
| MHT-X 790 Mining OLD X | MHT 14350 OLD | - | - | - | - | - | - | - | - | Х |
| | MHT-X 790 OLD | | | | Х | | | | | |
| | MHT-X 790 Mining OLD | - | - | - | Х | - | - | - | - | - |
| MHTX 14350 OLD | MHT-X 14350 OLD | | | | | | | | | Х |
| MRT 2470 Privilege Plus OLD X | MRT 2470 Privilege Plus OLD | - | - | - | Х | - | - | - | - | - |
| MRTX 2470 Privilege Plus OLD · · · · · · · · · · · · · · · · · · · | MRT-X 2470 Privilege Plus OLD | | | | Х | | | | | |

| TABLE SYMBOL | | | |
|--------------|----------------------------|-------------------------|--|
| \times | No predisposition required | Hydraulic line | Return piping to hydraulic oil tank |
| | Electric predisposition | Platform predisposition | Tyre handler, cylinder handler predisposition |



Head Office B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes