

Technical sheet :

# EXTENSIBLE JIB



## Technical characteristics

- Capacity 600 kg/1323 lb @ 4 m/300 kg / 13 ft/662 lb @ 5 m/100 kg / 16 ft/212 lb @ 6 m / 20 ft.
- Safety: homologated rotating truss hook.
- Safety: self-locking, rotating homologated hook.
- Easy and safe manual extension.
- Integrated stabilizer for easy storage.

[The 3D picture at the top of this page is the reference JE 6000/600 - 939995].

## Customer benefits

- Simple & safe solution for the handling & the placement of roof trusses (packed or separated).
- User-friendly: dedicated truss hook & standard hook allowing the use as an extension jib.
- Maximum visibility during transport: adapted attachment design that allows driving the machine with a lowered machine boom.
- Increased safety with the dedicated truss hook: no need to climb on the trusses to release them once placed.
- Simple & durable attachment.

| Technical characteristics          |    | JE 6000 / 600 |
|------------------------------------|----|---------------|
| Distance to center of gravity (mm) |    | 1516          |
| Capacities                         |    |               |
| Capacity (kg)                      |    | 600           |
| Capacity 2 (kg)                    |    | 300           |
| Capacity 3 (kg)                    |    | 100           |
| Weight                             |    |               |
| Overall weight (kg)                |    | 265           |
| Dimensions                         |    |               |
| Max. outreach (mm)                 |    | 3895          |
| Maximum outreach 2 (mm)            |    | 4845          |
| Maximum outreach 3 (mm)            |    | 5845          |
| Weight and dimensions              |    |               |
| Overall length (mm)                | I1 | 4347          |
| Width (mm)                         |    | 815           |
| Working Parameters                 |    |               |
| Required machine equipment         |    | ✕             |

| Machines compatibility        |  | JE 6000 / 600 |
|-------------------------------|--|---------------|
| Reference number              |  | 939995        |
| MRT 2260                      |  | X             |
| MRT 2260 e                    |  | X             |
| MRT 2570                      |  | X             |
| MRT 2660                      |  | X             |
| MRT 2660 e                    |  | X             |
| MRT 3060                      |  | X             |
| MRT 3570                      |  | X             |
| MRT 3570 ES                   |  | X             |
| MRT-X 2260                    |  | X             |
| MRT-X 2570                    |  | X             |
| MRT-X 2660                    |  | X             |
| MRT-X 3060                    |  | X             |
| MRT-X 3570                    |  | X             |
| MRT-X 3570 ES                 |  | X             |
| MT 730 H                      |  | X             |
| MT 735 75D ST5                |  | X             |
| MT 930 H                      |  | X             |
| MT 935 75D ST5                |  | X             |
| MT 1135 75 D                  |  | X             |
| MT 1135                       |  | X             |
| MT 1135 H 100D                |  | X             |
| MT 1335 75D ST5               |  | X             |
| MT 1335 100D ST5              |  | X             |
| MT 1335 H 75D ST5             |  | X             |
| MT 1335 H 100D ST5            |  | X             |
| MT 1335 HA 75D ST5            |  | X             |
| MT 1335 HA 100D ST5           |  | X             |
| MT 1440                       |  | X             |
| MT 1440 A                     |  | X             |
| MT 1440 e                     |  | X             |
| MT 1440 HA                    |  | X             |
| MT 1840                       |  | X             |
| MT 1840 A                     |  | X             |
| MT 1840 e                     |  | X             |
| MT 1840 HA                    |  | X             |
| MT-X 735                      |  | X             |
| MT-X 1135                     |  | X             |
| MT-X 1440                     |  | X             |
| MT-X 1440 A                   |  | X             |
| MT-X 1840                     |  | X             |
| MT-X 1840 A                   |  | X             |
| MT 733 Easy <b>OLD</b>        |  | X             |
| MT 930 HA <b>OLD</b>          |  | X             |
| MT 933 Easy <b>OLD</b>        |  | X             |
| MT 1033 easy <b>OLD</b>       |  | X             |
| MT 1135 H easy ST5 <b>OLD</b> |  | X             |
| MT 1335 <b>OLD</b>            |  | X             |
| MT 1440 A ST4 <b>OLD</b>      |  | X             |
| MT 1440 HA ST4 <b>OLD</b>     |  | X             |
| MT 1840 A STG4 <b>OLD</b>     |  | X             |
| MT 1840 HA ST4 <b>OLD</b>     |  | X             |
| MT-X 1440 A <b>OLD</b>        |  | X             |
| MT-X 1840 A <b>OLD</b>        |  | X             |

| TABLE SYMBOL |                            |   |                |   |                                     |
|--------------|----------------------------|---|----------------|---|-------------------------------------|
| ✕            | No predisposition required |  | Hydraulic line |  | Return piping to hydraulic oil tank |

TABLE SYMBOL

|  |                         |  |                         |  |   |
|--|-------------------------|--|-------------------------|--|---|
|  | Electric predisposition |  | Platform predisposition |  | Tyre handler, cylinder handler predisposition |
|--|-------------------------|--|-------------------------|--|---|



**Head Office**

B.P. 249 - 430 rue de l'Aubinière  
44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

[www.manitou.com](http://www.manitou.com)



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes