

Technical sheet :

# SWING JIB





## Technical characteristics

- Single-hook jib fitted with a 15°/15° rotation.
- Hydraulic rotation for more accuracy.
- Simple & strong attachment.
- Homologated, rotating self locking hook.

[The 3D picture at the top of this page is the reference PO 600 / 2500 - 784641].

## Customer benefits

- Easy load placement directly from the cab.
- Especially interesting to place loads in narrow spaces.
- Improves efficiency-less time wasted placing the machine.
- Placement through rotation, not side shift = load moves backward when the jib swings.

| Technical characteristics          |     | PO 600 / 2500   | PO 1000 / 1500  | PO 2000 / 1000  |
|------------------------------------|-----|---|---|---|
| Distance to center of gravity (mm) |     | 720   | 450   | 243   |
| <b>Capacities</b>                  |     |   |   |   |
| Capacity (kg)                      |     | 600   | 1000  | 2000  |
| <b>Weight</b>                      |     |   |   |   |
| Overall weight (kg)                |     | 320   | 275   | 255   |
| <b>Dimensions</b>                  |     |   |   |   |
| Max. outreach (mm)                 |     | 2500  | 1500  | 1000  |
| <b>Weight and dimensions</b>       |     |   |   |   |
| Overall height (mm)                | h17 | 842   | 1056  | 842   |
| Overall length (mm)                | l1  | 2874  | 1874  | 1374  |
| Width (mm)                         |     | 830   | 830   | 830   |
| <b>Working Parameters</b>          |     |   |   |   |
| Required machine equipment         |     |  |  |  |
| Rotation 1 (°)                     |     | 15  | 15  | 15  |
| Rotation 2 (°)                     |     | 15  | 15  | 15  |

| Machines compatibility       | PO 600 / 2500 | PO 1000 / 1500 | PO 2000 / 1000 |
|------------------------------|---------------|----------------|----------------|
| Reference number             | 784641        | 784642         | 784643         |
| MT 730 H                     | X             | X              | X              |
| MT 735 75D ST5               | X             | X              | X              |
| MT 930 H                     | X             | X              | X              |
| MT 935 75D ST5               | X             | X              | X              |
| MT 1135 75 D                 | X             | X              | X              |
| MT 1135 H 100D               | X             | X              | X              |
| MT 1335 75D ST5              | X             | X              | X              |
| MT 1335 100D ST5             | X             | X              | X              |
| MT 1335 H 75D ST5            | X             | X              | X              |
| MT 1335 H 100D ST5           | X             | X              | X              |
| MT 1335 HA 75D ST5           | X             | X              | X              |
| MT 1335 HA 100D ST5          | X             | X              | X              |
| MT 1440                      | X             | X              | X              |
| MT 1440 A                    | X             | X              | X              |
| MT 1440 easy ST5             | X             | X              | X              |
| MT 1440 HA                   | X             | X              | X              |
| MT 1440 ST5                  | X             | X              | X              |
| MT 1840                      | X             | X              | X              |
| MT 1840 A                    | X             | -              | X              |
| MT 1840 easy ST5             | X             | X              | X              |
| MT 1840 HA                   | X             | -              | X              |
| MT 1840 ST5                  | X             | X              | X              |
| MT-X 735                     | X             | X              | X              |
| MT-X 1135                    | X             | X              | X              |
| MT-X 1440                    | X             | X              | X              |
| MT-X 1440 A                  | X             | X              | X              |
| MT-X 1840                    | X             | X              | X              |
| MT-X 1840 A                  | X             | -              | X              |
| MT 733 Easy <b>OLD</b>       | X             | X              | X              |
| MT 930 HA <b>OLD</b>         | X             | X              | X              |
| MT 933 Easy <b>OLD</b>       | X             | X              | X              |
| MT 1033 easy <b>OLD</b>      | X             | X              | X              |
| MT 1440 A ST4 <b>OLD</b>     | X             | X              | X              |
| MT 1440 A ST5 <b>OLD</b>     | X             | X              | X              |
| MT 1440 HA ST4 <b>OLD</b>    | X             | X              | X              |
| MT 1440 HA ST5 <b>OLD</b>    | X             | X              | X              |
| MT 1840 A ST5 S1 <b>OLD</b>  | X             | X              | X              |
| MT 1840 A STG4 <b>OLD</b>    | X             | X              | X              |
| MT 1840 HA ST4 <b>OLD</b>    | X             | X              | X              |
| MT 1840 HA ST5 S1 <b>OLD</b> | X             | X              | X              |
| MT-X 733 <b>OLD</b>          | X             | X              | X              |
| MT-X 1033 <b>OLD</b>         | X             | X              | X              |
| MT-X 1440 A <b>OLD</b>       | X             | X              | X              |
| MT-X 1840 A <b>OLD</b>       | X             | X              | X              |

| TABLE SYMBOL  |                            |   |                         |   |   |
|---|----------------------------|---|-------------------------|---|---|
|  | No predisposition required |  | Hydraulic line          |  | Return piping to hydraulic oil tank           |
|  | Electric predisposition    |  | Platform predisposition |  | Tyre handler, cylinder handler predisposition |



**Head Office**

B.P. 249 - 430 rue de l'Aubinière  
44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

[www.manitou.com](http://www.manitou.com)



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes