Technical sheet:

AERIAL JIB 2



Technical characteristics

- 344° total boom rotation of the attachment.
- Basket width: 1200 mm / 47 in x depth 800 mm / 31 in.
- Legally approved for 2 persons.
- Wide stand for maximum stability during positive/negative position switch.
- Telescopic boom (2300 mm / 91 in).

Customer benefits

- Maximum safety in people.
- Positive work area (+ 9,3 m / 31 ft).
- Negative work area (- 6,4 m / 21 ft).
- Forward reach work area (+ 6,81 m / 22 ft).



Technical characteristics		Aerial Jib 2	PAJ2 1200 / 200		
Capacity including people (kg)		200	200		
Number of people		2	2		
Distance to center of gravity (mm)		1358	1358		
Weight					
Overall weight (kg)		1100	1200		
Weight and dimensions					
Overall height (mm)	h17	2823	2823		
Overall length (mm)	l1	4492	4471		
Width (mm)		1200	1200		
Depth (mm)	р5	800	800		
Working Parameters					
Required machine equipment		88 E.	\$\$ E		
Rotation 1 (°)		344	172		
Rotation 2 (°)			172		

Machines compatibility	Aerial Jib 2	PAJ2 1200 / 200
Reference number E-RECO	921293	52719269
MRT 1645 75	- -	X
MRT 1645 75 MRT 1645 115		X
MRT 1845 75	·	X
MRT 1845 115		X
MRT 2145 115	·	X
MRT 2260		X
MRT 2260 e	•	X
MRT 2545 115		X
MRT 2570	•	X
MRT 2660		X
MRT 2660 e	·	X
MRT 3060		X
MRT 3570	·	X
MRT 3570 ES		X
MRT-X 1645	·	X
MRT-X 1840 Easy 360°	Х	•
MRT-X 1840 Easy 400°	X	•
MRT-X 1845	-	X
MRT-X 2145		X
MRT-X 2145 Easy 360°	Х	•
MRT-X 2145 Easy 400°	Х	
MRT-X 2150 Privilege Plus	Х	
MRT-X 2260		X
MRT-X 2545		Х
MRT-X 2545 Easy 360°	Х	
MRT-X 2545 Easy 400°	X	
MRT-X 2570		X
MRT-X 2660		X
MRT-X 3060		X
MRT-X 3255 Privilege Plus	X	·
MRT-X 3570	·	X
MRT-X 3570 ES		X
MRT 1440 Easy T4 S2 400° OLD	X	
MRT 1640 Easy T4 S2 360° OLD	X	·
MRT 1640 Easy T4 S2 400° OLD	X	
MRT 1840 Easy T4 S2 360° OLD	X	
MRT 1840 Easy T4 S2 400° OLD	X	
MRT 2145 Easy T4 S2 360° OLD	X	·
MRT 2145 Easy T4 S2 300 OLD	X	
MRT 2150 Privilege Plus OLD	X	
MRT 2545 Easy T4 S2 360° OLD	X	
MRT 2545 Easy T4 S2 400° OLD	X X	
MRT 3255 Privilege Plus OLD	X X	
Reference number E-RECO 2	X 53027154	
MRT-X 2150 Privilege Plus	530Z/154 X	
MRT-X 2470 Privilege Plus	X	- X
MRT-X 2470 Privilege Plus MRT-X 2550 Privilege Plus		
·	X	
MRT-X 3050 Privilege Plus	X	X
MRT-X 3255 Privilege Plus	x	•
MRT 2150 Privilege Plus OLD	X	
MRT 2470 Privilege Plus OLD	X	X
MRT 2550 Privilege Plus OLD	Х	
MRT 3050 Privilege Plus OLD	Х	X
MRT 3255 Privilege Plus OLD	Х	•

TABLE SYMBOL							
×	No predisposition required	88	Hydraulic line		Return piping to hydraulic oil tank		
	Electric predisposition		Platform predisposition		Tyre handler, cylinder handler predisposition		





Head Office

B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes