

Technical sheet :

SYSTEM 3D



Technical characteristics

- Telescopic vertical arm + negative.
- 170° boom rotation on both sides of the basket.
- Positive and negative work area for applications .
- Legally approved for 2 persons.
- Boom position sensor.
- Locking pin presence sensor.

Customer benefits

- Maximum safety in people.
- Pendular design and structure allowing underbridge operations.
- Non-slip metal flooring.

| Technical characteristics | | P 3D 1000 / 200 L6700 | P 3D 1000 / 200 L7500 | System 3D | System 3D (2) |
|------------------------------------|-----|-----------------------|-----------------------|-----------|---------------|
| Capacity including people (kg) | | 200 | 200 | 200 | 200 |
| Number of people | | 2 | 2 | 2 | 2 |
| Distance to center of gravity (mm) | | 2324 | 2099 | 1954 | 2099 |
| Weight | | | | | |
| Overall weight (kg) | | 1030 | 1030 | 1100 | 1025 |
| Weight and dimensions | | | | | |
| Overall height (mm) | h17 | 2900 | 2900 | 2900 | 2898 |
| Overall length (mm) | l1 | 7647 | 8390 | 7670 | 8409 |
| Width (mm) | | 1676 | 1676 | 1676 | 1676 |
| Depth (mm) | p5 | 680 | 620 | 620 | 620 |
| Maximum working reach (mm) | | 8170 | 8540 | 8170 | 8540 |
| Working Parameters | | | | | |
| Required machine equipment | | | | | |
| Rotation 1 (°) | | 170 | 170 | 170 | 170 |
| Rotation 2 (°) | | 170 | 170 | 170 | 170 |
| Working width - angled (mm) | | 1100 | 1100 | 1100 | 1100 |
| Working height positive (mm) | | 9560 | 11100 | 9560 | 11100 |
| Working outreach (mm) | | 6700 | 7500 | 8170 | 8540 |

| Machines compatibility | | P 3D 1000 / 200 L6700 | P 3D 1000 / 200 L7500 | System 3D | System 3D (2) |
|--------------------------------------|--|-----------------------|-----------------------|-----------|---------------|
| Reference number E-RECO | | 52719363 | 52719270 | 921311 | 921312 |
| MRT 1645 75 | | - | X | - | - |
| MRT 1645 115 | | - | X | - | - |
| MRT 1845 75 | | X | - | - | - |
| MRT 1845 115 | | X | - | - | - |
| MRT 2145 115 | | - | X | - | - |
| MRT 2260 | | - | X | - | - |
| MRT 2260 e | | - | X | - | - |
| MRT 2545 115 | | - | X | - | - |
| MRT 2570 | | - | X | - | - |
| MRT 2660 | | - | X | - | - |
| MRT 2660 e | | - | X | - | - |
| MRT 3060 | | - | X | - | - |
| MRT 3570 | | - | X | - | - |
| MRT 3570 ES | | - | X | - | - |
| MRT-X 1645 | | - | X | - | - |
| MRT-X 1845 | | X | - | - | - |
| MRT-X 2145 | | - | X | - | - |
| MRT-X 2260 | | - | X | - | - |
| MRT-X 2545 | | - | X | - | - |
| MRT-X 2570 | | - | X | - | - |
| MRT-X 2660 | | - | X | - | - |
| MRT-X 3060 | | - | X | - | - |
| MRT-X 3570 | | - | X | - | - |
| MRT-X 3570 ES | | - | X | - | - |
| MRT 1440 Easy T4 S2 400° OLD | | - | - | X | - |
| MRT 1640 Easy T4 S2 360° OLD | | - | - | - | X |
| MRT 1640 Easy T4 S2 400° OLD | | - | - | - | X |
| MRT 1840 Easy T4 S2 360° OLD | | - | - | X | - |
| MRT 1840 Easy T4 S2 400° OLD | | - | - | X | - |
| MRT 2145 Easy T4 S2 360° OLD | | - | - | X | - |
| MRT 2145 Easy T4 S2 400° OLD | | - | - | X | - |
| MRT 2150 Privilege Plus OLD | | - | - | - | X |
| MRT 2470 Privilege Plus OLD | | - | - | - | X |
| MRT 2545 Easy T4 S2 360° OLD | | - | - | X | - |
| MRT 2545 Easy T4 S2 400° OLD | | - | - | X | - |
| MRT 2550 Privilege Plus OLD | | - | - | - | X |
| MRT 3050 Privilege Plus OLD | | - | - | - | X |
| MRT 3255 Privilege Plus OLD | | - | - | - | X |
| MRT-X 1840 Easy 360° OLD | | - | - | X | - |
| MRT-X 1840 Easy 400° OLD | | - | - | X | - |
| MRT-X 2145 Easy 360° OLD | | - | - | X | - |
| MRT-X 2145 Easy 400° OLD | | - | - | X | - |
| MRT-X 2150 Privilege Plus OLD | | - | - | - | X |
| MRT-X 2470 Privilege Plus OLD | | - | - | - | X |
| MRT-X 2545 Easy 360° OLD | | - | - | X | - |
| MRT-X 2545 Easy 400° OLD | | - | - | X | - |
| MRT-X 2550 Privilege Plus OLD | | - | - | - | X |
| MRT-X 3050 Privilege Plus OLD | | - | - | - | X |
| MRT-X 3255 Privilege Plus OLD | | - | - | - | X |
| Reference number E-RECO 2 | | 52719674 | 52719672 | - | 53027160 |
| MRT 1645 75 | | - | X | - | - |
| MRT 1645 115 | | - | X | - | - |
| MRT 1845 75 | | X | - | - | - |
| MRT 1845 115 | | X | - | - | - |
| MRT 2145 115 | | - | X | - | - |
| MRT 2260 | | - | X | - | - |
| MRT 2260 e | | - | X | - | - |
| MRT 2545 115 | | - | X | - | - |

| Machines compatibility | P 3D 1000 / 200 L6700 | P 3D 1000 / 200 L7500 | System 3D | System 3D (2) |
|-------------------------------------|-----------------------|-----------------------|-----------|---------------|
| MRT 2570 | - | X | - | - |
| MRT 2660 | - | X | - | - |
| MRT 2660 e | - | X | - | - |
| MRT 3060 | - | X | - | - |
| MRT 3570 | - | X | - | - |
| MRT 3570 ES | - | X | - | - |
| MRT-X 1645 | - | X | - | - |
| MRT-X 1845 | X | - | - | - |
| MRT-X 2145 | - | X | - | - |
| MRT-X 2260 | - | X | - | - |
| MRT-X 2545 | - | X | - | - |
| MRT-X 2570 | - | X | - | - |
| MRT-X 2660 | - | X | - | - |
| MRT-X 3060 | - | X | - | - |
| MRT-X 3570 | - | X | - | - |
| MRT-X 3570 ES | - | X | - | - |
| MRT 1440 Easy T4 S1 400° OLD | - | - | X | - |
| MRT 1840 Easy T4 S2 360° OLD | - | - | X | - |
| MRT 1840 Easy T4 S2 400° OLD | - | - | X | - |
| MRT-X 1840 Easy 360° OLD | - | - | X | - |
| MRT-X 1840 Easy 400° OLD | - | - | X | - |

| TABLE SYMBOL | | | | | |
|--------------|----------------------------|--|-------------------------|--|---|
| | No predisposition required | | Hydraulic line | | Return piping to hydraulic oil tank |
| | Electric predisposition | | Platform predisposition | | Tyre handler, cylinder handler predisposition |



Head Office

B.P. 249 - 430 rue de l'Aubinière
44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes