

技術シート：

# SYSTEM 3D



## お客様のメリット

- Maximum safety in people.
- Pendular design and structure allowing underbridge operations.
- Non-slip metal flooring.

## 諸元






- Telescopic vertical arm + negative.
- 170° boom rotation on both sides of the basket.
- Positive and negative work area for applications .
- Legally approved for 2 persons.
- Boom position sensor.
- Locking pin presence sensor.

諸元		P 3D 1000 / 200 L6700	P 3D 1000 / 200 L7500	System 3D (2)	システム 3D
人員を含む容量 (kg)		200	200	200	200
人員数		2	2	2	2
重心位置までの距離 (mm)		2324	2099	2099	1954
<b>重量</b>					
重量 (kg)		1030	1030	1025	1100
<b>仕様</b>					
全高 (mm)	h17	2900	2900	2898	2900
全長 (mm)	l1	7647	8390	8409	7670
幅 (mm)		1676	1676	1676	1676
深さ (mm)	p5	680	620	620	620
最大作業範囲 (mm)		8170	8540	8540	8170
<b>ワーキング パラメーター</b>					
機械設備					
回転 1 (°)		170	170	170	170
回転 2 (°)		170	170	170	170
作業時幅角度 (mm)		1100	1100	1100	1100
作業高 - ポジティブ (mm)		9560	11100	11100	9560
作業時アウトリーチ (mm)		6700	7500	8540	8170

マシンの互換性		P 3D 1000 / 200 L6700	P 3D 1000 / 200 L7500	System 3D (2)	システム 3D
参照番号 E-RECO		52719363	52719270	921312	921311
MRT 1645 75		-	X	-	-
MRT 1645 115		-	X	-	-
MRT 1845 75		X	-	-	-
MRT 1845 115		X	-	-	-
MRT 2145 115		-	X	-	-
MRT 2260		-	X	-	-
MRT 2260 e		-	X	-	-
MRT 2545 115		-	X	-	-
MRT 2570		-	X	-	-
MRT 2660		-	X	-	-
MRT 2660 e		-	X	-	-
MRT 3060		-	X	-	-
MRT 3570		-	X	-	-
MRT 3570 ES		-	X	-	-
MRT-X 1645		-	X	-	-
MRT-X 1845		X	-	-	-
MRT-X 2145		-	X	-	-
MRT-X 2260		-	X	-	-
MRT-X 2545		-	X	-	-
MRT-X 2570		-	X	-	-
MRT-X 2660		-	X	-	-
MRT-X 3060		-	X	-	-
MRT-X 3570		-	X	-	-
MRT-X 3570 ES		-	X	-	-
MRT 1440 Easy T4 S2 400° <b>OLD</b>		-	-	-	X
MRT 1640 Easy T4 S2 360° <b>OLD</b>		-	-	X	-
MRT 1640 Easy T4 S2 400° <b>OLD</b>		-	-	X	-
MRT 1840 Easy T4 S2 360° <b>OLD</b>		-	-	-	X
MRT 1840 Easy T4 S2 400° <b>OLD</b>		-	-	-	X
MRT 2145 Easy T4 S2 360° <b>OLD</b>		-	-	-	X
MRT 2145 Easy T4 S2 400° <b>OLD</b>		-	-	-	X
MRT 2150 Privilege Plus <b>OLD</b>		-	-	X	-
MRT 2470 Privilege Plus <b>OLD</b>		-	-	X	-
MRT 2545 Easy T4 S2 360° <b>OLD</b>		-	-	-	X
MRT 2545 Easy T4 S2 400° <b>OLD</b>		-	-	-	X
MRT 2550 Privilege Plus <b>OLD</b>		-	-	X	-
MRT 3050 Privilege Plus <b>OLD</b>		-	-	X	-
MRT 3255 Privilege Plus <b>OLD</b>		-	-	X	-
MRT-X 1840 Easy 360° <b>OLD</b>		-	-	-	X
MRT-X 1840 Easy 400° <b>OLD</b>		-	-	-	X
MRT-X 2145 Easy 360° <b>OLD</b>		-	-	-	X
MRT-X 2145 Easy 400° <b>OLD</b>		-	-	-	X
MRT-X 2150 Privilege Plus <b>OLD</b>		-	-	X	-
MRT-X 2470 Privilege Plus <b>OLD</b>		-	-	X	-
MRT-X 2545 Easy 360° <b>OLD</b>		-	-	-	X
MRT-X 2545 Easy 400° <b>OLD</b>		-	-	-	X
MRT-X 2550 Privilege Plus <b>OLD</b>		-	-	X	-
MRT-X 3050 Privilege Plus <b>OLD</b>		-	-	X	-
MRT-X 3255 Privilege Plus <b>OLD</b>		-	-	X	-
参照番号 E-RECO 2		52719674	52719672	53027160	-
MRT 1645 75		-	X	-	-
MRT 1645 115		-	X	-	-
MRT 1845 75		X	-	-	-
MRT 1845 115		X	-	-	-
MRT 2145 115		-	X	-	-
MRT 2260		-	X	-	-
MRT 2260 e		-	X	-	-
MRT 2545 115		-	X	-	-

マシンの互換性	P 3D 1000 / 200 L6700	P 3D 1000 / 200 L7500	System 3D (2)	システム 3D
MRT 2570	-	X	-	-
MRT 2660	-	X	-	-
MRT 2660 e	-	X	-	-
MRT 3060	-	X	-	-
MRT 3570	-	X	-	-
MRT 3570 ES	-	X	-	-
MRT-X 1645	-	X	-	-
MRT-X 1845	X	-	-	-
MRT-X 2145	-	X	-	-
MRT-X 2260	-	X	-	-
MRT-X 2545	-	X	-	-
MRT-X 2570	-	X	-	-
MRT-X 2660	-	X	-	-
MRT-X 3060	-	X	-	-
MRT-X 3570	-	X	-	-
MRT-X 3570 ES	-	X	-	-
MRT 1440 Easy T4 S1 400° <b>OLD</b>	-	-	-	X
MRT 1840 Easy T4 S2 360° <b>OLD</b>	-	-	-	X
MRT 1840 Easy T4 S2 400° <b>OLD</b>	-	-	-	X
MRT-X 1840 Easy 360° <b>OLD</b>	-	-	-	X
MRT-X 1840 Easy 400° <b>OLD</b>	-	-	-	X

## 記号の表

	前処理が不要		油圧ライン		タンクへの油圧リターン
	電気要素		プラットフォーム要素		タイヤクランプ、シリンダークランプ要素



# **MANITOU** HANDLING YOUR WORLD

## 本社ビル

B.P. 249 - 430 rue de l'Aubinière オービニエール通り

44150 Ancenis Cedex - France

電話 +33 (0)2 40 09 10 11 - ファックス +33 (0)2 40 09 10 97

[www.manitou.com](http://www.manitou.com)



本書では、マニトウ製品の構成バージョンやオプションについて説明していますが、機器によって異なる場合があります。このパンフレットで紹介されている機器は、バージョンによってシリーズの一部であったり、オプションであったり、あるいは利用できない場合があります。Manitouは、いつでも予告なしに、記載・表現されている仕様を変更する権利を有します。提供された仕様はメーカーを拘束するものではありません。詳細につきましては、マニトウの代理店にお問い合わせください。本資料は、契約上の拘束力を有するものではありません。製品の提示は、契約上の拘束力はありません。仕様のリストは無尽蔵です。ロゴおよび会社のビジュアル・アイデンティティはManitouが所有しており、許可なく使用することはできません。すべての権利はマニトウに帰属します。このパンフレットに掲載されている写真や図は、相談や情報提供を目的としています。

MANITOU BF SA - 取締役会を有する有限会社・株式資本。39 668 399 ユーロ - 857 802 508 RCS Nantes