Technical sheet:

SLIM TYRE HANDLER



Technical characteristics

- Maximum capacity up to 2900 kg / 6939 lb.
- · Clamping with forks, 93 mm / 4 in thin.
- Accept a wide variety of tyre diameters.
- Compact design, centre of gravity stays close to the telehandler.
- Body rotation : ± 360°.
- Constant side shift: ± 100 mm / 4 in.
- Control: from cab or remote control (MHT).

[The 3D picture at the top of this page is the reference TH $35 / 2900 \ S - 939040$].

Customer benefits

- A compact solution for all limited-access tyre removal operations.
- Fork-based concept (2 pairs of forks), suitable for underground mining trucks.
- Perfect tyre holding, fork covered with anti-slip material.
- Available on several telehandler types.
- Limited machine downtime.



2000 1160 916 1743 93 1360 1149 480 / 2100	2900 1345 916 1841 107 1650 1199 650 / 2650	
916 1743 93 1360 1149	916 1841 107 1650 1199	
916 1743 93 1360 1149	916 1841 107 1650 1199	
1743 93 1360 1149	1841 107 1650 1199	
1743 93 1360 1149	1841 107 1650 1199	
93 1360 1149	107 1650 1199	
1360 1149	1650 1199	
1149	1199	
480 / 2100	650 / 2650	
	650 / 2650	
360	360	
470 640		
2120 2700		
4	4	
	360 470 2120	

Machines compatibility	TH 33 / 2000 S	TH 35 / 2900 S		
Reference number	939039	939040		
MT-X 733 Mining	Х			
MT-X 1033 Mining	Х			
MT-X 1033 A Mining	Х			
MHT-X 860 S2 OLD	X	X		
MLT 845-100 H OLD	Х	Х		
MLT 845-120 OLD	X	X		
MLT-X 845-120 OLD	Х	Х		
MLT-X 845-120 H OLD	X	X		
Reference number E-RECO	939039	939040		

Reference number E-RECO	939039	939040
MHT 790	Х	Х
MHT 790 Mining ST5	Х	X
MHT 790 ST5	Х	X
MHT-X 790 ST3A	Х	Х
MHT-X 790 OLD	X	Х
MHT-X 790 Mining OLD	γ	γ

MIT I'M / 90 Millilling OLD	X	X.
Reference number E-RECO 2	52721340	
MRT 2260	Х	
MRT 2260 e	Х	·
MRT 2570	X	
MRT 2660	Х	
MRT 2660 e	X	
MRT 3060	Х	
MRT 3570	X	
MRT 3570 ES	X	
MRT-X 2260	X	
MRT-X 2570	X	
MRT-X 2660	X	
MRT-X 3060	X	
MRT-X 3570	X	·
MRT-X 3570 ES	X	

TABLE SYMBOL							
×	No predisposition required	88	Hydraulic line		Return piping to hydraulic oil tank		
	Electric predisposition		Platform predisposition		Tyre handler, cylinder handler predisposition		





Head Office

B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes