Technical sheet:

HIGH CAPACITY SILAGE & MANURE GRAB



Technical characteristics

- Large capacity 2000 L / 71 ft³.
- · Grapple rotation stops ensure long life for hydraulic cylinders.
- · Bolt-on teeth and tines for easy maintenance.
- High quality wear resistant and high yield steels used extensively.
- Teeth: Ø 45 mm / 2 in, 939 mm / 37 in.
- Tines: Ø 45 mm / 2 in, 1100 mm / 43 in.
- For silage and light straw manure. Max 700 kg/m³ / 44 lb/ft³.

[The 3D picture at the top of this page is the reference FMG 2450 / 2000 - 790534].

Customer benefits

- Massive and efficient attachment.
- · Excellent visibility thanks to innovative design.
- The best solution for manure handling.
- Improved design allows working flush with walls.
- Versatile attachment that enables occasional square bale handling.





Capacities		FMG 2100 / 1800 ONLY UK IRL	FMG 2450 / 2000		
Capacity (kg)		1260	1400		
Heaped capacity (I)		1800	2000		
Weight					
Overall weight (kg)		510	686		
Weight and dimensions					
Overall length (mm)	I1	1352	1381		
Forks length (mm)	ı	990	990		
Width (mm)		2100	2435		
Closed grapple height (mm)	h33	1223	1201		
Working Parameters					
Required machine equipment		\\ \\ \	 		
Teeth / Fingers		4 / 10	5 / 12		
Minimum forks spread (mm)	b5	221	210		
Maximum forks spread (mm)	b5	637	554		

Mart Colon 15 (15) X	Machines compatibility	FMG 2100 / 1800 ONLY UK IRL	FMG 2450 / 2000
MIT 630-115 V(151) MIT 630-115 V(161) MIT 630-130 Pec (51) MIT 630-130 V(102) MIT 630-130 V(102) MIT 630-130 V(102) MIT 730-130 Pec (31) MIT 730-130	Reference number	52000082	790534
MET 69519 VOP (93) MET 69510 PSP (90) MET 69510 PSP (90) MET 69510 PSP (90) MET 695110 PSP (90) MET 695110 PSP (90) MET 695115 SSP (90) MET 795115 SS	MLT 630-115 (S1)	Х	
MET 69519 VOP (93) MET 69510 PSP (90) MET 69510 PSP (90) MET 69510 PSP (90) MET 695110 PSP (90) MET 695110 PSP (90) MET 695115 SSP (90) MET 795115 SS	MLT 630-115 V (S1)	Х	
MIT 165-140 V+ (SI)		X	
MIT 165-140 V+ (SI)	MLT 635-130 PS+ (S1)		Х
MIT 455-140 W (51) MIT 733-115 (52) MIT 733-115 (53) MIT 733-115 (52) MIT	. ,		
MIT 739-115 (SZ)			Х
MUT 739-115 (S2) MUT 739-115 (S2) MUT 739-115 (S2) MUT 739-115 (S2) MUT 739-115 (S3) MUT 739-115 (S4) MUT 739-115 (S4) MUT 739-115 (S4) MUT 739-115 (S5) MUT 741-130 (S4) (S1) MUT 741-130 (S4) (S4) (S4) (S4) (S4) (S4) (S4) (S4)	` '		
MLT 733-115 LSU (S)	` '	·	
MLT 739-130 PS+ (S1) MLT 739-130 PS+ 74 (UL) MLT 739-130 PS+ (UL) MLT 739			
MLT 738-130 PSc (SI) MLT 738-130 PSc (SI) MLT 741-140 VC (SI) MLT 741	, ,	·	
MLT 73-130 RS+ (S1) MLT 741-130 RS+ (S1) MLT 741-140 RS+ (S1) M	, ,		
MLT 741-140 V+ (51) MLT 742-140 V+ (51) MLT 841-145 PSP MLT 851-145 V+ MLT 851-150 V+	, ,		
MLT 74-140 VF (51) MLT 742-140 VF (51) - MLT 742-140 VF (51) - MLT 742-140 VF (51) - MLT 841-145 PSF - MLT 841-145 PSF - MLT 841-145 PSF - MLT 940-140 VF (51) - MLT 940-140 VF (51) - MLT 940-140 VF (52) - MLT 940-140 VF (51) - MLT 940-140 VF			
MLT 742-130 PS+ (S1)			
MIT 782-140 V+ (S1)			
MLT 847-145 PS+			
MLT 850-145 V+ (S1)	` '		
MLT 940-140 V+ (ST) MLT 940-140 V+ (SZ) MLT 961-160 V+ L MLT 1041-145 PS+L MLT X22 MLT X232 MLT X25 TLSU ML			
MLT 940-140 V+ (\$2) MLT 940-140 V+ (\$2) MLT 940-140 V+ (\$2) MLT 940-140 V+ (\$2) MLT 1041-145 PS+L MLT 732			
MLT 961-160 V+ L MLT 101-145 PS+L MLT 735 T LSU MLTX 735 T LSU MLTX 735 T LSU MLTX 737 S 1 SU MLTX 841 - 145 PS+ MLTX 850-145 V+ MLTX 850-145 V+ MLTX 850-145 V S X MLTX 101-145 PS+L MLT 850-105 S 1 CUD MLT 630-105 S 1 CUD MLT 737-310 S 1 CUD MLTX 737-310 S 1	` '		
MLT 1041-145 PS+L MLT 2732	` '		
MIFX 735 T LSU			
MLEX 735 T LSU			
MLFX 738-130 PS+ (S1) MLFX 741 T LSU - MLFX 841-145 PS+ MLFX 851-145 V+ - MLFX 961-160 V+ L MLFX 961-160 V+ L MLFX 961-160 V+ L MLFX 961-160 V+ C MLFX 961-			
MLEX 741 T LSU			
MLTX 850-145 V+	, ,		
MLFX 950-145 V+			
MLFX 961-160 V+ L . X MLFX 1041-145 PS+L . X MLT 630-105 ST4 OLD X . MLT 630-105 V CP ST4 OLD X . MLT 635-130 PS+ ST4 OLD X . MLT 635-140 V+ ST4 OLD X . MLT 733-115 LSU ST4 OLD X . MLT 733-115 SU ST4 OLD X X MLT 733-110 PS+ ST4 OLD X X MLT 731-130 PS+ ST4 OLD X X MLT 741-140 V+ ST4 OLD X X MLT 840-145 PS+ OLD X X MLT 940-140 V+ ST4 OLD X X MLT 737-130 PS+ (S2) OLD X X MLT 737-130 PS+ (S2) OLD X X MLEX 740-140 V+ S1 OLD X X			
MLTX 1041-145 PS+L			
MLT 630-105 ST4 OLD			
MLT 630-105 V CP ST4 OLD			
MLT 630-105 V ST4 OLD MLT 635-130 PS+ ST4 OLD MLT 635-140 V+ ST4 OLD MLT 733-115 LSU ST4 OLD MLT 733-115 ST4 OLD MLT 733-115 ST4 OLD MLT 737-130 PS+ ST4 OLD MLT 741-140 V+ ST4 OLD MLT 741-140 V+ ST4 OLD MLT 840-145 PS+ OLD MLT 940-140 V+ ST4 OLD MLT 940-145 PS+ OLD MLT 1040-145 PS+ L OLD MLT WAS	_		
MLT 635-130 PS+ ST4			
MLT 635-140 V+ ST4 OLD			
MLT 733-115 LSU ST4 OLD			
MLT 733-115 ST4 OLD			
MLT 737-130 PS+ ST4 OLD			
MLT 741-140 V+ ST4 OLD			
MLT 840-145 PS+ OLD			
MLT 940-140 V+ ST4 OLD			
MLT 961-145 V+ L OLD - X MLT 1040-145 PS+ L OLD - X MLT-X 737-130 PS+ OLD - X MLT-X 737-130 PS+ (S2) OLD - X MLT-X 737-130 PS+ (S2) OLD - X MLT-X 741-140 V+ S1 OLD - X MLT-X 840-140 PS+ OLD - X MLT-X 961-145 V+ L OLD - X			
MLT 1040-145 PS+ L OLD			
MLT-X 737-130 PS+ OLD			
MLT-X 737-130 PS+ (S2) OLD	_		
MLT-X 741-140 V+ S1 OLD - X MLT-X 840-140 PS+ OLD - X MLT-X 961-145 V+ L OLD - X			
MLT-X 840-140 PS+ OLD . X MLT-X 961-145 V+ L OLD . X			
MLT-X 961-145 V+ L OLD - X			
MLT-X 1040-140 PS+ L (OLD) - X			
	MLI-X 1040-140 PS+ L OLD		Х

TABLE SYMBOL						
X	No predisposition required	88	Hydraulic line		Return piping to hydraulic oil tank	
	Electric predisposition		Platform predisposition		Tyre handler, cylinder handler predisposition	

High Capacity Silage & Manure Grab - Dimensional drawing









Head Office

B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes