

Technical sheet :

PICKUP SWEEPER



Customer benefits







- High output attachment for the most demanding applications.
- Sweep and pick-up in one operation.
- Up to 2500 m² / 26910 ft² cleaned in 10 minutes.
- High quality sweeping on uneven ground.
- Interchangeable side brush (right or left) for a perfect sweeping along wall and sidewalks.

Technical characteristics

- Floating frame which avoids any squashing the attachment when driving on the bumpy road.
- ø 230 mm / 9 in side brush in polyester and galvanized steel.
- Synchronisation valve: sweep and control the dirt tank with 1 single hydraulic function.
- Pressure limiter for powerful machine.
- Brush ø 600 mm / 24 in.
- 4x ø 200 mm / 8 in heavy duty wheels.
- Recommended option: continuous hydraulic flow.

| Technical characteristics | | BRB 1600 | BRB 2200 | BRB 2500 |
|------------------------------------|-----|---|---|---|
| Distance to center of gravity (mm) | | 1050 | 1050 | 1050 |
| Weight | | | | |
| Overall weight (kg) | | 775 | 925 | 1000 |
| Weight and dimensions | | | | |
| Overall height (mm) | h17 | 1068 | 1068 | 1068 |
| Overall length (mm) | l1 | 2370 | 2370 | 2370 |
| Width (mm) | | 2000 | 2600 | 2900 |
| Working Parameters | | | | |
| Machine Equipment | |  |  |  |

| Machines compatibility | BRB 1600 | BRB 2200 | BRB 2500 |
|--------------------------------|----------|----------|----------|
| Reference number | 790313 | 790315 | 790316 |
| MLT 625-75 H | X | - | - |
| MLT 635-130 PS+ | - | X | - |
| MLT 635-140 V+ | - | X | - |
| MLT 841-145 PS+ | - | X | - |
| MLT 850-145 V+ | - | X | - |
| MLT 961-160 V+ L | - | X | X |
| MLT 1041-145 PS+L | - | X | - |
| MLFX 625-75 H | X | - | - |
| MLFX 735 T LSU | - | X | - |
| MLFX 741 T LSU | - | X | - |
| MLFX 841 - 145 PS+ | - | X | - |
| MLFX 850-145 V+ | - | X | - |
| MLFX 961-160 V+ L | - | X | X |
| MLFX 1041-145 PS+L | - | X | - |
| MT 625 H | X | - | - |
| MT 625 H Comfort | X | - | - |
| MT 625 HA | X | - | - |
| MLT 635-130 PS+ ST4 OLD | - | X | - |
| MLT 635-140 V+ ST4 OLD | - | X | - |
| MLT 737-130 PS+ ST4 OLD | - | X | - |
| MLT 741-140 V+ ST4 OLD | - | X | - |
| MLT 840-145 PS+ OLD | - | X | - |
| MLT 940-140 V+ ST4 OLD | - | X | - |
| MLT 961-145 V+ L OLD | - | X | X |
| MLFX 737-130 PS+ OLD | - | X | - |
| MLFX 741-140 V+ S1 OLD | - | X | - |
| MLFX 840-140 PS+ OLD | - | X | - |
| MLFX 961-145 V+ L OLD | - | X | X |

| TABLE SYMBOL | | | | | |
|---|----------------------------|---|-------------------------|---|---|
|  | No predisposition required |  | Hydraulic line |  | Return piping to hydraulic oil tank |
|  | Electric predisposition |  | Platform predisposition |  | Tyre handler, cylinder handler predisposition |



Head Office

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes