

Technical sheet :

FLOATING FORK CARRIAGE WITH HYDRAULIC LEVELING



Technical characteristics

- Pin-type floating forks.
- Max. fork spread 1180 mm / 46 in (external fork edge).
- Note: road circulation kit mandatory in Italy. Contact your dealer
- Note: road circulation kit mandatory in Germany on MRT Vision/
Vision+. Contact your dealer


Customer benefits

- Easy pallet collection & placement with the hydraulic carriage levelling.
- Simplicity & accuracy: levelling with a hydraulic cylinder.

Technical characteristics		CAF 1200 / 5 B L	TFF 1230 + Levelling (a)
Distance to center of gravity (mm)		397	258
Capacities			
Capacity (kg)		5000	4900
Weight			
Overall weight (kg)		630	617
Weight and dimensions			
Overall height (mm)	h17	1320	1420
Overall length (mm)	l1	1703	1545
Width (mm)		1311	1311
Working Parameters			
Required machine equipment			
Minimum forks spread (mm)	b5	1180	1010
Available fork dimensions			
125 x 50 x 1200		52762430	924876

Machines compatibility		CAF 1200 / 5 B L	TFF 1230 + Levelling (a)
MRT 1645 75		-	X
MRT 1645 115		-	X
MRT 1845 75		-	X
MRT 1845 115		-	X
MRT 2145 115		-	X
MRT 2260		X	-
MRT 2260 e		X	-
MRT 2545 115		-	X
MRT 2570		X	-
MRT 2660		X	-
MRT 2660 e		X	-
MRT 3060		X	-
MRT 3570		X	-
MRT 3570 ES		X	-
MRT-X 1645		-	X
MRT-X 1845		-	X
MRT-X 2145		-	X
MRT-X 2260		X	-
MRT-X 2545		-	X
MRT-X 2570		X	-
MRT-X 2660		X	-
MRT-X 3060		X	-
MRT-X 3570		X	-
MRT-X 3570 ES		X	-
MRT 1440 Easy T4 S2 400° <small>OLD</small>		-	X
MRT 1640 Easy T4 S2 360° <small>OLD</small>		-	X
MRT 1640 Easy T4 S2 400° <small>OLD</small>		-	X
MRT 1840 Easy T4 S2 360° <small>OLD</small>		-	X
MRT 1840 Easy T4 S2 400° <small>OLD</small>		-	X
MRT 2145 Easy T4 S2 360° <small>OLD</small>		-	X
MRT 2145 Easy T4 S2 400° <small>OLD</small>		-	X
MRT 2150 Privilege Plus <small>OLD</small>		-	X
MRT 2470 Privilege Plus <small>OLD</small>		-	X
MRT 2545 Easy T4 S2 360° <small>OLD</small>		-	X
MRT 2545 Easy T4 S2 400° <small>OLD</small>		-	X
MRT 2550 Privilege Plus <small>OLD</small>		-	X
MRT 3050 Privilege Plus <small>OLD</small>		-	X
MRT-X 1840 Easy 360° <small>OLD</small>		-	X
MRT-X 1840 Easy 400° <small>OLD</small>		-	X
MRT-X 2145 Easy 360° <small>OLD</small>		-	X
MRT-X 2145 Easy 400° <small>OLD</small>		-	X
MRT-X 2150 Privilege Plus <small>OLD</small>		-	X
MRT-X 2470 Privilege Plus <small>OLD</small>		-	X
MRT-X 2545 Easy 360° <small>OLD</small>		-	X
MRT-X 2545 Easy 400° <small>OLD</small>		-	X
MRT-X 2550 Privilege Plus <small>OLD</small>		-	X
MRT-X 3050 Privilege Plus <small>OLD</small>		-	X

TABLE SYMBOL					
	No predisposition required		Hydraulic line		Return piping to hydraulic oil tank
	Electric predisposition		Platform predisposition		Tyre handler, cylinder handler predisposition



MANITOU HANDLING YOUR WORLD

Head Office

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes