

Technical sheet :

# ENVIRONMENT BUCKET



## Technical characteristics

- Extensive use of high resistance steel: body made of S355 steel, side knives, 500 HB lower wear pads and bolt-on blades.
- 3° angle between the bolt-on blade & the bucket's floor for more longevity.
- Massive structure adapted to the recycling conditions (carriage, bottom, body).
- Integrated spill guard to limit material loss while traveling.
- Max. material density: 1000 kg/m<sup>3</sup> / 62 lb/ft<sup>3</sup>.

[The 3D picture at the top of this page is the reference CBA 2500 / 3200 EN - 52000125].

## Customer benefits

- Bucket developed for a severe, daily use.
- Ideal attachment for the handling of bulk materials (paper, crushed green waste).
- Flat bottom for an easy penetration in the waste pit & an efficient unloading.


Technical characteristics	BEN 2500 / 3000 WP	CBA 2450 / 2200 EN	CBA 2500 / 3200 EN
Distance to center of gravity (mm)	679	642	652
<b>Capacities</b>			
Capacity (kg)	2900	2224	3197
Heaped capacity (l)	2900	2224	3197
Struck capacity (l)	2300	1371	2485
<b>Weight</b>			
Overall weight (kg)	1030	911	1110
<b>Weight and dimensions</b>			
Overall height (mm)	h17	1323	1223
Overall length (mm)	l1	1746	1487
Width (mm)		2500	2450
<b>Working Parameters</b>			
Required machine equipment	✗	✗	✗
<b>Other Data for Attachments</b>			
Bolted wearplate (LDR)	Standard	Standard	Standard
Wear plate hardness	500	500	500

Machines compatibility	BEN 2500 / 3000 WP	CBA 2450 / 2200 EN	CBA 2500 / 3200 EN
Reference number	52736126	52000524	52000125
ALT950	-	X	-
MLA-T 533-145 V+ - ST5	-	X	-
MLT 635-130 PS+ (S1)	-	X	-
MLT 635-130 PS+ (S2)	X	X	-
MLT 635-140 V+ (S1)	-	X	-
MLT 635-140 V+ (S2)	X	X	-
MLT 733-115	-	X	-
MLT 733-115 (S2)	-	X	-
MLT 733-115 LSU (S1)	-	X	-
MLT 737-130 PS+ (S1)	-	X	-
MLT 738-130 PS+ (S1)	X	X	-
MLT 741-130 PS+ (S1)	-	X	-
MLT 741-140 V+ (S1)	-	X	-
MLT 742-130 PS+ (S1)	X	X	-
MLT 742-140 V+ (S1)	X	X	-
MLT 841-145 PS+	-	X	-
MLT 850-145 V+	X	-	X
MLT 937-115 (S1)	X	-	-
MLT 961-160 V+ L	-	-	X
MLT 1041-145 PS+L	-	X	-
MLTX 738-130 PS+ (S1)	X	X	-
MLTX 741 T LSU	-	X	-
MLTX 841 - 145 PS+	-	X	-
MLTX 850-145 V+	X	-	X
MLTX 961-160 V+ L	-	-	X
MLTX 1041-145 PS+L	-	X	-
MLT 635-130 PS+ ST4 <span style="background-color: #d3d3d3; border: 1px solid black; padding: 0 2px;">OLD</span>	-	X	-
MLT 635-140 V+ ST4 <span style="background-color: #d3d3d3; border: 1px solid black; padding: 0 2px;">OLD</span>	-	X	-
MLT 733-115 LSU ST4 <span style="background-color: #d3d3d3; border: 1px solid black; padding: 0 2px;">OLD</span>	-	X	-
MLT 733-115 ST4 <span style="background-color: #d3d3d3; border: 1px solid black; padding: 0 2px;">OLD</span>	-	X	-
MLT 737-130 PS+ ST4 <span style="background-color: #d3d3d3; border: 1px solid black; padding: 0 2px;">OLD</span>	-	X	-
MLT 741-140 V+ ST4 <span style="background-color: #d3d3d3; border: 1px solid black; padding: 0 2px;">OLD</span>	-	X	-
MLT 840-145 PS+ <span style="background-color: #d3d3d3; border: 1px solid black; padding: 0 2px;">OLD</span>	-	X	-
MLT 845-100 H <span style="background-color: #d3d3d3; border: 1px solid black; padding: 0 2px;">OLD</span>	-	X	-
MLT 961-145 V+ L <span style="background-color: #d3d3d3; border: 1px solid black; padding: 0 2px;">OLD</span>	-	-	X
MLTX 737-130 PS+ <span style="background-color: #d3d3d3; border: 1px solid black; padding: 0 2px;">OLD</span>	-	X	-
MLTX 737-130 PS+ (S2) <span style="background-color: #d3d3d3; border: 1px solid black; padding: 0 2px;">OLD</span>	-	X	-
MLTX 741-140 V+ S1 <span style="background-color: #d3d3d3; border: 1px solid black; padding: 0 2px;">OLD</span>	-	X	-
MLTX 840-140 PS+ <span style="background-color: #d3d3d3; border: 1px solid black; padding: 0 2px;">OLD</span>	-	X	-
MLTX 845-120 H <span style="background-color: #d3d3d3; border: 1px solid black; padding: 0 2px;">OLD</span>	-	X	-
MLTX 961-145 V+ L <span style="background-color: #d3d3d3; border: 1px solid black; padding: 0 2px;">OLD</span>	-	-	X

## TABLE SYMBOL

	No predisposition required		Hydraulic line		Return piping to hydraulic oil tank
	Electric predisposition		Platform predisposition		Tyre handler, cylinder handler predisposition

## Environment Bucket - Dimensional drawing





# **MANITOU** HANDLING YOUR WORLD

## Head Office

B.P. 249 - 430 rue de l'Aubinière  
44150 Ancenis Cedex - France  
Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97  
[www.manitou.com](http://www.manitou.com)



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes