Technical sheet:

## PIPE HANDLER



## **Technical characteristics**

- Maximum capacity 14000 kg / 30865 lbs.
- Max. pipe diameter 1016 mm / 40".
- Increased component protection for less downtimes.
- Complete grapple opening, increased efficiency when loading palletized loads.
- Rubber-covered tine pads.
- Fork dimensions: 120 x 200 x 2400 mm / 4.7 x 8 x 94.5".
- · Forks can be used in floating or fixed mode.

[The 3D picture at the top of this page is the reference PH 2100 / 8000 - 939231].

## **Customer benefits**

- Increases working safety & output on all pipe-handling applications.
- Perfect upholding of pipes thanks to its mobile grapple with hydraulic tine pads- increased safety on rough terrain.
- "Appendix" at the end of the grapple, ensures complete closing & prevents the pipes from sliding away.
- · Separated control of grapple & tine pads for more accuracy.
- Increased polyvalence: can be used to handle other loads.



Technical characteristics		PH 2100 / 8000	PH 2500 / 14000
Distance to center of gravity (mm)		586	891
Capacities			
Capacity (kg)		8000	14000
Weight			
Overall weight (kg)		2200	3800
Weight and dimensions			
Overall length (mm)	l1	2143	3104
Forks section X Forks width X Forks length (mm)	s	70 X 200 X 1500	120 X 200 X 2400
Width (mm)		2115	2444
Closed grapple height (mm)	h33	1387	2068
Opened grapple height (mm)	h34	3286	4699
Minimum diameter / Maximum diameter (mm)		80 / 850	80 / 1016
Working Parameters			
Required machine equipment		₽₽ 🖾	

Machines compatibility	PH 2100 / 8000	PH 2500 / 14000		
Reference number E-RECO	939231	939332		
MHT 790	Х	· ·		
MHT 790 Mining ST5	Х			
MHT 790 ST5	X			
MHT 10130	X	X		
MHT 10135 ST5	X			
MHT 10160 ST5	X			
MHT 10180	•	X		
MHT 10200 ST5	Х	X		
MHT 10230	•	X		
MHT 11250 Mining ST5		X		
MHT 11250 ST5	•	X		
MHT 12330	Х	X		
MHT-X 790 ST3A	Х			
MHT-X 10135 ST3A	Х			
MHT-X 10160 ST3A	Х			
MHT-X 10200 ST3A	Х	X		
MHT-X 11250 Mining	•	X		
MHT-X 11250 ST3A		X		
MHT-X 12330	X	X		
MHT-X 790 <b>OLD</b>	X			
MHT-X 790 Mining OLD	Х			

TABLE SYMBOL								
$\times$	No predisposition required	88	Hydraulic line		Return piping to hydraulic oil tank			
	Electric predisposition		Platform predisposition		Tyre handler, cylinder handler predisposition			





## **Head Office**

B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes