技術シート:

HIGH CAPACITY AGRICULTURAL BUCKET



諸元

- Bulk product bucket suitable for handling materials with a density ≤ 1000 kg/m³ / 62 lb/ft³.
- · Reinforced structure (base, blade and sides).

[The 3D picture at the top of this page is the reference CBA $2700 / 4500 \, LDR - 52000508$].

お客様のメリット

- Ideal bucket for bulk products (cereals, woodchip, mineral feed etc.)
- Modern design with maximal rigidity and resistance.
- Shape designed with 3° angle for quick loading and unloading operation.
- 500HB bolt-on cutting edge (LDR) for more longevity.



HIGH CAPACITY AGRICULTURAL BUCKET 作成 2025年11月2日 8:46 UTC

諸元		CBA 2500 / 4000 LDR	CBA 2700 / 4500 LDR		
重心位置までの距離 (mm)		621	595		
キャパシティー					
諸元 (kg)		3205	3640		
ドーム容量 (I)		4007	4550		
打撃能力 (I)		3195	3617		
重量					
重量 (kg)		1310	1400		
仕様					
全高 (mm)	h17	1617	1677		
全長 (mm)	l1	1896	1896		
幅 (mm)		2500	2700		
深さ (mm)	р5	1700	1700		
ワーキング パラメーター					
機械設備		×	X		
アタッチメント用他 データ					
ウエアプレートハーネス		500	500		

マシンの互換性	CBA 2500 / 4000 LDR	CBA 2700 / 4500 LDR 52000508		
参照番号 ボルト締めウェアプレート LDR	52603178			
MLT 850-145 V+	X	X		
MLT 961-160 V+ L	X	X		
MLT-X 850-145 V+	X	X		
MLT-X 961-160 V+ L	X	X		
MLT 961-145 V+ L OLD	X	X		
MLT-X 961-145 V+ L OLD	X	X		

記号の表	3号の表						
X	前処理が不要	88	油圧ライン		タンクへの油圧リターン		
	電気要素		プラットフォーム要素		タイヤクランプ、シリンダークラン プ要素		





本社ビル

B.P. 249 - 430 rue de l'Aubinière オービニエール通り 44150 Ancenis Cedex - France 電話 +33 (0)2 40 09 10 11 - ファックス +33 (0)2 40 09 10 97 www.manitou.com



本書では、マニトウ製品の構成バージョンやオプションについて説明していますが、機器によって異なる場合があります。このパンフレットで紹介されている機器は、バージョンによってシリーズの一部であったり、オプションであったり、あるいは利用できない場合があります。Manitouは、いつでも予告なしに、記載・表現されている仕様を変更する権利を有します。提供された仕様はメーカーを拘束するものではありません。詳細につきましては、マニトウの代理店にお問い合わせください。本資料は、契約上の拘束力を有するものではありません。製品の提示は、契約上の拘束力はありません。仕様のリストは無尽蔵です。ロゴおよび会社のビジュアル・アイデンティティはManitouが所有しており、許可なく使用することはできません。すべての権利はマニトウに帰属します。このパンフレットに掲載されている写真や図は、相談や情報提供を目的としています。

MANITOU BF SA - 取締役会を有する有限会社 - 株式資本。39 668 399 ユーロ - 857 802 508 RCS Nantes