技術シート:

SQUARE WRAPPED BALE CLAMP



諸元

- Strong frame & components for intensive applications.
- Telescopic kinematics, smooth movement & strong clamping capacity.
- General use of Teflon® pads Limited maintenance.
- · Standard pressure limiter.

[The 3D picture at the top of this page is the reference CLBSW $2000 \ / \ 1000 \ - \ 52000812].$

お客様のメリット

- Tubular structure, no risk of damaging the film when moving wrapped bales.
- Wide clamp opening for big or multiple bale handling.
- Superior component protection.
- Multi-task: designed for wrapped square bales, can also handle standard square bales or round bales.



キャパシティー		CLBSW 2000 / 1000
諸元 (kg)		1000
重量		
重量 (kg)		483
仕様		
全高 (mm)	h17	679
全長 (mm)	l1	1849
幅 (mm)		1525
アーム長 (mm)		1000
ワーキング パラメーター		
機械設備		春 春
最小開口 (mm)		740
最大開口 (mm)		2090

マシンの互換性	CLBSW 2000 / 1000
参照番号	52000812
MLT 625-75 H	х
MLT 625 e	x
MLT 630-115 (S1)	x
MLT 630-115 (S2)	x
MLT 630-115 V (S1)	x
MLT 630-115 V (S2)	x
MLT 630-115 V CP (S1)	x
MLT 630-115 V CP (S2)	x
MLT 635-130 PS+ (S1)	х
MLT 635-130 PS+ (S2)	x
MLT 635-140 V+ (S1)	х
MLT 635-140 V+ (S2)	x
MLT 730-115 V (S1)	х
MLT 730-115 V (S2)	x
MLT 730-115 V CP (S1)	Х
MLT 730-115 V CP (S2)	X
MLT 733-115	X
MLT 733-115 (S2)	X
MLT 733-115 LSU (S1)	X
MLT 733-113 E30 (31) MLT 737-130 PS+ (S1)	X
MLT 738-130 PS+ (S1)	
MLT 741-130 PS+ (S1)	X
MLT 741-130 PS+ (S1) MLT 741-140 V+ (S1)	X
, ,	X
MLT 742-130 PS+ (S1)	X
MLT 742-140 V+ (S1)	X
MLT 841-145 PS+	X
MLT 850-145 V+	X
MLT 940-140 V+ (S1)	X
MLT 940-140 V+ (S2)	X
MLT 961-160 V+ L	X
MLT 1041-145 PS+L	Х
MLT-X 625-75 H	X
MLT-X 735 T LSU	Х
MLT-X 737-130 PS+ (S2)	х
MLT-X 738-130 PS+ (S1)	Х
MLT-X 741 T LSU	х
MLT-X 841 - 145 PS+	х
MLT-X 850-145 V+	x
MLT-X 961-160 V+ L	х
MLT-X 1041-145 PS+L	x
MLT 630-105 ST4 OLD	Х
MLT 630-105 V CP ST4 OLD	x
MLT 630-105 V ST4 OLD	Х
MLT 635-130 PS+ ST4 OLD	Х
MLT 635-140 V+ ST4 OLD	Х
MLT 730-115 V CP ST4 OLD	Х
MLT 733-115 LSU ST4 OLD	Х
MLT 733-115 ST4 OLD	Х
MLT 737-130 PS+ ST4 OLD	Х
MLT 741-140 V+ ST4 OLD	Х
MLT 840-145 PS+ OLD	Х
MLT 940-140 V+ ST4 OLD	Х
MLT 961-145 V+ L OLD	Х
MLT 1040-145 PS+ L OLD	Х
MLT-X 737-130 PS+ OLD	X
MLT-X 741-140 V+ S1 OLD	Х
MLT-X 840-140 PS+ OLD	X
MLT-X 961-145 V+ L OLD	Х
MLT-X 1040-140 PS+ L OLD	X

SQUARE WRAPPED BALE CLAMP 作成 2025年11月14日 9:33 UTC

記号の表				
×	前処理が不要	88	油圧ライン	タンクへの油圧リターン
	電気要素		プラットフォーム要素	タイヤクランプ、シリンダークラン プ要素





本社ビル

B.P. 249 - 430 rue de l'Aubinière オービニエール通り 44150 Ancenis Cedex - France 電話 +33 (0)2 40 09 10 11 - ファックス +33 (0)2 40 09 10 97 www.manitou.com



本書では、マニトウ製品の構成バージョンやオプションについて説明していますが、機器によって異なる場合があります。このパンフレットで紹介されている機器は、バージョンによってシリーズの一部であったり、オプションであったり、あるいは利用できない場合があります。Manitouは、いつでも予告なしに、記載・表現されている仕様を変更する権利を有します。提供された仕様はメーカーを拘束するものではありません。詳細につきましては、マニトウの代理店にお問い合わせください。本資料は、契約上の拘束力を有するものではありません。製品の提示は、契約上の拘束力はありません。仕様のリストは無尽蔵です。ロゴおよび会社のビジュアル・アイデンティティはManitouが所有しており、許可なく使用することはできません。すべての権利はマニトウに帰属します。このパンフレットに掲載されている写真や図は、相談や情報提供を目的としています。

MANITOU BF SA - 取締役会を有する有限会社 - 株式資本。39 668 399 ユーロ - 857 802 508 RCS Nantes