

Technical sheet :

# POT CLAMP



## Customer benefits


- Makes the handling of pots and plants in pots easy and efficient.
- Efficiently replaces forks, jibs or human strength.
- Wide opening & high capacity to adapt to many pot types.

## Technical characteristics







- Articulated handles for a smooth pot clamping.
- Adjustable pressure limiter to prevent from damaging fragile pots (terracotta).
- Increased component protection & simplified maintenance.
- Handles pot with maximum diameter of 1 m / 3 ft.

[The 3D picture at the top of this page is the reference CLP 1000 / 800 - 914770].

**MANITOU** GROUP ATTACHMENTS

Capacities		CLP 1000 / 800	
Capacity (kg)		800	
Weight			
Overall weight (kg)		136	
Weight and dimensions			
Overall height (mm)	h17	689	
Overall length (mm)	l1	1256	
Width (mm)		750	
Maximum diameter (mm)		1050	
Working Parameters			
Required machine equipment			
Minimum opening (mm)		400	
Maximum opening (mm)		1000	

Machines compatibility	CLP 1000 / 800	
Reference number	914770	
Skid Steer Camiage reference	939690	
MLT 420-60 H	X	
MLT 625-75 H	X	
MLT 625 e	X	
MLTX 625-75 H	X	
MT 420 H	X	
MT 625 e	X	
MT 625 H	X	
MT 625 H Comfort	X	
MT 625 HA	X	

TABLE SYMBOL					
	No predisposition required		Hydraulic line		Return piping to hydraulic oil tank
	Electric predisposition		Platform predisposition		Tyre handler, cylinder handler predisposition



**Head Office**

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

[www.manitou.com](http://www.manitou.com)



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes