

Technical sheet :

POT CLAMP



Technical characteristics

- Articulated handles for a smooth pot clamping.
- Adjustable pressure limiter to prevent from damaging fragile pots (terracotta).
- Increased component protection & simplified maintenance.
- Handles pot with maximum diameter of 1 m / 3 ft.

[The 3D picture at the top of this page is the reference CLP 1000 / 800 - 914770].

Customer benefits

- Makes the handling of pots and plants in pots easy and efficient.
- Efficiently replaces forks, jibs or human strength.
- Wide opening & high capacity to adapt to many pot types.

| Capacities | | CLP 1000 / 800 | |
|----------------------------|-----|----------------|---|
| Capacity (kg) | | | 800 |
| Weight | | | |
| Overall weight (kg) | | | 136 |
| Weight and dimensions | | | |
| Overall height (mm) | h17 | | 689 |
| Overall length (mm) | l1 | | 1256 |
| Width (mm) | | | 750 |
| Maximum diameter (mm) | | | 1050 |
| Working Parameters | | | |
| Required machine equipment | | |  |
| Minimum opening (mm) | | | 400 |
| Maximum opening (mm) | | | 1000 |

| Machines compatibility | | CLP 1000 / 800 | |
|-------------------------------|--|----------------|--------|
| Reference number | | | 914770 |
| Skid Steer Carriage reference | | | 939690 |
| MLT 420-60 H | | | X |
| MLT 625-75 H | | | X |
| MLT 625 e | | | X |
| MLFX 625-75 H | | | X |
| MT 420 H | | | X |
| MT 625 e | | | X |
| MT 625 H | | | X |
| MT 625 H Comfort | | | X |
| MT 625 HA OLD | | | X |

| TABLE SYMBOL | | | | | |
|--|----------------------------|--|-------------------------|--|---|
|  | No predisposition required |  | Hydraulic line |  | Return piping to hydraulic oil tank |
|  | Electric predisposition |  | Platform predisposition |  | Tyre handler, cylinder handler predisposition |



Head Office

B.P. 249 - 430 rue de l'Aubinière
44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes