Technical sheet :

AGRICULTURAL BUCKET

Technical characteristics

- Wide selection of capacities ranging from 900 L (31.8 ft³) to 3000 L (105.9 ft³).
- Light material bucket designed for handling loads with a density ≤ 1000 kg/m³ (62 lb/ft³).
- Reinforced structural design across the base, blade, and sides.
- "DA" version features a tip angle increased by 10°.
- Optional 500 HB reversible wear plate available for enhanced durability.

[The 3D picture at the top of this page is the reference CBA 2500/2450 - 570554].

Customer benefits

- Ideal bucket for bulk products (grains, woodchip, mineral feed etc.).
- Specific convex shape to facilitate loading and unloading operations.
- The shell is designed with a 3° angle between the bottom of the bucket and the cutting edge for better longevity.

		CBA 1500/2050	CBA 1500/2050 DA	CBA 1500/2050 DA LDR	CBA 1500/2450	CBA 1500/2450 LDR	CBA 1500/900 SK
Reference number		570546	653035	52000489	570547	570548	52658300
Heaped capacity (l)		1500	1500	1500	1529	1529	886
Struck capacity (l)		1101	1101	1101	1101	1101	672
Overall weight (kg)		490	482	525	493	566	339
Height (mm)		1119	1119	1139	1029	1049	1030
Length (mm)		1255	1200	1230	1135	1186	1203
Width (mm)		2050	2050	2050	2450	2450	1500
Depth (mm)	p5	1080	1080	1110	990	1015	980
Optimized tilting angle		No	Yes	Yes	No	No	No
Required machine equipment		✕	✕	✕	✕	✕	✕
Bucket type		N/A	N/A	N/A	N/A	N/A	N/A
Cutting edge		No	No	Bolt-on	No	Bolt-on	No
E-RECO		No	No	No	No	No	No
Connection system		Manitou	Manitou	Manitou	Manitou	Manitou	Universal Quick-attach

Machines compatibility						
ALT950	-	-	-	X	X	-
MLA-T 533-145 V+ - ST5	-	-	-	X	X	-
MLT 420-60 H	-	-	-	-	-	X
MLT 625-75 H	X	X	X	-	-	-
MLT 625 e	X	X	X	-	-	-
MLT 635-130 PS+ (S1)	-	-	-	X	X	-
MLT 635-130 PS+ (S2)	-	-	-	X	X	-
MLT 635-140 V+ (S1)	-	-	-	X	X	-
MLT 635-140 V+ (S2)	-	-	-	X	X	-
MLT 733-115	-	-	-	X	X	-
MLT 733-115 (S2)	-	-	-	X	X	-
MLT 733-115 LSU (S1)	-	-	-	X	X	-
MLT 737-130 PS+ (S1)	-	-	-	X	X	-
MLT 738-130 PS+ (S1)	-	-	-	X	X	-
MLT 741-130 PS+ (S1)	-	-	-	X	X	-
MLT 741-140 V+ (S1)	-	-	-	X	X	-
MLT 742-130 PS+ (S1)	-	-	-	X	X	-
MLT 742-140 V+ (S1)	-	-	-	X	X	-
MLT 937-115 (S1)	-	-	-	X	X	-
MLT-X 625-75 H	X	X	X	-	-	-
MLT-X 732	-	-	-	X	X	-
MLT-X 735 T LSU	-	-	-	X	X	-
MLT-X 738-130 PS+ (S1)	-	-	-	X	X	-
MLT-X 1035 LT LSU	-	-	-	X	X	-
MLT-X 737-130 PS+ OLD	-	-	-	X	X	-
MLT-X 737-130 PS+ (S2) OLD	-	-	-	X	X	-
MLT-X 741-140 V+ OLD	-	-	-	X	X	-

		CBA 1700/2100	CBA 1700/2100 LDR	CBA 2000/2250	CBA 2000/2250 LDR	CBA 2000/2450	CBA 2000/2450 LDR
Reference number		570549	52610570	790540	790541	570551	570552
Heaped capacity (l)		1703	1703	1970	1970	2010	2010
Struck capacity (l)		1271	1271	1456	1456	1484	1484
Overall weight (kg)		512	562	579	619	557	640
Height (mm)		1150	1170	1179	1199	1150	1170
Length (mm)		1280	1310	1405	1437	1310	1340
Width (mm)		2100	2100	2250	2250	2450	2450
Depth (mm)	p5	1140	1180	1208	1260	1150	1180
Optimized tilting angle		No	No	No	No	No	No
Required machine equipment		✕	✕	✕	✕	✕	✕
Bucket type		N/A	N/A	N/A	N/A	N/A	N/A
Cutting edge		No	Bolt-on	No	Bolt-on	No	Bolt-on
E-RECO		No	No	No	No	No	No
Connection system		Manitou	Manitou	Manitou	Manitou	Manitou	Manitou

Machines compatibility						
ALT950	-	-	X	X	X	X
MLA-T 533-145 V+ - ST5	-	-	X	X	X	X
MLT 630-115 (S1)	X	X	X	X	X	X
MLT 630-115 (S2)	X	X	X	X	X	X
MLT 630-115 V (S1)	X	X	X	X	X	X
MLT 630-115 V (S2)	X	X	X	X	X	X
MLT 630-115 V CP (S1)	X	X	X	X	X	X
MLT 630-115 V CP (S2)	X	X	X	X	X	X
MLT 635-130 PS+ (S1)	-	-	-	-	X	X
MLT 635-130 PS+ (S2)	-	-	-	-	X	X
MLT 635-140 V+ (S1)	-	-	-	-	X	X
MLT 635-140 V+ (S2)	-	-	-	-	X	X
MLT 730-115 V (S1)	X	X	X	X	X	X
MLT 730-115 V (S2)	X	X	X	X	X	X
MLT 730-115 V CP (S1)	X	X	X	X	X	X
MLT 730-115 V CP (S2)	X	X	X	X	X	X
MLT 733-115	-	X	-	-	X	X
MLT 733-115 (S2)	-	-	-	-	X	X
MLT 733-115 LSU (S1)	-	X	-	-	X	X
MLT 737-130 PS+ (S1)	-	X	-	-	X	X
MLT 738-130 PS+ (S1)	-	-	-	-	X	X
MLT 741-130 PS+ (S1)	-	-	-	-	X	X
MLT 741-140 V+ (S1)	-	X	-	-	X	X
MLT 742-130 PS+ (S1)	-	-	-	-	X	X
MLT 742-140 V+ (S1)	-	-	-	-	X	X
MLT 841-145 PS+	-	-	-	-	X	X
MLT 937-115 (S1)	-	-	X	X	X	X
MLT 940-140 V+ (S1)	-	-	-	-	X	X
MLT 940-140 V+ (S2)	-	-	-	-	X	X
MLT 1041-145 PS+L	-	-	-	-	X	X
MLT-X 732	-	-	-	-	X	X
MLT-X 735 T LSU	-	-	-	-	X	X
MLT-X 738-130 PS+ (S1)	-	X	-	-	X	X
MLT-X 741 T LSU	-	-	-	-	X	X
MLT-X 841 - 145 PS+	-	-	-	-	X	X
MLT-X 1035 LT LSU	-	-	-	-	X	X
MLT-X 1041-145 PS+L	-	-	-	-	X	X
MLT-X 737-130 PS+ OLD	-	X	-	-	X	X
MLT-X 737-130 PS+ (S2) OLD	-	X	-	-	X	X
MLT-X 741-140 V+ OLD	-	X	-	-	X	X

		CBA 2500/2450	CBA 2500/2450 LDR	CBA 3000/2500	CBA 3000/2500 LDR	CBA 900/1500
Reference number		570553	570554	570555	500701	570543
Heaped capacity (l)		2526	2526	3023	3023	886
Struck capacity (l)		1916	1916	2342	2342	672
Overall weight (kg)		675	728	753	840	360
Height (mm)		1250	1270	1314	1333	1029
Length (mm)		1497	1530	1734	1762	1155
Width (mm)		2450	2450	2500	2500	1500
Depth (mm)	p5	1300	1350	1460	1470	980
Optimized tilting angle		No	No	No	No	No
Required machine equipment		X	X	X	X	X
Bucket type		N/A	N/A	N/A	N/A	N/A
Cutting edge		No	Bolt-on	No	Bolt-on	No
E-RECO		No	No	No	No	No
Connection system		Manitou	Manitou	Manitou	Manitou	Manitou

Machines compatibility					
MLT 420-60 H	-	-	-	-	X
MLT 635-130 PS+ (S1)	X	X	X	X	-
MLT 635-130 PS+ (S2)	X	X	X	X	-
MLT 635-140 V+ (S1)	X	X	X	X	-
MLT 635-140 V+ (S2)	X	X	X	X	-
MLT 733-115	X	X	-	-	-
MLT 733-115 (S2)	X	X	-	-	-
MLT 733-115 LSU (S1)	X	X	-	-	-
MLT 737-130 PS+ (S1)	X	X	X	X	-
MLT 738-130 PS+ (S1)	X	X	X	X	-
MLT 741-130 PS+ (S1)	X	X	X	X	-
MLT 741-140 V+ (S1)	X	X	X	X	-
MLT 742-130 PS+ (S1)	X	X	X	X	-
MLT 742-140 V+ (S1)	X	X	X	X	-
MLT 841-145 PS+	X	X	X	X	-
MLT 850-145 V+	X	X	X	X	-
MLT 937-115 (S1)	X	X	-	-	-
MLT 940-140 V+ (S1)	X	X	X	X	-
MLT 940-140 V+ (S2)	X	X	X	X	-
MLT 1041-145 PS+L	X	X	X	X	-
MLT-X 732	-	X	-	-	-
MLT-X 735 T LSU	X	X	-	-	-
MLT-X 738-130 PS+ (S1)	X	X	X	X	-
MLT-X 741 T LSU	X	X	X	X	-
MLT-X 841 - 145 PS+	X	X	X	X	-
MLT-X 850-145 V+	X	X	X	X	-
MLT-X 1035 LT LSU	X	X	-	-	-
MLT-X 1041-145 PS+L	X	X	X	X	-
MLT-X 737-130 PS+ OLD	X	X	X	X	-
MLT-X 737-130 PS+ (S2) OLD	X	X	X	X	-
MLT-X 741-140 V+ OLD	X	X	X	X	-

TABLE SYMBOL

X	No predisposition required		Hydraulic line		Return piping to hydraulic oil tank
	Electric predisposition		Platform predisposition		Tyre handler, cylinder handler predisposition

Head Office
B.P. 249 - 430 rue de l'Aubinière
44150 Ancenis Cedex - France
Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97
www.manitou.com

This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.
MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes