Technical sheet :

AGRICULTURAL GRAPPLE BUCKET WITH WELDED TEETH - HIGH CAPACITY

Technical characteristics

- Welded teeth - WE.
- Handling materials with a density ≤ 1000 kg/m³ (62 lb/ft³).
- Dismountable sides, spill guard and 500 HB bolt-on cutting edge standard.
- Reinforced construction (base, blade and grab) for extended lifespan.
- Nitritized cylinders, bolted shaft stop.

[The 3D picture at the top of this page is the reference BG 1850/1050 DA WE - 52647326].

Customer benefits

- Robust and versatile bucket engineered for demanding, large-scale agricultural applications.
- The perfect solution for the efficient handling of manure, silage, and other dense materials.
- A must-have tool for livestock farms, offering superior durability thanks to its reinforced welded teeth.

		CBG 2480/2000 MS	CBG 2480/2600 MS
Reference number		790656	790658
Heaped capacity (l)		2000	2600
Struck capacity (l)		1500	1500
Overall weight (kg)		1225	1357
Length (mm)		1491	1670
Width (mm)		2480	2480
Closed grapple height (mm)	h33	1502	1502
Opened grapple height (mm)	h34	2292	2452
Depth (mm)	p5	1250	1420
Optimized tilting angle		No	No
Required machine equipment			
Bucket type		High capacity	High capacity
Tooth type		Welded	Welded
Cutting edge		Bolt-on	Bolt-on
Number of tooth		6	7
E-RECO		No	No
Connection system		Manitou	Manitou

Machines compatibility		
MLT 841-145 PS+	X	-
MLT 850-145 V+	X	X
MLT 961-160 V+ L	-	X
MLT 1041-145 PS+L	X	-
MLT-X 841 - 145 PS+	X	-
MLT-X 850-145 V+	X	X
MLT-X 961-160 V+ L	-	X
MLT-X 1041-145 PS+L	X	-

TABLE SYMBOL

	No predisposition required		Hydraulic line		Return piping to hydraulic oil tank
	Electric predisposition		Platform predisposition		Tyre handler, cylinder handler predisposition

Head Office
B.P. 249 - 430 rue de l'Aubinière
44150 Ancenis Cedex - France
Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97
www.manitou.com

This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.
MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes