Technical sheet:

ANGLE BROOM (COMPACT MACHINES)



Customer benefits

- Based on a bucket: cutting edge can be used to scrap packed material.

Technical characteristics

- Sweeps and picks-up in one operation.
- Strong construction with well-protected components. Polypropylene broom sections



Weight		SCA 1330	SCA 1530	SCA 1680	SCA 1750	SCA 1850	SCA 1900	SCA 2080 (a)	SCA 2080 (b)	SCA 2140
Overall weight (lb)		794	882	904	860	926	882	904	904	-
Weight and dimensions										
Overall height (in)	h17	2' 3"	2' 3"	2' 3"	2' 3"	2' 3"	2' 3"	2' 3"	2' 3"	-
Width (in)		4' 9"	5' 9"	6' 3"	5' 9"	6' 10"	6' 3"	6' 10"	6' 10"	7"
Depth (in)	p5	4' 4"	4' 4"	4' 4"	4' 4"	4' 4"	4' 4"	4' 4"	4' 4"	-
Working Parameters										
Required machine equipment		88	88	88	88	春春	各各	88	88	88
Horizontal angle (°)		30	30	30	30	30	30	30	30	

Machines compatibility	SCA 1330	SCA 1530	SCA 1680	SCA 1750	SCA 1850	SCA 1900	SCA 2080 (a)	SCA 2080 (b)	SCA 2140
All-Tach® Naπow	N004039	N004040	- -	- -	-		-	- -	- -
All-Tach®	-	N004041	N004042	N51502366	N004043	N51502367	N51502370	N51502496	N51502055
4 point Carriage	N51502376	N51502377	N51502378	-	N51502379	-	-	-	-
Euro Carriage	N51502380	N51502381	N51502382	_	N51502383	_	_	_	_
1050RT	-	-	-	Х	-	Х			
1350R NXT2				X		X	-		
1350RT				X	-	X	-	-	
1650R				-	-	X	-		
1650RT				Х	-	x	-	-	
1950RT				X	-	X	-	-	
1950RT				х	-	Х	-		
1950RT				Х		Х	-		
1950RT				х		Х	-	-	-
AL230	х	x		-	-		-		
AL320	X	Х	-		-	-	-	-	-
AL330	х	х					-		
AL420	X	Х	Х				-	-	
AL430	х	х	х				-		
AL530		Х	Х	-	-	-		-	
AL550		х	х	-	х		-		
MLA 2-25 H	Х	Х	-	-	-	-	-	-	
MLA 3-25 H	х	х		-	-		-		
MLA 3-25 H-C	X	Х	-	-	-	-	-	-	-
MLA 4-50 H	Х	Х	Х		-		-		
MLA 4-50 H-C	Χ	X	Х	-	-	-	-	-	
MLA 5-50 H	-	Х	х		-		-	-	
MLA 5-60 H-Z	-	X	Х	-	Х	-	-	-	-
R165	-	-	-	-	-	х	-	-	-
RT105	-	-	-	х	-	Х	-	-	-
RT135	-	-	-	Х	-	Х	-	-	-
RT165	-	-	-	х	-	х	-	-	-
RT195 - NEW	-	-	-	Х	-	Х	-	-	-
RT195 - NEW	-	-	-	Х	-	Х	-	-	-
RT195 - NEW	-	-	-	Х	-	Х	-	-	-
1850RT OLD									X
1900R OLD	-	-	-	-	-	-	-	X	-
2150RT OLD									X
2200R OLD	-	-	-	-	-	-	-	X	-
2600R OLD								X	
2700V NXT2 OLD	-	-	-	-	-		Х	-	-
AL140 OLD	X	X							
AL340 OLD	Х	X	-	-	-		-	-	-
AL440 OLD		X	X						
MLA 1-25 H OLD	Χ	Х					-	-	-
MLA 3-35 H OLD	Χ	Χ							
MLA 4-50 H OLD	Х	X	Х	-	-		-	-	-
R220 OLD								X	
R260 OLD			-	-	-	-	-	Х	-
RT185 OLD									Х
RT215 OLD	-	-	-	-	-	-	-	-	Х
V270 OLD							Χ		

TABLE SYMBOL				
X	No predisposition required	88	Hydraulic line	Return piping to hydraulic oil tank
	Electric predisposition		Platform predisposition	Tyre handler, cylinder handler predisposition





Head Office

B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes