AUGER (COMPACT MACHINES) MISCELLANEOUS ATTACHMENTS





Customer benefits

- All bits sold separately.
- Auger bits Earth ground AB Earth 150/1000 ref 52773069
- Auger bits Mixed ground AB Mixed 150/1000 ref 52773070
- Auger bits Mixed ground AB Mixed 250/1000 ref 52753012
- Auger bits Rocky ground AB Rocky 150/1000 ref 52773084
- Must-have attachment for drilling holes and repairing guardrails, installing poles or planting trees.

Technical characteristics

- Planetary auger.
- Gear motor protection with bolted carter.
- Hexagonal output shaft with locking pin.
- Possibility to choose drills depending on the type of grounds and diameters needed (earth ground, mixed ground or rock and asphalt).
- Possibility to add an extension 500 mm / 20 in or 1000 mm / 39 in
- Hydraulics requirements min/max = 25-70 l/min / 7-18 gpm.
- Max drill = 600 mm / 24 in.



AUGER (COMPACT MACHINES) Created on December 22, 2024 at 7:04 AM UTC

| Weight | A 110 H 4P | A 110 H | A 110 H EU | | | |
|-----------------------|------------|---------|------------|--|--|--|
| Overall weight (kg) | 110 | 110 | 110 | | | |
| Weight and dimensions | | | | | | |
| Width (mm) | - | 352 | - | | | |
| Working Parameters | | | | | | |
| Machine Equipment | 88 | 88 | 88 | | | |

| Machines compatibility | A 110 H 4P | A 110 H | A 110 H EU |
|------------------------|--------------|----------|------------|
| All-Tach® | - | 52728005 | - |
| 4 point Carriage | 52741078 | 52741078 | - |
| Euro Carriage | | 52741077 | 52741077 |
| AL420 | - | X | - |
| AL430 | - | X | - |
| AL530 | - | X | - |
| GCT 3-14 | - | X | - |
| GCT 3-14 | - | X | - |
| GCT 3-14 + | - | X | <u>-</u> |
| GCT 3-14+ | - | X | - |
| MLA 4-50 H | - | X | <u>-</u> |
| MLA 4-50 H-C | - | X | • |
| MLA 5-50 H | - | X | - |
| ULM 412 H | - | X | |
| ULM 412 H | - | X | - |
| ULM 415 H | - | X | * |
| ULM 415 H | - | X | - |
| MLA 4-50 H OLD | - | X | - |

| TABLE SYMBOL | | | | | | |
|--------------|----------------------------|----|-------------------------|--|---|--|
| \times | No predisposition required | 88 | Hydraulic line | | Return piping to hydraulic oil tank | |
| | Electric predisposition | | Platform predisposition | | Tyre handler, cylinder handler predisposition | |





Siège Social P.O. Box 179 - One Gehl Way - West Bend, WI, USA 53095 Tel: (262) 334-9461 - Fax: (262) 338-7517 www.gehl.com



This brochure describes versions and configuration options for Gehl products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Gehl reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Gehl dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Gehl and may not be used without authorization. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU EQUIPMENT AMERICAS, LLC - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS West Bend