

PLANETARY AUGER (COMPACT MACHINES)

MISCELLANEOUS ATTACHMENTS



GEHL®






Customer benefits

- Must-have attachment for drilling holes and repairing guardrails, installing poles or planting trees.

Technical characteristics







- Bidirectional hydraulic motor.
- Totally closed structure for full protection and great compactness
- Hexagonal output shaft.
- Possibility to choose drills depending on the type of grounds and diameters needed (earth ground, mixed ground or rock and asphalt).
- Possibility to add an extension 500 mm or 1000 mm.
- All bits and extensions are sold separately.

MANITOU GROUP ATTACHMENTS

Weight		A 110 H 4P	A 110 H	A 110 H EU	APD 800/HX QA (a)	APD 800/HX QA (b)
Overall weight (kg)		110	110	110	98	125
Weight and dimensions						
Overall length (mm)	l1	-	-	-	1020	-
Width (mm)		-	352	-	-	-
Working Parameters						
Machine Equipment						
Head type		hex	-	hex	hex	hex
Theoretic torque (Nm)		-	-	-	450	710
Minimum hydraulic requirements (l/min)		25	-	25	60	80
Maximum hydraulic requirements (l/min)		70	-	70	100	120
Auger bit		No	-	No	No	No
Auger mount		Si	-	Si	Si	Si
Rotation speed (rpm)		-	-	-	60	50
Maximum bit diameter (mm)		600	-	600	800	800
Other Data for Attachments						
Connection system		4-point	-	Euro	Universal Quick-attach	Universal Quick-attach

Compatibilità della macchina	A 110 H 4P	A 110 H	A 110 H EU	APD 800/HX QA (a)	APD 800/HX QA (b)
All-Tach®	-	52728005	-	52861474	52861477
4 point Carriage	52741078	52741078	-	-	-
Euro Carriage	-	52741077	52741077	-	-
2100V	-	-	-	X	-
2100VT	-	-	-	X	-
2300V	-	-	-	X	-
2300VT	-	-	-	X	-
2750V	-	-	-	-	X
2750VT	-	-	-	-	X
AL420	X	X	X	-	-
AL430	X	X	X	-	-
AL530	X	X	X	-	-
GCT 3-14	X	X	X	-	-
GCT 3-14	X	X	X	-	-
GCT 3-14 +	X	X	X	-	-
GCT 3-14+	X	X	X	-	-
MLA 4-50 H	X	X	X	-	-
MLA 4-50 H-C	X	X	X	-	-
MLA 5-50 H	X	X	X	-	-
ULM 412 H	X	X	X	-	-
ULM 412 H	X	X	X	-	-
ULM 415 H	X	X	X	-	-
ULM 415 H	X	X	X	-	-
V210	-	-	-	X	-
V230	-	-	-	X	-
V275	-	-	-	-	X
VT210	-	-	-	X	-
VT230	-	-	-	X	-
VT275	-	-	-	-	X
MLA 4-50 H OLD	X	X	X	-	-

TABELLA DEI SIMBOLI

	Nessuna predisposizione richiesta		Linea idraulica		Ritorno idraulico al serbatoio
	Predisposizione elettrica		Predisposizione piattaforma		Predisposizione per la movimentazione dei pneumatici, dei cilindri



GEHL®

Siège Social
P.O. Box 179 - One Gehl Way - West Bend, WI, USA 53095
Tel: (262) 334-9461 - Fax: (262) 338-7517
www.gehl.com



This brochure describes versions and configuration options for Gehl products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Gehl reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Gehl dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Gehl and may not be used without authorization. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU EQUIPMENT AMERICAS, LLC - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS West Bend