Technical sheet:

AUGER (COMPACT MACHINES)



Customer benefits

- All bits sold separately.
- Auger bits Earth ground AB Earth 150/1000 ref 52773069
- Auger bits Mixed ground AB Mixed 150/1000 ref 52773070
- Auger bits Mixed ground AB Mixed 250/1000 ref 52753012
- Auger bits Rocky ground AB Rocky 150/1000 ref 52773084
- Must-have attachment for drilling holes and repairing guardrails, installing poles or planting trees.

Technical characteristics

- Planetary auger.
- Gear motor protection with bolted carter.
- Hexagonal output shaft with locking pin.
- Possibility to choose drills depending on the type of grounds and diameters needed (earth ground, mixed ground or rock and asphalt).
- Possibility to add an extension 500 mm or 1000 mm.
- Hydraulics requirements min/max = 25-70 l/min.
- Max drill = 600 mm.



AUGER (COMPACT MACHINES) Created on May 22, 2024 at 2:53:00 AM UTC

Weight	A 110 H
Overall weight (kg) Weight and dimensions	110
Weight and dimensions	
Width (mm)	352
Working Parameters	
Machine Equipment	

Machines compatibility	A 110 H
All-Tach®	52728005
4 point Carriage	52741078
Euro Carriage	\$2741 07 7
AL420	x
AL430	x
AL530	x
GCT 3-14	x
GCT 3-14	x
GCT 3-14 +	x
GCT 3-14+	x
MLA 4-50 H	x
MLA 4-50 H-C	x
MLA 5-50 H	x
ULM 412 H	x
ULM 412 H	x
ULM 415 H	х
ULM 415 H	x
MLA 4-50 H OLD	x

TABLE SYMBOL						
\times	No predisposition required	88	Hydraulic line		Return piping to hydraulic oil tank	
	Electric predisposition		Platform predisposition		Tyre handler, cylinder handler predisposition	





Head Office

B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes