Technical sheet:

PLANETARY AUGER (COMPACT MACHINES)



Technical characteristics

- Bidirectional hydraulic motor.
- Fully enclosed structure for complete protection and excellent compactness.
- Hexagonal output shaft. Size varies by model: 50mm or 70mm.
- Round and compact design for easy hole entry.
- Possibility to choose drills depending on the type of grounds and diameters needed (earth, mixed soil or rock and asphalt).
- Extension options available. Size varies by model: 500mm and/or 1000mm.
- · All bits and extensions are sold separately.

Customer benefits

 Must-have attachment for drilling holes and repairing guardrails, installing poles or planting trees.



PLANETARY AUGER (COMPACT MACHINES) Created on December 14, 2025 at 4:19 PM UTC

Weight		APD 800/HX QA (a)	APD 800/HX QA (b)		
Overall weight (kg)		194	167		
Dimensions					
Shaft diameter (mm)		50	70		
Weight and dimensions					
Overall length (mm)	l1	1020	1103		
Working Parameters					
Required machine equipment		 			
Head type		Hex	Hex		
Theoretic torque (Nm)		450	710		
Minimum hydraulic requirements (I/min)		60	80		
Maximum hydraulic requirements (I/min)		100	120		
Rotation speed (rpm)		60	50		
Maximum bit diameter (mm)	um bit diameter (mm) 800		800		
Other Data for Attachments					
E-RECO	No		No		
Connection system		Universal Quick-attach	Universal Quick-attach		

Machines compatibility	APD 800/HX QA (a) APD 800/HX QA (b)		
All-Tach®	52861474	52861477	
2100V	X		
2100VT	X		
2300V	X		
2300VT	X	·	
2750V		X	
2750VT		X	
V210	X	+	
V230	Х		
V275		X	
VT210	Х		
VT230	X	+	
VT275	•	X	

TABLE SYMBOL								
X	No predisposition required	88	Hydraulic line		Return piping to hydraulic oil tank			
	Electric predisposition		Platform predisposition		Tyre handler, cylinder handler predisposition			





Head Office

B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes