Technical sheet :

BALE CLAMP FOR SQUARE BALE

Technical characteristics

- Capacity: 2100 kg (4630 lb) / 5 bales (700 mm (27.6 in) high).
- Reinforced frame & grab structure for extreme working conditions.
- 2x7 forged teeth, Ø 25 mm (1.0 in) length 340 mm (13.4 in).
- 3x lower tines, Ø 40 mm (1.6 in) length 1000 mm (39.4 in).
- Synchronized closure.

[The 3D picture at the top of this page is the reference CLBS 2x7/2100 - 52000015].

Customer benefits

- High capacity & power for intensive straw stacking
- Lateral clamp kinematics: in building stacking made easy
- Good bale penetration & upholding
- Possible handling & rotation of a single bale.

	CLBS 2x7/2100
Reference number	52000015
Capacity (kg)	2100
Overall weight (kg)	760
Height (mm)	3010
Length (mm)	1590
Width (mm)	1800
Bale type	Unwrapped
Number of spear	3
Required machine equipment	
Bale shape	Round and square
Number of tooth	14
Min. opening (mm)	420
Max. opening (mm)	1570
E-RECO	No
Connection system	Manitou

Machines compatibility	
MLT 742-130 PS+ (S1)	X
MLT 742-140 V+ (S1)	X
MLT 841-145 PS+	X
MLT 850-145 V+	X
MLT 940-140 V+ (S1)	X
MLT 940-140 V+ (S2)	X
MLT 961-160 V+ L	X
MLT 1041-145 PS+L	X
MLT-X 841 - 145 PS+	X
MLT-X 850-145 V+	X
MLT-X 961-160 V+ L	X
MLT-X 1041-145 PS+L	X

TABLE SYMBOL					
	No predisposition required		Hydraulic line		Return piping to hydraulic oil tank
	Electric predisposition		Platform predisposition		Tyre handler, cylinder handler predisposition

Head Office
B.P. 249 - 430 rue de l'Aubinière
44150 Ancenis Cedex - France
Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97
www.manitou.com

This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.
MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes