Technical sheet:

## BALE CLAMP HIGH INTENSIVE



## **Technical characteristics**

- 2x6 teeth.
- · Synchronized closure.
- Excellent lifting capacity of 2000 kg / 3310 lb at 800 mm / 31 in or 2500 kg / 5513 lb with optional lower tines.
- Handles 1 round bales Ø 1.8 m / 6 ft max. for the 2x4 and Ø 1.5 m / 5 ft to 2 m / 7 ft for the 2x3.
- Handles 2 rectangular bales of maximum 0.8 m / 3 ft high per bale.

[The 3D picture at the top of this page is the reference CLBR 2x6 - 757666].

## **Customer benefits**

- Easy to use and efficient attachment.
- Handles up to 2 round bales or 3 rectangular bales at the same time
- Rounded teeth in wrought iron that offer an accurate and clean penetration on materials.



Capacities		CLBR 2x6				
Capacity (kg)		2000				
Weight						
Overall weight (kg)		434				
Weight and dimensions						
Overall height (mm)	h17	2256				
Overall length (mm)	l1	1276				
Forks length (mm)	1	335				
Width (mm)		1002				
Arm length (mm)		700				
Working Parameters						
Required machine equipment		<b> </b>				
Teeth / Fingers		2 / 6				
Minimum opening (mm)		186				
Maximum opening (mm)		1960				

March to a constant the	
Machines compatibility	CLBR 2x6
Reference number	757666
MLT 635-130 PS+ (S1)	X
MLT 635-130 PS+ (S2)	x
MLT 635-140 V+ (S1)	х
MLT 635-140 V+ (S2)	X
MLT 733-115	х
MLT 733-115 (S2)	х
MLT 733-115 LSU (S1)	х
MLT 737-130 PS+ (S1)	х
MLT 738-130 PS+ (S1)	x
MLT 741-130 PS+ (S1)	x
MLT 741-140 V+ (S1)	x
MLT 742-130 PS+ (S1)	x
MLT 742-140 V+ (S1)	х
MLT 841-145 PS+	х
MLT 850-145 V+	х
MLT 940-140 V+ (S1)	х
MLT 940-140 V+ (S2)	х
MLT 1041-145 PS+L	х
MLT-X 741 T LSU	х
MLT-X 841 - 145 PS+	x
MLT-X 850-145 V+	х
MLT-X 1041-145 PS+L	х
MLT 635-130 PS+ ST4 <b>OLD</b>	x
MLT 635-140 V+ ST4 OLD	Х
MLT 733-115 LSU ST4 <b>OLD</b>	Х
MLT 733-115 ST4 <b>OLD</b>	Х
MLT 737-130 PS+ ST4 <b>OLD</b>	x
MLT 741-140 V+ ST4 <b>OLD</b>	x
MLT 840-145 PS+ <b>OLD</b>	x
MLT 940-140 V+ ST4 <b>OLD</b>	x
MLT 1040-145 PS+ L OLD	x
MLT-X 737-130 PS+ <b>OLD</b>	x
MLT-X 737-130 PS+ (S2) OLD	x
MLT-X 741-140 V+ S1 <b>OLD</b>	x
MLT-X 840-140 PS+ OLD	x
MLT-X 1040-140 PS+ L <b>OLD</b>	x

TABLE SYMBOL							
X	No predisposition required	88	Hydraulic line		Return piping to hydraulic oil tank		
	Electric predisposition		Platform predisposition		Tyre handler, cylinder handler predisposition		





## **Head Office**

B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes