Technical sheet :

BIG BAG FILLING BUCKET



Customer benefits

- For loading bulk material like sand, gravel, grains, fertilizer, seeds...

 \cdot Enables bulk material to be loaded, big bags to be filled and then moved.

- Saves time and productivity for the operator.

- Ensures less material loss during big bag filling.

- Easy to use: specifically designed for big bag filling, handling and unhooking.

Technical characteristics

adjustable and hydraulic door opening from the cab. Bolt-on cutting edge standard.



BIG BAG FILLING BUCKET Created on August 1, 2025 at 9:04 PM UTC

| Capacities | | BBF 1200 / 600 | BBF 1400 / 1100 | BBF 1650 / 1750 |
|-------------------------------------|-----|----------------|-----------------|-----------------|
| Heaped capacity (I) | | 600 | 1120 | 1750 |
| Weight | | | | |
| Overall weight (kg) | | 455 | 610 | 750 |
| Weight and dimensions | | | | |
| Overall height (mm) | h17 | 685 | 923 | 1158 |
| Overall length (mm) | 11 | 1549 | 1723 | 1896 |
| Width (mm) | | 1200 | 1400 | 1650 |
| Working Parameters | | | | |
| Required machine equipment | | | | |
| Maximum density of material (kg/m3) | | 2000 | 2000 | 1000 |
| Opening type | | Hydraulic | Hydraulic | Hydraulic |
| Other Data for Attachments | | | | |
| Connection system | | Manitou | Manitou | Manitou |
| E-RECO | | No | No | No |

| Machines compatibility | BBF 1200 / 600 | BBF 1400 / 1100 | BBF 1650 / 1750 |
|------------------------|----------------|-----------------|-----------------|
| Reference number | 52676645 | 52614700 | 52634800 |
| MLT 630-115 (S2) | Х | Х | |
| MLT 630-115 V (S2) | х | Х | |
| MLT 630-115 V CP (S2) | Х | х | |
| MLT 635-130 PS+ (S2) | х | x | х |
| MLT 635-140 V+ (S2) | х | x | х |
| MLT 730-115 V (S2) | х | x | |
| MLT 730-115 V CP (S2) | х | x | |
| MLT 733-115 (S2) | х | x | |
| MLT 738-130 PS+ (S1) | х | x | х |
| MLT 742-130 PS+ (S1) | х | Х | х |
| MLT 742-140 V+ (S1) | Х | х | х |
| MLT 937-115 (S1) | х | x | |
| MLT-X 738-130 PS+ (S1) | X | x | х |

| TABLE SYMBOL | | | | | | | | |
|--------------|----------------------------|--|-------------------------|--|---|--|--|--|
| \times | No predisposition required | | Hydraulic line | | Return piping to hydraulic oil tank | | | |
| | Electric predisposition | | Platform predisposition | | Tyre handler, cylinder handler predisposition | | | |



Head Office B.P. 249 - 430 rue de l'Aubinière 44150 Ancenis Cedex - France Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes