

Technical sheet :

BUCKET 4 IN 1 WITH TEETH (COMPACT MACHINES)



Customer benefits

- Designed for all construction applications.
- Versatile use: handles bulk material, pushes, grabs etc.

Technical characteristics

- HD bolted teeth for more digging efficiency.
- Wear blades and reinforcements in 400 HB steel for more resistance.

MANITOU GROUP ATTACHMENTS

Capacities		B4x1 920 / 170 T (a)	B4x1 1080 / 210 T	B4x1 1380 / 270 T	B4x1 1380 / 300 T	B4x1 1520 / 330 T	B4x1 1525 / 360 T	B4x1 1550 / 340 T	B4x1 1650 / 610 T	B4x1 1680 / 370 T	B4x1 1680 / 430 T
Heaped capacity (l)		170	210	270	300	330	360	340	610	370	430
Weight											
Overall weight (kg)		175	180	219	250	253	287	260	482	328	350
Weight and dimensions											
Overall height (mm)	h17	713	713	713	721	721	721	721	863	721	767
Width (mm)		920	1080	1380	1380	1520	1525	1550	1650	1680	1680
Depth (mm)	p5	870	671	870	730	730	830	730	933	730	786
Working Parameters											
Machine Equipment							-				
Hydraulic system		-	-	-	-	-	Yes	-	-	-	-
Teeth		5	6	7	7	7	7	7	8	8	8

Machines compatibility	B4x1 920 / 170 T (a)	B4x1 1080 / 210 T	B4x1 1380 / 270 T	B4x1 1380 / 300 T	B4x1 1520 / 330 T	B4x1 1525 / 360 T	B4x1 1550 / 340 T	B4x1 1650 / 610 T	B4x1 1680 / 370 T	B4x1 1680 / 430 T
All-Tach® Narrow	N004068	-	N004070	-	-	-	-	-	-	-
All-Tach®	N726015	N726017	-	N736020	N736021	N004071	N736068	N51502525	N747019	N51502045
4 point Carriage	N51502392	-	N51502394	-	-	N003095	-	N51502590	-	-
Euro Carriage	-	-	N51502137	-	-	N51502170	-	N51502549	-	-
1050R	-	-	-	X	-	-	-	-	-	-
1050RT	-	-	-	X	-	-	-	-	-	-
1350R NXT2	-	-	-	X	X	-	X	-	-	-
1350RT	-	-	-	X	X	-	X	-	-	-
1640 E	X	X	-	-	-	-	-	-	-	-
1650R	-	-	-	-	-	-	-	-	X	-
1650RT	-	-	-	-	-	-	X	-	X	-
1850RT	-	-	-	-	-	-	-	-	-	X
1900R	-	-	-	-	-	-	-	-	X	-
1950RT	-	-	-	-	-	-	X	-	X	-
1950RT	-	-	-	-	-	-	X	-	X	-
1950RT	-	-	-	-	-	-	X	-	X	-
1950RT	-	-	-	-	-	-	X	-	X	-
2100V	-	-	-	-	-	-	-	-	X	-
2100VT	-	-	-	-	-	-	-	-	-	X
AL230	-	-	X	-	-	-	-	-	-	-
AL320	-	-	X	-	-	-	-	-	-	-
AL330	-	-	X	-	-	-	-	-	-	-
AL420	-	-	X	-	-	-	-	-	-	-
AL430	-	-	X	-	-	-	-	-	-	-
AL650	-	-	-	-	-	-	-	X	-	-
AL750	-	-	-	-	-	-	-	X	-	-
MLA 2-25 H	-	-	X	-	-	-	-	-	-	-
MLA 3-25 H	-	-	X	-	-	-	-	-	-	-
MLA 3-25 H-C	-	-	X	-	-	-	-	-	-	-
MLA 4-50 H	-	-	X	-	-	-	-	-	-	-
MLA 4-50 H-C	-	-	X	-	-	-	-	-	-	-
MLA 6-65 H-Z	-	-	-	-	-	-	-	X	-	-
R165	-	-	-	-	-	-	-	-	X	-
RT105	-	-	-	X	-	-	-	-	-	-
RT135	-	-	-	X	X	-	X	-	-	-
RT165	-	-	-	-	-	-	X	-	X	-
RT185	-	-	-	-	-	-	-	-	-	X
RT195	-	-	-	-	-	-	X	-	X	-
RT195	-	-	-	-	-	-	X	-	X	-
RT195	-	-	-	-	-	-	X	-	X	-
V210 - NEW	-	-	-	-	-	-	-	-	X	-
VT210 - NEW	-	-	-	-	-	-	-	-	-	X
AL140 OLD	X	-	-	-	-	-	-	-	-	-
MLA 1-25 H OLD	X	-	-	-	-	-	-	-	-	-
MLA 3-35 H OLD	-	-	X	-	-	-	-	-	-	-

Capacities		B4x1 1760 / 420 T	B4x1 1760 / 450 T	B4x1 1800 / 670 T	B4x1 1830 / 450 T (a)	B4x1 1830 / 450 T (b)	B4x1 1850 / 480 T	B4x1 1880 / 480 T	B4x1 1950 / 720 T	B4x1 2140 / 560 T (a)	B4x1 2140 / 560 T (b)
Heaped capacity (l)		420	450	670	450	450	480	480	720	560	560
Weight											
Overall weight (kg)		385	410	514	420	420	420	420	540	475	475
Weight and dimensions											
Overall height (mm)	h17	767	767	863	767	767	767	767	863	767	767
Width (mm)		1760	1760	1800	1830	1830	1850	1880	1950	2140	2140
Depth (mm)	p5	800	786	933	800	800	786	786	933	786	786
Working Parameters											
Machine Equipment											
Hydraulic system		-	-	-	-	-	-	-	-	-	-
Teeth		8	8	9	9	9	9	9	10	11	11

Machines compatibility	B4x1 1760 / 420 T	B4x1 1760 / 450 T	B4x1 1800 / 670 T	B4x1 1830 / 450 T (a)	B4x1 1830 / 450 T (b)	B4x1 1850 / 480 T	B4x1 1880 / 480 T	B4x1 1950 / 720 T	B4x1 2140 / 560 T (a)	B4x1 2140 / 560 T (b)
All-Tach® Narrow	-	-	-	-	-	-	-	-	-	-
All-Tach®	N51502477	N51502046	N51502524	N757025	N51502479	N51502047	N51502083	N51502523	N700256	N51502048
4 point Camage	-	-	N51502592	-	-	-	-	N51502594	-	-
Euro Camage	-	-	N51502551	-	-	-	-	N51502553	-	-
1850RT	-	X	-	-	-	X	-	-	-	-
2100V	-	-	-	-	X	-	X	-	-	-
2100VT	-	X	-	-	-	X	X	-	-	-
2150RT	-	-	-	-	-	X	-	-	-	X
2200R	X	-	-	-	X	-	X	-	-	-
2300V	X	-	-	-	X	-	-	-	-	-
2300VT	-	-	-	-	-	X	-	-	-	-
2600R	-	-	-	-	X	-	X	-	-	-
2700V NXT2	-	-	-	X	-	-	X	-	-	-
2750V	X	-	-	X	X	-	X	-	-	-
2750VT	-	-	-	-	-	X	-	-	-	X
3300V NXT2	-	-	-	X	-	-	X	-	X	-
4200V	-	-	-	-	-	-	-	-	X	-
AL650	-	-	X	-	-	-	-	X	-	-
AL750	-	-	X	-	-	-	-	X	-	-
MLA 6-65 H-Z	-	-	X	-	-	-	-	X	-	-
R220	X	-	-	-	X	-	X	-	-	-
R260	-	-	-	-	X	-	X	-	-	-
RT185	-	X	-	-	-	X	-	-	-	-
RT215	-	-	-	-	-	X	-	-	-	X
V210 - NEW	-	-	-	-	X	-	X	-	-	-
V230 - NEW	X	-	-	-	X	-	X	-	-	-
V275 - NEW	X	-	-	X	X	-	X	-	-	-
V330 GEN:2	-	-	-	X	-	-	X	-	X	-
V330 GEN:2	-	-	-	X	-	-	X	-	X	-
VT210 - NEW	-	X	-	-	-	X	-	-	-	-
VT230 - NEW	-	-	-	-	-	X	-	-	-	-
VT275 - NEW	-	-	-	-	-	X	-	-	-	X

Capacities		B4x1 2150 / 800 T
Heaped capacity (l)		820
Weight		
Overall weight (kg)		572
Weight and dimensions		
Overall height (mm)	h17	863
Width (mm)		2150
Depth (mm)	p5	933
Working Parameters		
Machine Equipment		
Hydraulic system		-
Teeth		11

Machines compatibility	B4x1 2150 / 800 T
All-Tach® Narrow	-
All-Tach®	N51502522
4 point Camage	N51502596
Euro Camage	N51502555
AL750	X

TABLE SYMBOL					
	No predisposition required		Hydraulic line		Return piping to hydraulic oil tank
	Electric predisposition		Platform predisposition		Tyre handler, cylinder handler predisposition



Head Office

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes