

Technical sheet :

CARRIAGE FLOATING LOAD BACKREST AND FORKS (MT - MLT)



Customer benefits

- Solution adapted to uneven ground : floating forks + leveling.

Technical characteristics

- Load backrest standard.
- Fork levelling.
- Fork travel lock possible - order kit ref. 52675100.
- Note: road circulation kit mandatory in Italy. Contact your dealer.
- Note: road circulation kit mandatory in Germany on MRT Vision/Vision+. Contact your dealer.

[The 3D picture at the top of this page is the reference CAF 1000 / 3 LB - 52654990].

Technical characteristics		CAF 1000 / 3 LB	CAF 1000 / 3 LB (b)	CAF 1000 / 1.5 LB	CAF 1000 / 4.1 LB	CAF 1300 / 4.1 LB
Distance to center of gravity (mm)		308	263	168	275	259
Capacities						
Capacity (kg)		3000	3000	1500	4100	4100
Weight						
Overall weight (kg)		240	254	175	306	355
Weight and dimensions						
Overall height (mm)	h17	989	989	1049	1036	1036
Overall length (mm)	l1	1359	1479	1384	1514	1514
Width (mm)		1002	1002	1156	1160	1420
Working Parameters						
Machine Equipment		×	×	×	×	×
Fork spread minimum (mm)	b5	244	284	160	493	245
Fork spread maximum (mm)	b5	924	924	927	1022	1282
Available fork dimensions						
100 x 50 x 1070		52654990				
75 x 35 x 1100				52693600		
120 x 40 x 1200			52744200			
100 x 50 x 1200					52722290	52810870

Machines compatibility	CAF 1000 / 3 LB	CAF 1000 / 3 LB (b)	CAF 1000 / 1.5 LB	CAF 1000 / 4.1 LB	CAF 1300 / 4.1 LB
Reference number	52654990	52744200	-	52722290	52810870
All-Tach®	-	-	52693600	-	-
4 point Carriage	-	-	52723634	-	-
Euro Carriage	-	-	52723635	-	-
AL230	-	-	X	-	-
AL320	-	-	X	-	-
AL330	-	-	X	-	-
AL420	-	-	X	-	-
AL430	-	-	X	-	-
AL530	-	-	X	-	-
GCT 3-14	-	-	X	-	-
GCT 3-14 +	-	-	X	-	-
MLA 2-25 H	-	-	X	-	-
MLA 3-25 H	-	-	X	-	-
MLA 3-25 H-C	-	-	X	-	-
MLA 4-50 H	-	-	X	-	-
MLA 4-50 H-C	-	-	X	-	-
MLA 5-50 H	-	-	X	-	-
MLT 420-60 H	X	X	-	-	-
MLT 625-75 H	X	X	-	-	-
MLT 733-115 LSU	-	-	-	X	-
MLT 737-130 PS+	-	-	-	X	-
MLT 741-130 PS+	-	-	-	X	-
MLT 741-140 V+	-	-	-	X	-
MLT 841-145 PS+	-	-	-	X	-
MLT 940-140 V+	-	-	-	X	-
MLT 1041-145 PS+L	-	-	-	X	-
MLT-X 625-75 H	X	X	-	-	-
MLT-X 732	-	-	-	X	-
MLT-X 735 T LSU	-	-	-	X	-
MLT-X 735 T LSU (70 KW)	-	-	-	X	-
MLT-X 737-130 PS+	-	-	-	X	-
MLT-X 841 - 145 PS+	-	-	-	X	-
MLT-X 1035 LT LSU	-	-	-	X	-
MLT-X 1041-145 PS+L	-	-	-	X	-
MT 420 H	X	X	-	-	-
MT 625 e	X	X	-	-	-
MT 625 H	X	X	-	-	-
MT 625 H Comfort	X	X	-	-	-
MT 625 HA	X	X	-	-	-
MT 730 H	X	X	-	-	-
MT 735 75D ST5	-	-	-	X	X
MT 930 H	X	X	-	-	-
MT 930 HA	X	X	-	-	-
MT 935 75D ST5	-	-	-	X	X
MT 1135 75 D	-	-	-	X	X
MT 1135 H 100D	-	-	-	X	X
MT 1335 75D ST5	-	-	-	X	X
MT 1335 100D ST5	-	-	-	X	X
MT 1335 H 75D ST5	-	-	-	X	X
MT 1335 H 100D ST5	-	-	-	X	X
MT 1440 A ST5	-	-	-	X	X
MT 1440 easy ST5	-	-	-	X	X
MT 1440 HA ST5	-	-	-	X	X
MT 1440 ST5	-	-	-	X	X
MT 1840 A 100D ST5 S1	-	-	-	X	X
MT 1840 easy ST5	-	-	-	X	X
MT 1840 HA	-	-	-	X	X
MT 1840 ST5	-	-	-	X	X

Machines compatibility	CAF 1000 / 3 LB	CAF 1000 / 3 LB (b)	CAF 1000 / 1.5 LB	CAF 1000 / 4.1 LB	CAF 1300 / 4.1 LB
MT-X 420 H	X	X	-	-	-
MT-X 733	-	-	-	X	X
MT-X 1033	-	-	-	X	X
MT-X 1440	-	-	-	X	X
MT-X 1440 A	-	-	-	X	X
MT-X 1840	-	-	-	X	X
MT-X 1840 A	-	-	-	X	X
ULM 412 H	-	-	X	-	-
ULM 412 H	-	-	X	-	-
ULM 415 H	-	-	X	-	-
ULM 415 H	-	-	X	-	-
MLA 4-50 H OLD	-	-	X	-	-
MLT 733-115 OLD	-	-	-	X	-
MLT 733-115 LSU ST4 OLD	-	-	-	X	-
MLT 733-115 ST4 OLD	-	-	-	X	-
MLT 737-130 PS+ ST4 OLD	-	-	-	X	-
MLT 741-140 V+ ST4 OLD	-	-	-	X	-
MLT 940-140 V+ ST4 OLD	-	-	-	X	-
MLT-X 737-130 PS+ OLD	-	-	-	X	-
MLT-X 741-140 V+ S1 OLD	-	-	-	X	-
MT 733 Easy OLD	-	-	-	-	X
MT 933 Easy OLD	-	-	-	X	X
MT 1033 easy OLD	-	-	-	X	X
MT 1135 OLD	-	-	-	X	-
MT 1135 easy ST5 OLD	-	-	-	X	X
MT 1135 H easy ST5 OLD	-	-	-	X	X
MT 1135 HA Easy ST5 OLD	-	-	-	X	X
MT 1135 ST5 OLD	-	-	-	X	X
MT 1335 OLD	-	-	-	X	X
MT 1335 easy ST5 OLD	-	-	-	X	X
MT 1335 H easy ST5 OLD	-	-	-	X	X
MT 1335 HA easy ST5 OLD	-	-	-	X	-
MT 1335 ST5 OLD	-	-	-	X	X
MT 1440 OLD	-	-	-	X	-
MT 1440 A OLD	-	-	-	X	X
MT 1440 HA OLD	-	-	-	X	X
MT 1840 OLD	-	-	-	X	-
MT 1840 A OLD	-	-	-	X	X
MT 1840 HA OLD	-	-	-	X	X

TABLE SYMBOL

	No predisposition required		Hydraulic line		Return piping to hydraulic oil tank
	Electric predisposition		Platform predisposition		Tyre handler, cylinder handler predisposition



Head Office

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes