

Technical sheet :

COLD PLANER WITH SIDE SHIFT




Customer benefits







- Designed to carry out road maintenance work, to remove a layer of asphalt or concrete.
- Possibility to reuse the removed material for the subsequent filling of the excavation or for the restoration of the road surface itself.

Technical characteristics

- Manual side shift for milling flush to the wall easily.
- Manual depth adjustment with independent left or right side movement in order to perform side-by-side passes with high precision but also to remove only the necessary layer of asphalt.
- 2 wheels on the frame and 2 front slides for stability and less vibrations.
- Asphalt teeth in standard.
- Easy tooth removal for easy maintenance.
- [The 3D picture at the top of this page is the reference PLC 400 SK - 52832870]

Weight		PLC 400 SK
Overall weight (kg)		505
Weight and dimensions		
Overall height (mm)	h17	830
Overall length (mm)	l1	1098
Width (mm)		1500
Working Parameters		
Required machine equipment		
Depth adjustment		manual
Maximum depth (mm)		125
Side shift		Yes
Side shift type		manual
Maximum outreach side shift (mm)		600
Working width (mm)		400
Number of tooth		48
Minimum hydraulic requirements (l/min)		45
Maximum hydraulic requirements (l/min)		80
Water sprayer		No
Other Data for Attachments		
Connection system		Universal Quick-attach
E-RECO		No

Machines compatibility	PLC 400 SK
All-Tach®	52832870
2100V	X
2100VT	X
2300V	X
2300VT	X
2750V	X
V210	X
V230	X
V275	X
VT210	X
VT230	X

TABLE SYMBOL					
	No predisposition required		Hydraulic line		Return piping to hydraulic oil tank
	Electric predisposition		Platform predisposition		Tyre handler, cylinder handler predisposition



Head Office

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes