Technical sheet :

CONCRETE MIXING BUCKET

Technical characteristics

- Hydraulic side discharge bucket that ensures an easy and safe unloading for the operator.
- Bolted helix made of wear steel HB400 for a consistent mix from one side to the other.
- Equipped with an unloading pipe that the operator connects at the side of the bucket for even more safety and precision.
- Featured with a galvanized rounded protection grid with bag splitter.

  [The 3D picture at the top of this page is the reference BMC 1495/250 SK - 52832877].

Customer benefits

- The Concrete Mixing Bucket is designed to load, mix, transport and unload concrete quickly and easily.
- Ideal attachment for industries requiring small quantities of concrete on a daily basis.
- Easy to use & time saving : the operator can get out of the cab while the concrete mixing bucket is running.
- Profitability : the operator mixes just enough concrete for what he needs.
- Safety : the operator can easily work along a wall or a sidewalk and his presence is not required underneath the bucket.

	BMC 1495/250	BMC 1605/330
Reference number	52832877	52832878
Struck capacity (l)	250	330
Overall weight (kg)	415	435
Height (mm)	800	800
Length (mm)	860	860
Width (mm)	1495	1605
Required machine equipment		
Pipe / chute	Flexible pipe	Flexible pipe
Opening location	Central	Central
Cutting edge	No	No
Min. hydraulic requirements (l/min)	40	35
Max. hydraulic requirements (l/min)	75	75
Opening type	Hydraulic	Hydraulic
E-RECO	No	No
Connection system	Universal Quick-attach	Universal Quick-attach

Machines compatibility		
2300V	X	-
2300V	X	-
2300VT	X	-
2300VT	X	-
2750V	-	X
2750V	-	X
2750VT	-	X
2750VT	-	X
V230	X	-
V230	X	-
V275	-	X
V275	-	X
VT230	X	-
VT230	X	-
VT275	-	X
VT275	-	X

TABLE SYMBOL					
	No predisposition required		Hydraulic line		Return piping to hydraulic oil tank
	Electric predisposition		Platform predisposition		Tyre handler, cylinder handler predisposition

Head Office
B.P. 249 - 430 rue de l'Aubinière
44150 Ancenis Cedex - France
Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97
www.manitou.com

This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.
MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes