

Technical sheet :

# DEEP EXTENSIBLE PLATFORM







## Customer benefits

- Interesting for asbestos removal and 2nd fix applications- easy access & significant space to place tiles.







## Technical characteristics

- 2 m / 7 ft deep platform to facilitate the handling of bulky loads in the platform.

**MANITOU** GROUP ATTACHMENTS

Technical characteristics		NAC 2.2.5 / 4m 1000kg	ORH 2.2.5 / 4m 700kg	PFE 4000 / 1000 FD	PSE 4000 / 700 FD
Capacity including people (kg)		1000	700	1000	700
Number of people		3	3	3	3
<b>Weight</b>					
Overall weight (kg)		1000	1300	1000	1300
<b>Weight and dimensions</b>					
Overall height (mm)	h17	1290	1290	1669	1669
Overall length (mm)	l1	2615	2855	2615	2855
Width minimum (mm)		2500	2500	2500	2500
Width maximum (mm)		4046	4046	4000	4046
Depth (mm)	p5	1920	1920	1920	1920
<b>Working Parameters</b>					
Machine Equipment					
Rotation 1 (°)		-	40	-	40
Rotation 2 (°)		-	40	-	40
Working outreach (mm)		2000	2000	2000	2000

Machines compatibility		NAC 2.2.5 / 4m 1000kg	ORH 2.2.5 / 4m 700kg	PFE 4000 / 1000 FD	PSE 4000 / 700 FD
Reference number E-RECO		921355	921358	52719265	52719266
MRT 1645 75		-	-	X	X
MRT 1645 115		-	-	X	X
MRT 1845 75		-	-	X	X
MRT 1845 115		-	-	X	X
MRT 2145 115		-	-	X	X
MRT 2260		-	-	X	X
MRT 2260 e		-	-	X	X
MRT 2545 115		-	-	X	X
MRT 2570		-	-	X	X
MRT 2660		-	-	X	X
MRT 2660 e		-	-	X	X
MRT 3060		-	-	X	X
MRT 3570		-	-	X	X
MRT 3570 ES		-	-	X	X
MRT-X 1645		-	-	X	X
MRT-X 1845		-	-	X	X
MRT-X 2145		-	-	X	X
MRT-X 2260		-	-	X	X
MRT-X 2545		-	-	X	X
MRT-X 2570		-	-	X	X
MRT-X 2660		-	-	X	X
MRT-X 3060		-	-	X	X
MRT-X 3570		-	-	X	X
MRT-X 3570 ES		-	-	X	X
MRT 2145 Easy T4 S2 360° <b>OLD</b>		X	X	-	-
MRT 2145 Easy T4 S2 400° <b>OLD</b>		X	X	-	-
MRT 2150 Privilege Plus <b>OLD</b>		X	X	-	-
MRT 2470 Privilege Plus <b>OLD</b>		X	X	-	-
MRT 2545 Easy T4 S2 360° <b>OLD</b>		X	X	-	-
MRT 2545 Easy T4 S2 400° <b>OLD</b>		X	X	-	-
MRT 2550 Privilege Plus <b>OLD</b>		X	X	-	-
MRT 3050 Privilege Plus <b>OLD</b>		X	X	-	-
MRT-X 2145 Easy 360° <b>OLD</b>		X	X	-	-
MRT-X 2145 Easy 400° <b>OLD</b>		X	X	-	-
MRT-X 2150 Privilege Plus <b>OLD</b>		X	X	-	-
MRT-X 2470 Privilege Plus <b>OLD</b>		X	X	-	-
MRT-X 2545 Easy 360° <b>OLD</b>		X	X	-	-
MRT-X 2545 Easy 400° <b>OLD</b>		X	X	-	-
MRT-X 2550 Privilege Plus <b>OLD</b>		X	X	-	-
MRT-X 3050 Privilege Plus <b>OLD</b>		X	X	-	-

TABLE SYMBOL					
	No predisposition required		Hydraulic line		Return piping to hydraulic oil tank
	Electric predisposition		Platform predisposition		Tyre handler, cylinder handler predisposition



**Head Office**

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

[www.manitou.com](http://www.manitou.com)



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes