

Technical sheet :

DEEP EXTENSIBLE PLATFORM



Technical characteristics

- 2 m / 7 ft deep platform to facilitate the handling of bulky loads in the platform.

Customer benefits

- Interesting for asbestos removal and 2nd fix applications- easy access & significant space to place tiles.

| Technical characteristics | | NAC 2.2.5 / 4m 1000kg | ORH 2.2.5 / 4m 700kg | PFE 4000 / 1000 FD | PSE 4000 / 700 FD |
|--------------------------------|-----|---|---|---|---|
| Capacity including people (kg) | | 1000 | 700 | 1000 | 700 |
| Number of people | | 3 | 3 | 3 | 3 |
| Weight | | | | | |
| Overall weight (kg) | | 1000 | 1300 | 1000 | 1300 |
| Weight and dimensions | | | | | |
| Overall height (mm) | h17 | 1290 | 1290 | 1669 | 1669 |
| Overall length (mm) | l1 | 2615 | 2855 | 2615 | 2855 |
| Width minimum (mm) | | 2500 | 2500 | 2500 | 2500 |
| Width maximum (mm) | | 4046 | 4046 | 4000 | 4046 |
| Depth (mm) | p5 | 1920 | 1920 | 1920 | 1920 |
| Working Parameters | | | | | |
| Required machine equipment | |  |  |  |  |
| Rotation 1 (°) | | - | 40 | - | 40 |
| Rotation 2 (°) | | - | 40 | - | 40 |
| Working outreach (mm) | | 2000 | 2000 | 2000 | 2000 |

| Machines compatibility | NAC 2.2.5 / 4m 1000kg | ORH 2.2.5 / 4m 700kg | PFE 4000 / 1000 FD | PSE 4000 / 700 FD |
|--------------------------------------|-----------------------|----------------------|--------------------|-------------------|
| Reference number E-RECO | 921355 | 921358 | 52719265 | 52719266 |
| MRT 1645 75 | - | - | X | X |
| MRT 1645 115 | - | - | X | X |
| MRT 1845 75 | - | - | X | X |
| MRT 1845 115 | - | - | X | X |
| MRT 2145 115 | - | - | X | X |
| MRT 2260 | - | - | X | X |
| MRT 2260 e | - | - | X | X |
| MRT 2545 115 | - | - | X | X |
| MRT 2570 | - | - | X | X |
| MRT 2660 | - | - | X | X |
| MRT 2660 e | - | - | X | X |
| MRT 3060 | - | - | X | X |
| MRT 3570 | - | - | X | X |
| MRT 3570 ES | - | - | X | X |
| MRT-X 1645 | - | - | X | X |
| MRT-X 1845 | - | - | X | X |
| MRT-X 2145 | - | - | X | X |
| MRT-X 2260 | - | - | X | X |
| MRT-X 2545 | - | - | X | X |
| MRT-X 2570 | - | - | X | X |
| MRT-X 2660 | - | - | X | X |
| MRT-X 3060 | - | - | X | X |
| MRT-X 3570 | - | - | X | X |
| MRT-X 3570 ES | - | - | X | X |
| MRT 2145 Easy T4 S2 360° OLD | X | X | - | - |
| MRT 2145 Easy T4 S2 400° OLD | X | X | - | - |
| MRT 2150 Privilege Plus OLD | X | X | - | - |
| MRT 2470 Privilege Plus OLD | X | X | - | - |
| MRT 2545 Easy T4 S2 360° OLD | X | X | - | - |
| MRT 2545 Easy T4 S2 400° OLD | X | X | - | - |
| MRT 2550 Privilege Plus OLD | X | X | - | - |
| MRT 3050 Privilege Plus OLD | X | X | - | - |
| MRT-X 2145 Easy 360° OLD | X | X | - | - |
| MRT-X 2145 Easy 400° OLD | X | X | - | - |
| MRT-X 2150 Privilege Plus OLD | X | X | - | - |
| MRT-X 2470 Privilege Plus OLD | X | X | - | - |
| MRT-X 2545 Easy 360° OLD | X | X | - | - |
| MRT-X 2545 Easy 400° OLD | X | X | - | - |
| MRT-X 2550 Privilege Plus OLD | X | X | - | - |
| MRT-X 3050 Privilege Plus OLD | X | X | - | - |

| TABLE SYMBOL | | | | | |
|---|----------------------------|---|-------------------------|---|---|
|  | No predisposition required |  | Hydraulic line |  | Return piping to hydraulic oil tank |
|  | Electric predisposition |  | Platform predisposition |  | Tyre handler, cylinder handler predisposition |



Head Office

B.P. 249 - 430 rue de l'Aubinière
44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes