

Technical sheet :

DOZER BLADE (COMPACT MACHINES)



Technical characteristics

- Orientation: mechanical or hydraulic (2 cylinders).
- Bolt-on wear plate.

Customer benefits

- For all material pushing applications.

Weight		BLD 1525	BLD 1980	BLD 2135
Overall weight (kg)		240	450	470
Weight and dimensions				
Overall height (mm)	h17	677	677	677
Width (mm)		1525	1980	2135
Depth (mm)	p5	813	933	933

Machines compatibility	BLD 1525	BLD 1980	BLD 2135
All-Tach®	N700396	N51502067	N51502068
4 point Carriage	N750996	-	-
Euro Carriage	N51502207	-	-
AL420	X	-	-
AL430	X	-	-
AL530	X	-	-
MLA 4-50 H	X	-	-
MLA 4-50 H-C	X	-	-
MLA 5-50 H	X	-	-
MLA 4-50 H OLD	X	-	-

TABLE SYMBOL					
	No predisposition required		Hydraulic line		Return piping to hydraulic oil tank
	Electric predisposition		Platform predisposition		Tyre handler, cylinder handler predisposition



Head Office

B.P. 249 - 430 rue de l'Aubinière

44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes