Technical sheet :

DOZER BLADE (COMPACT MACHINES)



Customer benefits

- For all material pushing applications.

Technical characteristics

Orientation: mechanical or hydraulic (2 cylinders).Bolt-on wear plate.

MANITOU ATTACHMENTS

DOZER BLADE (COMPACT MACHINES) Created on 3 May 2024 at 10:27:02 pm UTC

Weight		BLD 1525	BLD 1980	BLD 2135
Overall weight (kg)		240	450	470
Weight and dimensions				
Overall height (mm)	h17	677	677	677
Width (mm)		1525	1980	2135
Depth (mm)	р5	813	933	933
Working Parameters				
Machine Equipment		×		
Horizontal angle (°)		18	30	30

Machines compatibility	BLD 1525	BLD 1980	BLD 2135
All-Tach®	N700396	N51502067	N51502068
4 point Carriage Euro Carriage	N750996	-	-
Euro Carriage	N51502207	-	-
AL420	х		•
AL430	х		
AL530	х		
MLA 4-50 H	х		
MLA 4-50 H-C	х		•
MLA 5-50 H	X	•	
MLA 4-50 H OLD	Х		

TABLE SYMBOL							
\times	No predisposition required	₽₽	Hydraulic line		Retum piping to hydraulic oil tank		
	Electric predisposition		Platform predisposition		Tyre handler, cylinder handler predisposition		





This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes