

Technical sheet :

DOZER BLADE - MANUAL (COMPACT MACHINES)



Technical characteristics

- Orientation: mechanical or hydraulic (2 cylinders).
- Bolt-on wear plate.

Customer benefits

- For all material pushing applications.

| Weight | | BLD 1080 | BLD 1480 | BLD 1800 (a) | BLD 1800 (b) | BLD 2000 (a) | BLD 2000 (b) |
|-----------------------|-----|----------|----------|--------------|--------------|--------------|--------------|
| Overall weight (kg) | | 135 | 185 | 205 | 205 | 288 | 288 |
| Weight and dimensions | | | | | | | |
| Overall height (mm) | h17 | 677 | 677 | 677 | 677 | 677 | 677 |
| Width (mm) | | 1080 | 1480 | 1800 | 1800 | 2000 | 2000 |
| Depth (mm) | p5 | 813 | 813 | 813 | 813 | 813 | 813 |

| Machines compatibility | | BLD 1080 | BLD 1480 | BLD 1800 (a) | BLD 1800 (b) | BLD 2000 (a) | BLD 2000 (b) |
|------------------------|--|----------|----------|--------------|--------------|--------------|--------------|
| All-Tach® | | N726032 | N736036 | N51502488 | N757041 | N51502489 | N757042 |
| 850R | | X | - | - | - | - | - |
| 1050R | | - | X | - | - | - | - |
| 1050RT | | - | X | - | - | - | - |
| 1350R NXT2 | | - | X | - | - | - | - |
| 1350RT | | - | X | - | - | - | - |
| 1650R | | - | - | X | - | - | - |
| 1650RT | | - | - | - | X | - | - |
| 1950RT | | - | - | - | X | - | - |
| 1950RT | | - | - | - | X | - | - |
| 1950RT | | - | - | - | X | - | - |
| 1950RT | | - | - | - | X | - | - |
| 2100V | | - | - | - | X | - | - |
| 2300V | | - | - | - | X | - | - |
| 2750V | | - | - | - | - | X | - |
| R105 | | - | X | - | - | - | - |
| R165 | | - | - | X | - | - | - |
| RT105 | | - | X | - | - | - | - |
| RT135 | | - | X | - | - | - | - |
| RT165 | | - | - | - | X | - | - |
| RT195 - NEW | | - | - | - | X | - | - |
| RT195 - NEW | | - | - | - | X | - | - |
| RT195 - NEW | | - | - | - | X | - | - |
| V210 | | - | - | - | X | - | - |
| V230 | | - | - | - | X | - | - |
| V275 | | - | - | - | - | X | - |
| 1640E OLD | | X | - | - | - | - | - |
| 1900R OLD | | - | - | - | X | - | - |
| 2200R OLD | | - | - | - | X | - | - |
| 2600R OLD | | - | - | - | X | - | X |
| 2700V NXT2 OLD | | - | - | - | - | X | - |
| R220 OLD | | - | - | - | X | - | - |
| R260 OLD | | - | - | - | X | - | X |
| V270 OLD | | - | - | - | - | X | - |

| TABLE SYMBOL | | | | | |
|---|----------------------------|---|-------------------------|---|---|
|  | No predisposition required |  | Hydraulic line |  | Return piping to hydraulic oil tank |
|  | Electric predisposition |  | Platform predisposition |  | Tyre handler, cylinder handler predisposition |



Head Office

B.P. 249 - 430 rue de l'Aubinière
44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes